
MushroomRL Documentation

Release 1.5.3

Carlo D'Eramo, Davide Tateo

Sep 28, 2020

1 Reinforcement Learning python library	1
2 Basic run example	3
3 Download and installation	5
3.1 Agent-Environment Interface	5
3.2 Actor-Critic	11
3.3 Policy search	27
3.4 Value-Based	37
3.5 Approximators	66
3.6 Distributions	73
3.7 Environments	81
3.8 Features	105
3.9 Policy	110
3.10 Solvers	139
3.11 Utils	142
3.12 How to make a simple experiment	170
3.13 How to make an advanced experiment	171
3.14 How to create a regressor	173
3.15 How to make a deep RL experiment	175
Python Module Index	183
Index	185

CHAPTER 1

Reinforcement Learning python library

MushroomRL is a Reinforcement Learning (RL) library that aims to be a simple, yet powerful way to make **RL** and **deep RL** experiments. The idea behind Mushroom consists in offering the majority of RL algorithms providing a common interface in order to run them without excessive effort. Moreover, it is designed in such a way that new algorithms and other stuff can generally be added transparently without the need of editing other parts of the code. MushroomRL makes a large use of the environments provided by [OpenAI Gym](#), [DeepMind Control Suite](#) and [MuJoCo](#) libraries, and the [PyTorch](#) library for tensor computation.

With MushroomRL you can:

- solve RL problems simply writing a single small script;
- add custom algorithms and other stuff transparently;
- use all RL environments offered by well-known libraries and build customized environments as well;
- exploit regression models offered by Scikit-Learn or build a customized one with PyTorch;
- run experiments on GPU.

CHAPTER 2

Basic run example

Solve a discrete MDP in few a lines. Firstly, create a **MDP**:

```
from mushroom_rl.environments import GridWorld
mdp = GridWorld(width=3, height=3, goal=(2, 2), start=(0, 0))
```

Then, an epsilon-greedy **policy** with:

```
from mushroom_rl.policy import EpsGreedy
from mushroom_rl.utils.parameters import Parameter

epsilon = Parameter(value=1.)
policy = EpsGreedy(epsilon=epsilon)
```

Eventually, the **agent** is:

```
from mushroom_rl.algorithms.value import QLearning

learning_rate = Parameter(value=.6)
agent = QLearning(mdp.info, policy, learning_rate)
```

Learn:

```
from mushroom_rl.core.core import Core

core = Core(agent, mdp)
core.learn(n_steps=10000, n_steps_per_fit=1)
```

Print final Q-table:

```
import numpy as np

shape = agent.Q.shape
q = np.zeros(shape)
```

(continues on next page)

(continued from previous page)

```
for i in range(shape[0]):  
    for j in range(shape[1]):  
        state = np.array([i])  
        action = np.array([j])  
        q[i, j] = agent.Q.predict(state, action)  
print(q)
```

Results in:

```
[[ 6.561   7.29   6.561   7.29 ]  
 [ 7.29    8.1    6.561   8.1   ]  
 [ 8.1     9.     7.29   8.1   ]  
 [ 6.561   8.1    7.29   8.1   ]  
 [ 7.29    9.     7.29   9.    ]  
 [ 8.1     10.    8.1    9.    ]  
 [ 7.29    8.1    8.1    9.    ]  
 [ 8.1     9.     8.1    10.   ]  
 [ 0.      0.     0.     0.    ]]
```

where the Q-values of each action of the MDP are stored for each rows representing a state of the MDP.

CHAPTER 3

Download and installation

MushroomRL can be downloaded from the [GitHub](#) repository. Installation can be done running

```
pip3 install mushroom_rl
```

To compile the documentation:

```
cd mushroom_rl/docs  
make html
```

or to compile the pdf version:

```
cd mushroom_rl/docs  
make latexpdf
```

To launch MushroomRL test suite:

```
pytest
```

3.1 Agent-Environment Interface

The three basic interface of mushroom_rl are the Agent, the Environment and the Core interface.

- The `Agent` is the basic interface for any Reinforcement Learning algorithm.
- The `Environment` is the basic interface for every problem/task that the agent should solve.
- The `Core` is a class used to control the interaction between an agent and an environment.

To implement serialization of MushroomRL data on the disk (load/save functionality) we also provide the `Serializable` interface.

3.1.1 Agent

MushroomRL provides the implementations of several algorithms belonging to all categories of RL:

- value-based;
- policy-search;
- actor-critic.

One can easily implement customized algorithms following the structure of the already available ones, by extending the following interface:

```
class mushroom_rl.algorithms.agent.Agent(mdp_info, policy, features=None)
Bases: mushroom_rl.core.serialization.Serializable
```

This class implements the functions to manage the agent (e.g. move the agent following its policy).

```
__init__(mdp_info, policy, features=None)
Constructor.
```

Parameters

- **mdp_info** (`MDPInfo`) – information about the MDP;
- **policy** (`Policy`) – the policy followed by the agent;
- **features** (`object`, `None`) – features to extract from the state.

```
fit(dataset)
Fit step.
```

Parameters `dataset` (`list`) – the dataset.

```
draw_action(state)
```

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state` (`np.ndarray`) – the state where the agent is.

Returns The action to be executed.

```
episode_start()
```

Called by the agent when a new episode starts.

```
stop()
```

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
_add_save_attr(**attr_dict)
```

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

```
_post_load()
```

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
copy()
```

Returns A deepcopy of the agent.

```
classmethod load(path)
```

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=’’*)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where the object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ‘’*) – subfolder to be used by the save method.

3.1.2 Environment

MushroomRL provides several implementation of well known benchmarks with both continuous and discrete action spaces.

To implement a new environment, it is mandatory to use the following interface:

class `mushroom_rl.environments.environment.MDPInfo` (*observation_space, action_space, gamma, horizon*)

Bases: `object`

This class is used to store the information of the environment.

__init__ (*observation_space, action_space, gamma, horizon*)

Constructor.

Parameters

- `observation_space` (`[Box, Discrete]`) – the state space;
- `action_space` (`[Box, Discrete]`) – the action space;
- `gamma` (`float`) – the discount factor;
- `horizon` (`int`) – the horizon.

size

The sum of the number of discrete states and discrete actions. Only works for discrete spaces.

Type Returns

shape

The concatenation of the shape tuple of the state and action spaces.

Type Returns

class `mushroom_rl.environments.environment.Environment` (*mdp_info*)

Bases: `object`

Basic interface used by any mushroom environment.

__init__(mdp_info)

Constructor.

Parameters `mdp_info` ([MDP Info](#)) – an object containing the info of the environment.

seed(seed)

Set the seed of the environment.

Parameters `seed` (*float*) – the value of the seed.

reset(state=None)

Reset the current state.

Parameters `state` (*np.ndarray*, *None*) – the state to set to the current state.

Returns The current state.

step(action)

Move the agent from its current state according to the action.

Parameters `action` (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing `action` in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

info

An object containing the info of the environment.

Type Returns

static _bound(x, min_value, max_value)

Method used to bound state and action variables.

Parameters

- `x` – the variable to bound;
- `min_value` – the minimum value;
- `max_value` – the maximum value;

Returns The bounded variable.

3.1.3 Core

```
class mushroom_rl.core.core.Core(agent, mdp, callbacks_fit=None, callback_step=None, preprocessors=None)
```

Bases: `object`

Implements the functions to run a generic algorithm.

__init__(agent, mdp, callbacks_fit=None, callback_step=None, preprocessors=None)

Constructor.

Parameters

- `agent` ([Agent](#)) – the agent moving according to a policy;
- `mdp` ([Environment](#)) – the environment in which the agent moves;

- **callbacks_fit** (*list*) – list of callbacks to execute at the end of each fit;
- **callback_step** (*Callback*) – callback to execute after each step;
- **preprocessors** (*list*) – list of state preprocessors to be applied to state variables before feeding them to the agent.

learn (*n_steps=None*, *n_episodes=None*, *n_steps_per_fit=None*, *n_episodes_per_fit=None*, *render=False*, *quiet=False*)

This function moves the agent in the environment and fits the policy using the collected samples. The agent can be moved for a given number of steps or a given number of episodes and, independently from this choice, the policy can be fitted after a given number of steps or a given number of episodes. By default, the environment is reset.

Parameters

- **n_steps** (*int*, *None*) – number of steps to move the agent;
- **n_episodes** (*int*, *None*) – number of episodes to move the agent;
- **n_steps_per_fit** (*int*, *None*) – number of steps between each fit of the policy;
- **n_episodes_per_fit** (*int*, *None*) – number of episodes between each fit of the policy;
- **render** (*bool*, *False*) – whether to render the environment or not;
- **quiet** (*bool*, *False*) – whether to show the progress bar or not.

evaluate (*initial_states=None*, *n_steps=None*, *n_episodes=None*, *render=False*, *quiet=False*)

This function moves the agent in the environment using its policy. The agent is moved for a provided number of steps, episodes, or from a set of initial states for the whole episode. By default, the environment is reset.

Parameters

- **initial_states** (*np.ndarray*, *None*) – the starting states of each episode;
- **n_steps** (*int*, *None*) – number of steps to move the agent;
- **n_episodes** (*int*, *None*) – number of episodes to move the agent;
- **render** (*bool*, *False*) – whether to render the environment or not;
- **quiet** (*bool*, *False*) – whether to show the progress bar or not.

_step (*render*)

Single step.

Parameters **render** (*bool*) – whether to render or not.

Returns A tuple containing the previous state, the action sampled by the agent, the reward obtained, the reached state, the absorbing flag of the reached state and the last step flag.

reset (*initial_states=None*)

Reset the state of the agent.

_preprocess (*state*)

Method to apply state preprocessors.

Parameters **state** (*np.ndarray*) – the state to be preprocessed.

Returns The preprocessed state.

3.1.4 Serialization

```
class mushroom_rl.core.serialization.Serializable
Bases: object
```

Interface to implement serialization of a MushroomRL object. This provide load and save functionality to save the object in a zip file. It is possible to save the state of the agent with different levels of

```
save(path, full_save=False)
```

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

```
save_zip(zip_file, full_save, folder="")
```

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

```
classmethod load(path)
```

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

```
copy()
```

Returns A deepcopy of the agent.

```
_add_save_attr(**attr_dict)
```

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

```
_post_load()
```

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
__init__
```

Initialize self. See help(type(self)) for accurate signature.

3.2 Actor-Critic

3.2.1 Classical Actor-Critic Methods

```
class mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPDAC_Q(mdp_info,
    pol-
    icy,
    mu,
    al-
    pha_theta,
    al-
    pha_omega,
    al-
    pha_v,
    value_function_features=None,
    pol-
    icy_features=None)
```

Bases: *mushroom_rl.algorithms.agent.Agent*

Compatible off-policy deterministic actor-critic algorithm. “Deterministic Policy Gradient Algorithms”. Silver D. et al.. 2014.

```
__init__(mdp_info, policy, mu, alpha_theta, alpha_omega, alpha_v, value_function_features=None,
        policy_features=None)
```

Constructor.

Parameters

- **mu** ([Regressor](#)) – regressor that describe the deterministic policy to be learned i.e., the deterministic mapping between state and action.
- **alpha_theta** ([Parameter](#)) – learning rate for policy update;
- **alpha_omega** ([Parameter](#)) – learning rate for the advantage function;
- **alpha_v** ([Parameter](#)) – learning rate for the value function;
- **value_function_features** ([Features](#), `None`) – features used by the value function approximator;
- **policy_features** ([Features](#), `None`) – features used by the policy.

```
fit(dataset)
```

Fit step.

Parameters **dataset** (*list*) – the dataset.

```
_add_save_attr(**attr_dict)
```

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

```
_post_load()
```

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
copy()
```

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.actor_critic.classic_actor_critic.StochasticAC(mdp_info,
    policy,
    alpha_theta,
    alpha_v,
    lambda_par=0.9,
    value_function_features=None,
    policy_features=None)
```

Bases: *mushroom_rl.algorithms.agent.Agent*

Stochastic Actor critic in the episodic setting as presented in: “Model-Free Reinforcement Learning with Continuous Action in Practice”. Degris T. et al.. 2012.

```
__init__(mdp_info, policy, alpha_theta, alpha_v, lambda_par=0.9, value_function_features=None,
        policy_features=None)
```

Constructor.

Parameters

- **alpha_theta** (`Parameter`) – learning rate for policy update;
- **alpha_v** (`Parameter`) – learning rate for the value function;
- **lambda_par** (`float, 9`) – trace decay parameter;
- **value_function_features** (`Features, None`) – features used by the value function approximator;
- **policy_features** (`Features, None`) – features used by the policy.

episode_start()

Called by the agent when a new episode starts.

fit (dataset)

Fit step.

Parameters `dataset` (`list`) – the dataset.

_add_save_attr (attr_dict)**

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action (state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state` (`np.ndarray`) – the state where the agent is.

Returns The action to be executed.

classmethod load (path)

Load and deserialize the agent from the given location on disk.

Parameters `path` (`Path, string`) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (`Path, str`) – Relative or absolute path to the object save location;
- **full_save** (`bool`) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (zip_file, full_save, folder=”)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (`ZipFile`) – ZipFile where te object needs to be saved;

- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ' ') – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.actor_critic.classic_actor_critic.StochasticAC_AVG (mdp_info,  
                                pol-  
                                icy,  
                                al-  
                                pha_theta,  
                                al-  
                                pha_v,  
                                al-  
                                pha_r,  
                                lambda_par=0.9,  
                                value_function_  
                                pol-  
                                icy_features=N
```

Bases: mushroom_rl.algorithms.actor_critic.classic_actor_critic.
stochastic_ac.StochasticAC

Stochastic Actor critic in the average reward setting as presented in: “Model-Free Reinforcement Learning with Continuous Action in Practice”. Degrif T. et al.. 2012.

__init__ (*mdp_info*, *policy*, *alpha_theta*, *alpha_v*, *alpha_r*, *lambda_par=0.9*,
value_function_features=None, *policy_features=None*)
Constructor.

Parameters **alpha_r** ([Parameter](#)) – learning rate for the reward trace.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

3.2.2 Deep Actor-Critic Methods

```
class mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC (mdp_info, policy, actor_optimizer, parameters)
```

Bases: *mushroom_rl.algorithms.agent.Agent*

Base class for algorithms that uses the reparametrization trick, such as SAC, DDPG and TD3.

__init__(mdp_info, policy, actor_optimizer, parameters)

Constructor.

Parameters

- **actor_optimizer** (*dict*) – parameters to specify the actor optimizer algorithm;
- **parameters** – policy parameters to be optimized.

fit(dataset)

Fit step.

Parameters **dataset** (*list*) – the dataset.

_optimize_actor_parameters(loss)

Method used to update actor parameters to maximize a given loss.

Parameters **loss** (*torch.tensor*) – the loss computed by the algorithm.

_add_save_attr (**attr_dict)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.actor_critic.deep_actor_critic.**A2C** (*mdp_info, policy, actor_optimizer, critic_params, ent_coeff, max_grad_norm=None, critic_fit_params=None*)

Bases: `mushroom_rl.algorithms.actor_critic.deep_actor_critic.deep_actor_critic.DeepAC`

Advantage Actor Critic algorithm (A2C). Synchronous version of the A3C algorithm. “Asynchronous Methods for Deep Reinforcement Learning”. Mnih V. et. al.. 2016.

`__init__(mdp_info, policy, actor_optimizer, critic_params, ent_coeff, max_grad_norm=None, critic_fit_params=None)`
Constructor.

Parameters

- `policy` (`TorchPolicy`) – torch policy to be learned by the algorithm;
- `actor_optimizer` (`dict`) – parameters to specify the actor optimizer algorithm;
- `critic_params` (`dict`) – parameters of the critic approximator to build;
- `ent_coeff` (`float, 0`) – coefficient for the entropy penalty;
- `max_grad_norm` (`float, None`) – maximum norm for gradient clipping. If None, no clipping will be performed, unless specified otherwise in actor_optimizer;
- `critic_fit_params` (`dict, None`) – parameters of the fitting algorithm of the critic approximator.

`fit(dataset)`
Fit step.

Parameters `dataset` (`list`) – the dataset.

`_post_load()`
This method can be overwritten to implement logic that is executed after the loading of the agent.

`_add_save_attr(**attr_dict)`
Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

`_optimize_actor_parameters(loss)`
Method used to update actor parameters to maximize a given loss.

Parameters `loss` (`torch.tensor`) – the loss computed by the algorithm.

`copy()`

Returns A deepcopy of the agent.

`draw_action(state)`
Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state` (`np.ndarray`) – the state where the agent is.

Returns The action to be executed.

`episode_start()`
Called by the agent when a new episode starts.

`classmethod load(path)`
Load and deserialize the agent from the given location on disk.

Parameters `path` (`Path, string`) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
 - **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file*, *full_save*, *folder*=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
 - **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
 - **folder** (*string*, ‘’) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

Bases: mushroom_rl.algorithms.actor_critic.deep_actor_critic.
deep_actor_critic.DeepAC

Deep Deterministic Policy Gradient algorithm. “Continuous Control with Deep Reinforcement Learning”. Lillicrap T. P. et al.. 2016.

```
__init__(mdp_info, policy_class, policy_params, actor_params, actor_optimizer,
        critic_params, batch_size, initial_replay_size, max_replay_size, tau, policy_delay=1,
        critic_fit_params=None)
```

Constructor.

Parameters

- **policy_class** (`Policy`) – class of the policy;
 - **policy_params** (`dict`) – parameters of the policy to build;
 - **actor_params** (`dict`) – parameters of the actor approximator to build;
 - **actor_optimizer** (`dict`) – parameters to specify the actor optimizer algorithm;

- **critic_params** (*dict*) – parameters of the critic approximator to build;
- **batch_size** (*int*) – the number of samples in a batch;
- **initial_replay_size** (*int*) – the number of samples to collect before starting the learning;
- **max_replay_size** (*int*) – the maximum number of samples in the replay memory;
- **tau** (*float*) – value of coefficient for soft updates;
- **policy_delay** (*int*, *1*) – the number of updates of the critic after which an actor update is implemented;
- **critic_fit_params** (*dict*, *None*) – parameters of the fitting algorithm of the critic approximator;

fit (*dataset*)
Fit step.

Parameters **dataset** (*list*) – the dataset.

_next_q (*next_state*, *absorbing*)

Parameters

- **next_state** (*np.ndarray*) – the states where next action has to be evaluated;
- **absorbing** (*np.ndarray*) – the absorbing flag for the states in *next_state*.

Returns Action-values returned by the critic for *next_state* and the action returned by the actor.

_post_load()
This method can be overwritten to implement logic that is executed after the loading of the agent.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if *full_save* is set to True.

_optimize_actor_parameters (*loss*)

Method used to update actor parameters to maximize a given loss.

Parameters **loss** (*torch.tensor*) – the loss computed by the algorithm.

copy()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path*, *string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path*, *str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ' ') – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3(mdp_info, policy_class, policy_params, actor_params, actor_optimizer, critic_params, batch_size, initial_replay_size, max_replay_size, tau, policy_delay=2, noise_std=0.2, noise_clip=0.5, critic_fit_params=None)
```

Bases: `mushroom_rl.algorithms.actor_critic.deep_actor_critic.ddpg.DDPG`

Twin Delayed DDPG algorithm. “Addressing Function Approximation Error in Actor-Critic Methods”. Fujimoto S. et al.. 2018.

```
__init__(mdp_info, policy_class, policy_params, actor_params, actor_optimizer, critic_params, batch_size, initial_replay_size, max_replay_size, tau, policy_delay=2, noise_std=0.2, noise_clip=0.5, critic_fit_params=None)
```

Constructor.

Parameters

- **policy_class** (*Policy*) – class of the policy;
- **policy_params** (*dict*) – parameters of the policy to build;
- **actor_params** (*dict*) – parameters of the actor approximator to build;
- **actor_optimizer** (*dict*) – parameters to specify the actor optimizer algorithm;
- **critic_params** (*dict*) – parameters of the critic approximator to build;

- **batch_size** (*int*) – the number of samples in a batch;
- **initial_replay_size** (*int*) – the number of samples to collect before starting the learning;
- **max_replay_size** (*int*) – the maximum number of samples in the replay memory;
- **tau** (*float*) – value of coefficient for soft updates;
- **policy_delay** (*int, 2*) – the number of updates of the critic after which an actor update is implemented;
- **noise_std** (*float, 2*) – standard deviation of the noise used for policy smoothing;
- **noise_clip** (*float, 5*) – maximum absolute value for policy smoothing noise;
- **critic_fit_params** (*dict, None*) – parameters of the fitting algorithm of the critic approximator.

_next_q (*next_state, absorbing*)

Parameters

- **next_state** (*np.ndarray*) – the states where next action has to be evaluated;
- **absorbing** (*np.ndarray*) – the absorbing flag for the states in *next_state*.

Returns Action-values returned by the critic for *next_state* and the action returned by the actor.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_optimize_actor_parameters (*loss*)

Method used to update actor parameters to maximize a given loss.

Parameters **loss** (*torch.tensor*) – the loss computed by the algorithm.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=’’*)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where the object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC(mdp_info, actor_mu_params,
actor_sigma_params, actor_optimizer, critic_params, batch_size, initial_replay_size,
max_replay_size, warmup_transitions, tau, lr_alpha, target_entropy=None,
critic_fit_params=None)
```

Bases: `mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC`

Soft Actor-Critic algorithm. “Soft Actor-Critic Algorithms and Applications”. Haarnoja T. et al.. 2019.

```
__init__(mdp_info, actor_mu_params, actor_sigma_params, actor_optimizer, critic_params,
batch_size, initial_replay_size, max_replay_size, warmup_transitions, tau, lr_alpha, target_entropy=None, critic_fit_params=None)
```

Constructor.

Parameters

- `actor_mu_params` (*dict*) – parameters of the actor mean approximator to build;
- `actor_sigma_params` (*dict*) – parameters of the actor sigma approximator to build;
- `actor_optimizer` (*dict*) – parameters to specify the actor optimizer algorithm;
- `critic_params` (*dict*) – parameters of the critic approximator to build;

- **batch_size** (*int*) – the number of samples in a batch;
- **initial_replay_size** (*int*) – the number of samples to collect before starting the learning;
- **max_replay_size** (*int*) – the maximum number of samples in the replay memory;
- **warmup_transitions** (*int*) – number of samples to accumulate in the replay memory to start the policy fitting;
- **tau** (*float*) – value of coefficient for soft updates;
- **lr_alpha** (*float*) – Learning rate for the entropy coefficient;
- **target_entropy** (*float, None*) – target entropy for the policy, if None a default value is computed ;
- **critic_fit_params** (*dict, None*) – parameters of the fitting algorithm of the critic approximator.

fit (*dataset*)
Fit step.

Parameters **dataset** (*list*) – the dataset.

_add_save_attr (***attr_dict*)
Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_next_q (*next_state, absorbing*)

Parameters

- **next_state** (*np.ndarray*) – the states where next action has to be evaluated;
- **absorbing** (*np.ndarray*) – the absorbing flag for the states in *next_state*.

Returns Action-values returned by the critic for *next_state* and the action returned by the actor.

_optimize_actor_parameters (*loss*)

Method used to update actor parameters to maximize a given loss.

Parameters **loss** (*torch.tensor*) – the loss computed by the algorithm.

copy ()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start ()

Called by the agent when a new episode starts.

classmethod **load** (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
class mushroom_rl.algorithms.actor_critic.deep_actor_critic.TRPO(mdp_info,
                                                               policy,
                                                               critic_params,
                                                               ent_coeff=0.0,
                                                               max_kl=0.001,
                                                               lam=1.0,
                                                               n_epochs_line_search=10,
                                                               n_epochs_cg=10,
                                                               cg_damping=0.01,
                                                               cg_residual_tol=1e-
                                                               10,
                                                               quiet=True,
                                                               critic_fit_params=None)
```

Bases: *mushroom_rl.algorithms.agent.Agent*

Trust Region Policy optimization algorithm. “Trust Region Policy Optimization”. Schulman J. et al.. 2015.

```
__init__(mdp_info, policy, critic_params, ent_coeff=0.0, max_kl=0.001, lam=1.0,
        n_epochs_line_search=10, n_epochs_cg=10, cg_damping=0.01, cg_residual_tol=1e-
        10, quiet=True, critic_fit_params=None)
```

Constructor.

Parameters

- **policy** (*TorchPolicy*) – torch policy to be learned by the algorithm
- **critic_params** (*dict*) – parameters of the critic approximator to build;
- **ent_coeff** (*float, 0*) – coefficient for the entropy penalty;
- **max_kl** (*float, 001*) – maximum kl allowed for every policy update;
- **float** (*lam*) – lambda coefficient used by generalized advantage estimation;

- **n_epochs_line_search** (*int*, *10*) – maximum number of iterations of the line search algorithm;
- **n_epochs_cg** (*int*, *10*) – maximum number of iterations of the conjugate gradient algorithm;
- **cg_damping** (*float*, *1e-2*) – damping factor for the conjugate gradient algorithm;
- **cg_residual_tol** (*float*, *1e-10*) – conjugate gradient residual tolerance;
- **quiet** (*bool*, *True*) – if true, the algorithm will print debug information;
- **critic_fit_params** (*dict*, *None*) – parameters of the fitting algorithm of the critic approximator.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start ()

Called by the agent when a new episode starts.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path*, *string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path*, *str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ' ') – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPPO (mdp_info,  
                                  policy,     ac-  
                                  tor_optimizer,  
                                  critic_params,  
                                  n_epochs_policy,  
                                  batch_size,  
                                  eps_ppo, lam,  
                                  quiet=True,  
                                  critic_fit_params=None)
```

Bases: *mushroom_rl.algorithms.agent.Agent*

Proximal Policy Optimization algorithm. “Proximal Policy Optimization Algorithms”. Schulman J. et al.. 2017.

__init__ (*mdp_info*, *policy*, *actor_optimizer*, *critic_params*, *n_epochs_policy*, *batch_size*, *eps_ppo*,
 lam, *quiet=True*, *critic_fit_params=None*)

Constructor.

Parameters

- **policy** (*TorchPolicy*) – torch policy to be learned by the algorithm
- **actor_optimizer** (*dict*) – parameters to specify the actor optimizer algorithm;
- **critic_params** (*dict*) – parameters of the critic approximator to build;
- **n_epochs_policy** (*int*) – number of policy updates for every dataset;
- **batch_size** (*int*) – size of minibatches for every optimization step
- **eps_ppo** (*float*) – value for probability ratio clipping;
- **float** (*lam*) – lambda coefficient used by generalized advantage estimation;
- **quiet** (*bool*, *True*) – if true, the algorithm will print debug information;
- **critic_fit_params** (*dict*, *None*) – parameters of the fitting algorithm of the critic approximator.

fit(*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a ‘!’ character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

3.3 Policy search

3.3.1 Policy gradient

```
class mushroom_rl.algorithms.policy_search.policy_gradient.REINFORCE(mdp_info,
policy,
learn-
ing_rate,
fea-
tures=None)
```

Bases: *mushroom_rl.algorithms.policy_search.policy_gradient.policy_gradient.PolicyGradient*

REINFORCE algorithm. “Simple Statistical Gradient-Following Algorithms for Connectionist Reinforcement Learning”, Williams R. J.. 1992.

__init__(*mdp_info, policy, learning_rate, features=None*)
Constructor.

Parameters **learning_rate** (*float*) – the learning rate.

_compute_gradient(*J*)
Return the gradient computed by the algorithm.

Parameters **J** (*list*) – list of the cumulative discounted rewards for each episode in the dataset.

_step_update(*x, u, r*)
This function is called, when parsing the dataset, at each episode step.

Parameters

- **x** (*np.ndarray*) – the state at the current step;
- **u** (*np.ndarray*) – the action at the current step;
- **r** (*np.ndarray*) – the reward at the current step.

_episode_end_update()

This function is called, when parsing the dataset, at the beginning of each episode. The implementation is dependent on the algorithm (e.g. REINFORCE updates some data structures).

_init_update()

This function is called, when parsing the dataset, at the beginning of each episode. The implementation is dependent on the algorithm (e.g. REINFORCE resets some data structure).

_add_save_attr(attr_dict)**
Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_parse(*sample*)
Utility to parse the sample.

Parameters **sample** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag. If provided, state is preprocessed with the features.

_post_load()
This method can be overwritten to implement logic that is executed after the loading of the agent.

_update_parameters(*J*)
Update the parameters of the policy.

Parameters **J** (*list*) – list of the cumulative discounted rewards for each episode in the dataset.

copy()

Returns A deepcopy of the agent.

draw_action(*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()
Called by the agent when a new episode starts.

fit(dataset)
Fit step.

Parameters `dataset` (`list`) – the dataset.

classmethod load(path)
Load and deserialize the agent from the given location on disk.

Parameters `path` (`Path, string`) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)
Serialize and save the object to the given path on disk.

Parameters

- `path` (`Path, str`) – Relative or absolute path to the object save location;
- `full_save` (`bool`) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")
Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (`ZipFile`) – ZipFile where te object needs to be saved;
- `full_save` (`bool`) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (`string, ''`) – subfolder to be used by the save method.

stop()
Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class `mushroom_rl.algorithms.policy_search.policy_gradient.GPOMDP(mdp_info, policy, learn-ing_rate, fea-tures=None)`
Bases: `mushroom_rl.algorithms.policy_search.policy_gradient.policy_gradient.PolicyGradient`

GPOMDP algorithm. “Infinite-Horizon Policy-Gradient Estimation”. Baxter J. and Bartlett P. L.. 2001.

__init__(mdp_info, policy, learning_rate, features=None)
Constructor.

Parameters `learning_rate` (`float`) – the learning rate.

_compute_gradient(J)
Return the gradient computed by the algorithm.

Parameters `J` (`list`) – list of the cumulative discounted rewards for each episode in the dataset.

_step_update(x, u, r)
This function is called, when parsing the dataset, at each episode step.

Parameters

- **x** (*np.ndarray*) – the state at the current step;
- **u** (*np.ndarray*) – the action at the current step;
- **r** (*np.ndarray*) – the reward at the current step.

_episode_end_update()

This function is called, when parsing the dataset, at the beginning of each episode. The implementation is dependent on the algorithm (e.g. REINFORCE updates some data structures).

_init_update()

This function is called, when parsing the dataset, at the beginning of each episode. The implementation is dependent on the algorithm (e.g. REINFORCE resets some data structure).

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_parse(sample)

Utility to parse the sample.

Parameters **sample** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag. If provided, state is preprocessed with the features.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

_update_parameters(J)

Update the parameters of the policy.

Parameters **J** (*list*) – list of the cumulative discounted rewards for each episode in the dataset.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit(dataset)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.policy_search.policy_gradient.eNAC (mdp_info,
policy, learning_rate, features=None,
critic_features=None)
```

Bases: mushroom_rl.algorithms.policy_search.policy_gradient.policy_gradient.PolicyGradient

Episodic Natural Actor Critic algorithm. “A Survey on Policy Search for Robotics”, Deisenroth M. P., Neumann G., Peters J. 2013.

```
__init__ (mdp_info, policy, learning_rate, features=None, critic_features=None)
Constructor.
```

Parameters **critic_features** (*Features, None*) – features used by the critic.**_compute_gradient** (*J*)

Return the gradient computed by the algorithm.

Parameters **J** (*list*) – list of the cumulative discounted rewards for each episode in the dataset.**_step_update** (*x, u, r*)

This function is called, when parsing the dataset, at each episode step.

Parameters

- **x** (*np.ndarray*) – the state at the current step;
- **u** (*np.ndarray*) – the action at the current step;
- **r** (*np.ndarray*) – the reward at the current step.

_episode_end_update ()

This function is called, when parsing the dataset, at the beginning of each episode. The implementation is dependent on the algorithm (e.g. REINFORCE updates some data structures).

_init_update ()

This function is called, when parsing the dataset, at the beginning of each episode. The implementation is dependent on the algorithm (e.g. REINFORCE resets some data structure).

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

_parse (`sample`)

Utility to parse the sample.

Parameters `sample` (`list`) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag. If provided, `state` is preprocessed with the features.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

_update_parameters (`J`)

Update the parameters of the policy.

Parameters `J` (`list`) – list of the cumulative discounted rewards for each episode in the dataset.

copy()

Returns A deepcopy of the agent.

draw_action (`state`)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state` (`np.ndarray`) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit (`dataset`)

Fit step.

Parameters `dataset` (`list`) – the dataset.

classmethod `load` (`path`)

Load and deserialize the agent from the given location on disk.

Parameters `path` (`Path, string`) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (`path, full_save=False`)

Serialize and save the object to the given path on disk.

Parameters

- `path` (`Path, str`) – Relative or absolute path to the object save location;
- `full_save` (`bool`) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (`zip_file, full_save, folder=”`)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (`ZipFile`) – ZipFile where te object needs to be saved;
- `full_save` (`bool`) – flag to specify the amount of data to save for MushroomRL data structures;

- **folder** (*string*, ' ') – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

3.3.2 Black-Box optimization

```
class mushroom_rl.algorithms.policy_search.black_box_optimization.RWR (mdp_info,  

    dis-  

    tribu-  

    tion,  

    pol-  

    icy,  

    beta,  

    fea-  

    tures=None)
```

Bases: mushroom_rl.algorithms.policy_search.black_box_optimization.
black_box_optimization.BlackBoxOptimization

Reward-Weighted Regression algorithm. “A Survey on Policy Search for Robotics”, Deisenroth M. P., Neumann G., Peters J.. 2013.

init (*mdp_info*, *distribution*, *policy*, *beta*, *features=None*)
Constructor.

Parameters **beta** (*float*) – the temperature for the exponential reward transformation.

_update (*Jep*, *theta*)

Function that implements the update routine of distribution parameters. Every black box algorithms should implement this function with the proper update.

Parameters

- **Jep** (*np.ndarray*) – a vector containing the J of the considered trajectories;
- **theta** (*np.ndarray*) – a matrix of policy parameters of the considered trajectories.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=*”)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.policy_search.black_box_optimization.**PGPE** (*mdp_info, distribution, transition, policy, learning_rate, features=None*)

Bases: mushroom_rl.algorithms.policy_search.black_box_optimization.BlackBoxOptimization

Policy Gradient with Parameter Exploration algorithm. “A Survey on Policy Search for Robotics”, Deisenroth M. P., Neumann G., Peters J.. 2013.

__init__ (*mdp_info, distribution, policy, learning_rate, features=None*)

Constructor.

Parameters **learning_rate** (*Parameter*) – the learning rate for the gradient step.

_update (*Jep, theta*)

Function that implements the update routine of distribution parameters. Every black box algorithms should implement this function with the proper update.

Parameters

- **Jep** (*np.ndarray*) – a vector containing the J of the considered trajectories;
- **theta** (*np.ndarray*) – a matrix of policy parameters of the considered trajectories.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit(dataset)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.policy_search.black_box_optimization.REPS (mdp_info,
dis-
tri-
bu-
tion,
pol-
icy,
eps,
fea-
tures=None)
```

Bases: mushroom_rl.algorithms.policy_search.black_box_optimization.
black_box_optimization.BlackBoxOptimization

Episodic Relative Entropy Policy Search algorithm. “A Survey on Policy Search for Robotics”, Deisenroth M. P., Neumann G., Peters J.. 2013.

__init__ (*mdp_info, distribution, policy, eps, features=None*)
Constructor.

Parameters **eps** (*float*) – the maximum admissible value for the Kullback-Leibler divergence between the new distribution and the previous one at each update step.

_update (*Jep, theta*)

Function that implements the update routine of distribution parameters. Every black box algorithms should implement this function with the proper update.

Parameters

- **Jep** (*np.ndarray*) – a vector containing the J of the considered trajectories;
- **theta** (*np.ndarray*) – a matrix of policy parameters of the considered trajectories.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit (*dataset*)

Fit step.

Parameters `dataset` (*list*) – the dataset.

classmethod `load` (*path*)

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

`save` (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

`save_zip` (*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where te object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ‘’*) – subfolder to be used by the save method.

`stop()`

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

3.4 Value-Based

3.4.1 TD

class `mushroom_rl.algorithms.value.td.SARSA` (*mdp_info, policy, learning_rate*)

Bases: `mushroom_rl.algorithms.value.td.td.TD`

SARSA algorithm.

`__init__` (*mdp_info, policy, learning_rate*)

Constructor.

Parameters

- `approximator` (*object*) – the approximator to use to fit the Q-function;
- `learning_rate` (*Parameter*) – the learning rate.

`_update` (*state, action, reward, next_state, absorbing*)

Update the Q-table.

Parameters

- `state` (*np.ndarray*) – state;
- `action` (*np.ndarray*) – action;
- `reward` (*np.ndarray*) – reward;

- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _parse (*dataset*)

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load ()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start ()

Called by the agent when a new episode starts.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;

- **folder** (*string*, ' ') – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.value.td.SARSALambda (mdp_info, policy, learning_rate,  
                                          lambda_coeff, trace='replacing')
```

Bases: mushroom_rl.algorithms.value.td.td.TD

The SARSA(lambda) algorithm for finite MDPs.

__init__ (*mdp_info*, *policy*, *learning_rate*, *lambda_coeff*, *trace*='replacing')

Constructor.

Parameters

- **lambda_coeff** (*float*) – eligibility trace coefficient;
- **trace** (*str*, 'replacing') – type of eligibility trace to use.

_update (*state*, *action*, *reward*, *next_state*, *absorbing*)

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

episode_start()

Called by the agent when a new episode starts.

_add_save_attr (attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _parse (*dataset*)

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=*”)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.value.td.**ExpectedSARSA** (*mdp_info, policy, learning_rate*)

Bases: mushroom_rl.algorithms.value.td.td.TD

Expected SARSA algorithm. “A theoretical and empirical analysis of Expected Sarsa”. Seijen H. V. et al.. 2009.

__init__ (*mdp_info, policy, learning_rate*)

Constructor.

Parameters

- **approximator** (*object*) – the approximator to use to fit the Q-function;
- **learning_rate** (*Parameter*) – the learning rate.

_update (*state, action, reward, next_state, absorbing*)

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

_add_save_attr(***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _parse(*dataset*)

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit(*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.value.td.QLearning(mdp_info, policy, learning_rate)

Bases: mushroom_rl.algorithms.value.td.td.TD

Q-Learning algorithm. “Learning from Delayed Rewards”. Watkins C.J.C.H.. 1989.

__init__(mdp_info, policy, learning_rate)

Constructor.

Parameters

- **approximator** (*object*) – the approximator to use to fit the Q-function;
- **learning_rate** (*Parameter*) – the learning rate.

_update(state, action, reward, next_state, absorbing)

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _parse(dataset)

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit(dataset)

Fit step.

Parameters `dataset` (*list*) – the dataset.

classmethod `load` (*path*)

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where te object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ‘’*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class `mushroom_rl.algorithms.value.td.QLambda` (*mdp_info, policy, learning_rate, lambda_coeff, trace='replacing'*)

Bases: `mushroom_rl.algorithms.value.td.TD`

Q(Lambda) algorithm. “Learning from Delayed Rewards”. Watkins C.J.C.H.. 1989.

__init__ (*mdp_info, policy, learning_rate, lambda_coeff, trace='replacing'*)

Constructor.

Parameters

- `lambda_coeff` (*float*) – eligibility trace coefficient;
- `trace` (*str, ‘replacing’*) – type of eligibility trace to use.

_update (*state, action, reward, next_state, absorbing*)

Update the Q-table.

Parameters

- `state` (*np.ndarray*) – state;
- `action` (*np.ndarray*) – action;
- `reward` (*np.ndarray*) – reward;
- `next_state` (*np.ndarray*) – next state;
- `absorbing` (*np.ndarray*) – absorbing flag.

episode_start ()

Called by the agent when a new episode starts.

_add_save_attr (attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _parse (dataset)

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load ()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

draw_action (state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

fit (dataset)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load (path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (zip_file, full_save, folder=”)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.value.td.DoubleQLearning(mdp_info, policy, learning_rate)
```

Bases: mushroom_rl.algorithms.value.td.td.TD

Double Q-Learning algorithm. “Double Q-Learning”. Hasselt H. V.. 2010.

```
__init__(mdp_info, policy, learning_rate)
```

Constructor.

Parameters

- **approximator** (*object*) – the approximator to use to fit the Q-function;
- **learning_rate** (*Parameter*) – the learning rate.

```
_update(state, action, reward, next_state, absorbing)
```

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

```
_add_save_attr(**attr_dict)
```

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

```
static _parse(dataset)
```

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

```
_post_load()
```

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
copy()
```

Returns A deepcopy of the agent.

```
draw_action(state)
```

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

```
episode_start()
```

Called by the agent when a new episode starts.

```
fit(dataset)
```

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.value.td.SpeedyQLearning(mdp_info, policy, learning_rate)

Bases: mushroom_rl.algorithms.value.td.TD

Speedy Q-Learning algorithm. “Speedy Q-Learning”. Ghavamzadeh et. al.. 2011.

__init__(mdp_info, policy, learning_rate)

Constructor.

Parameters

- **approximator** (*object*) – the approximator to use to fit the Q-function;
- **learning_rate** (*Parameter*) – the learning rate.

_update(state, action, reward, next_state, absorbing)

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

`static _parse(dataset)`

Utility to parse the dataset that is supposed to contain only a sample.

Parameters `dataset (list)` – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`copy()`

Returns A deepcopy of the agent.

`draw_action(state)`

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state (np.ndarray)` – the state where the agent is.

Returns The action to be executed.

`episode_start()`

Called by the agent when a new episode starts.

`fit(dataset)`

Fit step.

Parameters `dataset (list)` – the dataset.

`classmethod load(path)`

Load and deserialize the agent from the given location on disk.

Parameters `path (Path, string)` – Relative or absolute path to the agents save location.

Returns The loaded agent.

`save(path, full_save=False)`

Serialize and save the object to the given path on disk.

Parameters

- `path (Path, str)` – Relative or absolute path to the object save location;
- `full_save (bool)` – Flag to specify the amount of data to save for MushroomRL data structures.

`save_zip(zip_file, full_save, folder=’’)`

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file (ZipFile)` – ZipFile where the object needs to be saved;
- `full_save (bool)` – flag to specify the amount of data to save for MushroomRL data structures;
- `folder (string, ‘’)` – subfolder to be used by the save method.

`stop()`

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.value.td.RLearning(*mdp_info, policy, learning_rate, beta*)

Bases: mushroom_rl.algorithms.value.td.td.TD

R-Learning algorithm. “A Reinforcement Learning Method for Maximizing Undiscounted Rewards”. Schwartz A.. 1993.

__init__(*mdp_info, policy, learning_rate, beta*)

Constructor.

Parameters **beta** ([Parameter](#)) – beta coefficient.

_update(*state, action, reward, next_state, absorbing*)

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

_add_save_attr(***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _parse(*dataset*)

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit(*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path*, *str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=””*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ‘’) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.value.td.WeightedQLearning(mdp_info, policy, learning_rate, sampling=True, precision=1000)
```

Bases: *mushroom_rl.algorithms.value.td.TD*

Weighted Q-Learning algorithm. “Estimating the Maximum Expected Value through Gaussian Approximation”. D’Eramo C. et. al.. 2016.

__init__ (*mdp_info*, *policy*, *learning_rate*, *sampling=True*, *precision=1000*)

Constructor.

Parameters

- **sampling** (*bool*, *True*) – use the approximated version to speed up the computation;
- **precision** (*int*, *1000*) – number of samples to use in the approximated version.

_update (*state*, *action*, *reward*, *next_state*, *absorbing*)

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

_next_q (*next_state*)

Parameters **next_state** (*np.ndarray*) – the state where next action has to be evaluated.

Returns The weighted estimator value in *next_state*.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

static `_parse(dataset)`

Utility to parse the dataset that is supposed to contain only a sample.

Parameters `dataset (list)` – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state (np.ndarray)` – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit(dataset)

Fit step.

Parameters `dataset (list)` – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters `path (Path, string)` – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (`Path, str`) – Relative or absolute path to the object save location;
- **full_save** (`bool`) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’ ’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (`ZipFile`) – ZipFile where te object needs to be saved;
- **full_save** (`bool`) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (`string, ‘ ’`) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.value.td.RQLearning(mdp_info, policy, learning_rate,  
                                  off_policy=False,              beta=None,  
                                  delta=None)
```

Bases: mushroom_rl.algorithms.value.td.td.TD

RQ-Learning algorithm. “Exploiting Structure and Uncertainty of Bellman Updates in Markov Decision Processes”. Tateo D. et al.. 2017.

```
__init__(mdp_info, policy, learning_rate, off_policy=False, beta=None, delta=None)
```

Constructor.

Parameters

- **off_policy** (`bool`, `False`) – whether to use the off policy setting or the online one;
- **beta** (`Parameter`, `None`) – beta coefficient;
- **delta** (`Parameter`, `None`) – delta coefficient.

```
_add_save_attr(**attr_dict)
```

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

```
static _parse(dataset)
```

Utility to parse the dataset that is supposed to contain only a sample.

Parameters `dataset` (`list`) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

```
_post_load()
```

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
_update(state, action, reward, next_state, absorbing)
```

Update the Q-table.

Parameters

- **state** (`np.ndarray`) – state;
- **action** (`np.ndarray`) – action;
- **reward** (`np.ndarray`) – reward;
- **next_state** (`np.ndarray`) – next state;
- **absorbing** (`np.ndarray`) – absorbing flag.

```
copy()
```

Returns A deepcopy of the agent.

```
draw_action(state)
```

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state` (`np.ndarray`) – the state where the agent is.

Returns The action to be executed.

```
episode_start()
```

Called by the agent when a new episode starts.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

_next_q (*next_state*)

Parameters **next_state** (*np.ndarray*) – the state where next action has to be evaluated.

Returns The weighted estimator value in ‘next_state’.

class mushroom_rl.algorithms.value.td.**SARSALambdaContinuous** (*mdp_info, policy, approximator, learning_rate, lambda_coeff, features, approximator_params=None*)

Bases: mushroom_rl.algorithms.value.td.td.TD

Continuous version of SARSA(lambda) algorithm.

__init__ (*mdp_info, policy, approximator, learning_rate, lambda_coeff, features, approximator_params=None*)

Constructor.

Parameters **lambda_coeff** (*float*) – eligibility trace coefficient.

_update (*state, action, reward, next_state, absorbing*)

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;

- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

episode_start()

Called by the agent when a new episode starts.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _parse(dataset)

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

fit(dataset)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ' ') – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.value.td.TrueOnlineSARSALambda (mdp_info, policy, learning_rate, lambda_coeff, features, approximator_params=None)
```

Bases: mushroom_rl.algorithms.value.td.td.TD

True Online SARSA(lambda) with linear function approximation. “True Online TD(lambda)”. Seijen H. V. et al.. 2014.

```
_init_ (mdp_info, policy, learning_rate, lambda_coeff, features, approximator_params=None)
```

Constructor.

Parameters **lambda_coeff** (*float*) – eligibility trace coefficient.

```
_update (state, action, reward, next_state, absorbing)
```

Update the Q-table.

Parameters

- **state** (*np.ndarray*) – state;
- **action** (*np.ndarray*) – action;
- **reward** (*np.ndarray*) – reward;
- **next_state** (*np.ndarray*) – next state;
- **absorbing** (*np.ndarray*) – absorbing flag.

```
episode_start()
```

Called by the agent when a new episode starts.

```
_add_save_attr (**attr_dict)
```

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

```
static _parse (dataset)
```

Utility to parse the dataset that is supposed to contain only a sample.

Parameters **dataset** (*list*) – the current episode step.

Returns A tuple containing state, action, reward, next state, absorbing and last flag.

```
_post_load()
```

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
copy()
```

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

fit(dataset)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

3.4.2 Batch TD

```
class mushroom_rl.algorithms.value.batch_td.FQI (mdp_info, policy, approximator, n_iterations, approximator_params=None, fit_params=None, quiet=False, boosted=False)
```

Bases: *mushroom_rl.algorithms.value.batch_td.BatchTD*

Fitted Q-Iteration algorithm. “Tree-Based Batch Mode Reinforcement Learning”, Ernst D. et al.. 2005.

```
__init__(mdp_info, policy, approximator, n_iterations, approximator_params=None, fit_params=None, quiet=False, boosted=False)
```

Constructor.

Parameters

- **n_iterations** (*int*) – number of iterations to perform for training;

- **quiet** (*bool*, *False*) – whether to show the progress bar or not;
- **boosted** (*bool*, *False*) – whether to use boosted FQI or not.

fit (*dataset*)
Fit loop.

_fit (*x*)
Single fit iteration.

Parameters **x** (*list*) – the dataset.

_fit_boosted (*x*)
Single fit iteration for boosted FQI.

Parameters **x** (*list*) – the dataset.

_add_save_attr (***attr_dict*)
Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load ()
This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()
Returns A deepcopy of the agent.

draw_action (*state*)
Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start ()
Called by the agent when a new episode starts.

classmethod load (*path*)
Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path*, *string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)
Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path*, *str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=*)
Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;

- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ' ') – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.value.batch_td.DoubleFQI (mdp_info, policy, approximator, n_iterations, approximator_params=None, fit_params=None, quiet=False)
```

Bases: mushroom_rl.algorithms.value.batch_td.FQI

Double Fitted Q-Iteration algorithm. “Estimating the Maximum Expected Value in Continuous Reinforcement Learning Problems”. D’Eramo C. et al.. 2017.

```
_init_ (mdp_info, policy, approximator, n_iterations, approximator_params=None, fit_params=None, quiet=False)
```

Constructor.

Parameters

- **n_iterations** (*int*) – number of iterations to perform for training;
- **quiet** (*bool*, *False*) – whether to show the progress bar or not;
- **boosted** (*bool*, *False*) – whether to use boosted FQI or not.

_fit (x)

Single fit iteration.

Parameters **x** (*list*) – the dataset.**_add_save_attr (**attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_fit_boosted (x)

Single fit iteration for boosted FQI.

Parameters **x** (*list*) – the dataset.**_post_load()**

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action (state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit (*dataset*)
Fit loop.

classmethod load (*path*)
Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)
Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=”*)
Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.value.batch_td.**LSPI** (*mdp_info, policy, approximator_params=None, epsilon=0.01, fit_params=None, features=None*)

Bases: mushroom_rl.algorithms.value.batch_td.BatchTD

Least-Squares Policy Iteration algorithm. “Least-Squares Policy Iteration”. Lagoudakis M. G. and Parr R.. 2003.

__init__ (*mdp_info, policy, approximator_params=None, epsilon=0.01, fit_params=None, features=None*)
Constructor.

Parameters **epsilon** (*float, 1e-2*) – termination coefficient.

fit (*dataset*)
Fit step.

Parameters **dataset** (*list*) – the dataset.

_add_save_attr (***attr_dict*)
Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load ()
This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

3.4.3 DQN

```
class mushroom_rl.algorithms.value.dqn.DQN(mdp_info, policy, approximator,
approximator_params, batch_size,
target_update_frequency, re-
play_memory=None, initial_replay_size=500,
max_replay_size=5000, fit_params=None,
n_approximators=1, clip_reward=True)
```

Bases: *mushroom_rl.algorithms.agent.Agent*

Deep Q-Network algorithm. “Human-Level Control Through Deep Reinforcement Learning”. Mnih V. et al.. 2015.

```
__init__(mdp_info, policy, approximator, approximator_params, batch_size, tar-
get_update_frequency, replay_memory=None, initial_replay_size=500,
max_replay_size=5000, fit_params=None, n_approximators=1, clip_reward=True)
```

Constructor.

Parameters

- **approximator** (*object*) – the approximator to use to fit the Q-function;
- **approximator_params** (*dict*) – parameters of the approximator to build;
- **batch_size** (*int*) – the number of samples in a batch;
- **target_update_frequency** (*int*) – the number of samples collected between each update of the target network;
- **replay_memory** ([*ReplayMemory*, *PrioritizedReplayMemory*], *None*) – the object of the replay memory to use; if *None*, a default replay memory is created;
- **initial_replay_size** (*int*) – the number of samples to collect before starting the learning;
- **max_replay_size** (*int*) – the maximum number of samples in the replay memory;
- **fit_params** (*dict*, *None*) – parameters of the fitting algorithm of the approximator;
- **n_approximators** (*int*, *1*) – the number of approximator to use in AveragedDQN;
- **clip_reward** (*bool*, *True*) – whether to clip the reward or not.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

_update_target()

Update the target network.

_next_q (*next_state*, *absorbing*)

Parameters

- **next_state** (*np.ndarray*) – the states where next action has to be evaluated;
- **absorbing** (*np.ndarray*) – the absorbing flag for the states in *next_state*.

Returns Maximum action-value for each state in *next_state*.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ***attr_dict* – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if *full_save* is set to True.

copy ()

Returns A deepcopy of the agent.

episode_start()

Called by the agent when a new episode starts.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where te object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ''*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

```
class mushroom_rl.algorithms.value.dqn.DoubleDQN(mdp_info, policy, approximator, approximator_params, batch_size, target_update_frequency, replay_memory=None, initial_replay_size=500, max_replay_size=5000, fit_params=None, n_approximators=1, clip_reward=True)
```

Bases: `mushroom_rl.algorithms.value.dqn.DQN`

Double DQN algorithm. “Deep Reinforcement Learning with Double Q-Learning”. Hasselt H. V. et al.. 2016.

_next_q(next_state, absorbing)**Parameters**

- `next_state` (*np.ndarray*) – the states where next action has to be evaluated;
- `absorbing` (*np.ndarray*) – the absorbing flag for the states in `next_state`.

Returns Maximum action-value for each state in `next_state`.

```
__init__(mdp_info, policy, approximator, approximator_params, batch_size, target_update_frequency, replay_memory=None, initial_replay_size=500, max_replay_size=5000, fit_params=None, n_approximators=1, clip_reward=True)
```

Constructor.

Parameters

- **approximator** (*object*) – the approximator to use to fit the Q-function;
- **approximator_params** (*dict*) – parameters of the approximator to build;
- **batch_size** (*int*) – the number of samples in a batch;
- **target_update_frequency** (*int*) – the number of samples collected between each update of the target network;
- **replay_memory** ([*ReplayMemory*, *PrioritizedReplayMemory*], *None*) – the object of the replay memory to use; if *None*, a default replay memory is created;
- **initial_replay_size** (*int*) – the number of samples to collect before starting the learning;
- **max_replay_size** (*int*) – the maximum number of samples in the replay memory;
- **fit_params** (*dict*, *None*) – parameters of the fitting algorithm of the approximator;
- **n_approximators** (*int*, *1*) – the number of approximator to use in AveragedDQN;
- **clip_reward** (*bool*, *True*) – whether to clip the reward or not.

_add_save_attr (**attr_dict)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

_update_target()

Update the target network.

copy()

Returns A deepcopy of the agent.

draw_action (*state*)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit (*dataset*)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classemethod **load** (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path*, *string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop ()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

class mushroom_rl.algorithms.value.dqn.**AveragedDQN** (*mdp_info, policy, approximator, **params*)

Bases: mushroom_rl.algorithms.value.dqn.DQN

Averaged-DQN algorithm. “Averaged-DQN: Variance Reduction and Stabilization for Deep Reinforcement Learning”. Anschel O. et al.. 2017.

__init__ (*mdp_info, policy, approximator, **params*)

Constructor.

Parameters

- **approximator** (*object*) – the approximator to use to fit the Q-function;
- **approximator_params** (*dict*) – parameters of the approximator to build;
- **batch_size** (*int*) – the number of samples in a batch;
- **target_update_frequency** (*int*) – the number of samples collected between each update of the target network;
- **replay_memory** (*[ReplayMemory, PrioritizedReplayMemory], None*) – the object of the replay memory to use; if None, a default replay memory is created;
- **initial_replay_size** (*int*) – the number of samples to collect before starting the learning;
- **max_replay_size** (*int*) – the maximum number of samples in the replay memory;
- **fit_params** (*dict, None*) – parameters of the fitting algorithm of the approximator;
- **n_approximators** (*int, 1*) – the number of approximator to use in AveragedDQN;
- **clip_reward** (*bool, True*) – whether to clip the reward or not.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action to be executed.

episode_start()

Called by the agent when a new episode starts.

fit(dataset)

Fit step.

Parameters **dataset** (*list*) – the dataset.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

_update_target()

Update the target network.

_next_q(next_state, absorbing)

Parameters

- **next_state** (*np.ndarray*) – the states where next action has to be evaluated;
- **absorbing** (*np.ndarray*) – the absorbing flag for the states in `next_state`.

Returns Maximum action-value for each state in `next_state`.

```
class mushroom_rl.algorithms.value.dqn.CategoricalDQN(mdp_info, policy, approximator_params, n_atoms, v_min, v_max, **params)
```

Bases: `mushroom_rl.algorithms.value.dqn.DQN`

Categorical DQN algorithm. “A Distributional Perspective on Reinforcement Learning”. Bellemare M. et al.. 2017.

```
__init__(mdp_info, policy, approximator_params, n_atoms, v_min, v_max, **params)
```

Constructor.

Parameters

- `n_atoms` (`int`) – number of atoms;
- `v_min` (`float`) – minimum value of value-function;
- `v_max` (`float`) – maximum value of value-function.

```
_add_save_attr(**attr_dict)
```

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

```
_next_q(next_state, absorbing)
```

Parameters

- `next_state` (`np.ndarray`) – the states where next action has to be evaluated;
- `absorbing` (`np.ndarray`) – the absorbing flag for the states in `next_state`.

Returns Maximum action-value for each state in `next_state`.

```
_post_load()
```

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
_update_target()
```

Update the target network.

```
copy()
```

Returns A deepcopy of the agent.

```
draw_action(state)
```

Return the action to execute in the given state. It is the action returned by the policy or the action set by the algorithm (e.g. in the case of SARSA).

Parameters `state` (`np.ndarray`) – the state where the agent is.

Returns The action to be executed.

```
episode_start()
```

Called by the agent when a new episode starts.

```
fit(dataset)
```

Fit step.

Parameters `dataset` (`list`) – the dataset.

```
classmethod load(path)
```

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=’’*)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where the object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ‘’*) – subfolder to be used by the save method.

stop()

Method used to stop an agent. Useful when dealing with real world environments, simulators, or to cleanup environments internals after a core learn/evaluate to enforce consistency.

3.5 Approximators

MushroomRL exposes the high-level class `Regressor` that can manage any type of function regressor. This class is a wrapper for any kind of function approximator, e.g. a scikit-learn approximator or a pytorch neural network.

3.5.1 Regressor

```
class mushroom_rl.approximators.regressor.Regressor(approximator,      input_shape,
                                                    output_shape=(1,          ),
                                                    n_actions=None,   n_models=1,
                                                    **params)
```

Bases: *mushroom_rl.core.serialization.Serializable*

This class implements the function to manage a function approximator. This class selects the appropriate kind of regressor to implement according to the parameters provided by the user; this makes this class the only one to use for each kind of task that has to be performed. The inference of the implementation to choose is done checking the provided values of parameters `n_actions`. If `n_actions` is provided, it means that the user wants to implement an approximator of the Q-function: if the value of `n_actions` is equal to the `output_shape` then a `QRegressor` is created, else (`output_shape` should be `(1,)`) an `ActionRegressor` is created. Otherwise a `GenericRegressor` is created. An `Ensemble` model can be used for all the previous implementations listed before simply providing a `n_models` parameter greater than 1.

```
__init__(approximator, input_shape, output_shape=(1,), n_actions=None, n_models=1, **params)
```

Constructor.

Parameters

- `approximator` (*class*) – the approximator class to use to create the model;
- `input_shape` (*tuple*) – the shape of the input of the model;

- **output_shape** (*tuple, (1,)*) – the shape of the output of the model;
- **n_actions** (*int, None*) – number of actions considered to create a QRegressor or an ActionRegressor;
- **n_models** (*int, 1*) – number of models to create;
- ****params** – other parameters to create each model.

__call__ (**z*, ***predict_params*)

Call self as a function.

fit (**z*, ***fit_params*)

Fit the model.

Parameters

- ***z** – list of input of the model;
- ****fit_params** – parameters to use to fit the model.

predict (**z*, ***predict_params*)

Predict the output of the model given an input.

Parameters

- ***z** – list of input of the model;
- ****predict_params** – parameters to use to predict with the model.

Returns The model prediction.

model

The model object.

Type Returns

reset()

Reset the model parameters.

input_shape

The shape of the input of the model.

Type Returns

output_shape

The shape of the output of the model.

Type Returns

weights_size

The shape of the weights of the model.

Type Returns

get_weights()

Returns The weights of the model.

set_weights (*w*)

Parameters **w** (*list*) – list of weights to be set in the model.

diff (**z*)

Parameters ***z** – the input of the model.

Returns The derivative of the model.

_add_save_attr(***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

classmethod load(*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path**(*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path**(*Path, str*) – Relative or absolute path to the object save location;
- **full_save**(*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file**(*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save**(*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder**(*string, ‘’*) – subfolder to be used by the save method.

3.5.2 Approximator

Linear

```
class mushroom_rl.approximators.parametric.linear.LinearApproximator(weights=None,
in-
put_shape=None,
out-
put_shape=(1,
),
**kwargs)
```

Bases: *mushroom_rl.core.serialization.Serializable*

This class implements a linear approximator.

```
__init__(weights=None, input_shape=None, output_shape=(1, ), **kwargs)
```

Constructor.

Parameters

- **weights** (*np.ndarray*) – array of weights to initialize the weights of the approximator;
- **input_shape** (*np.ndarray, None*) – the shape of the input of the model;
- **output_shape** (*np.ndarray, (1,)*) – the shape of the output of the model;
- ****kwargs** – other params of the approximator.

fit (*x, y, **fit_params*)

Fit the model.

Parameters

- **x** (*np.ndarray*) – input;
- **y** (*np.ndarray*) – target;
- ****fit_params** – other parameters used by the fit method of the regressor.

predict (*x, **predict_params*)

Predict.

Parameters

- **x** (*np.ndarray*) – input;
- ****predict_params** – other parameters used by the predict method the regressor.

Returns The predictions of the model.

weights_size

The size of the array of weights.

Type Returns**get_weights()**

Getter.

Returns The set of weights of the approximator.

set_weights(*w*)

Setter.

Parameters **w** (*np.ndarray*) – the set of weights to set.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

diff(state, action=None)

Compute the derivative of the output w.r.t. state, and action if provided.

Parameters

- **state** (*np.ndarray*) – the state;
- **action** (*np.ndarray, None*) – the action.

Returns The derivative of the output w.r.t. state, and action if provided.

classmethod **load**(*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path**(*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path**(*Path, str*) – Relative or absolute path to the object save location;
- **full_save**(*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file**(*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save**(*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder**(*string, ‘’*) – subfolder to be used by the save method.

Torch Approximator

```
class mushroom_rl.approximators.parametric.torch_approximator.TorchApproximator(input_shape,
out-
put_shape,
net-
work,
op-
ti-
mizer=None,
loss=None,
batch_size=0,
n_fit_targets=1,
use_cuda=False,
reini-
tial-
ize=False,
dropout=False,
quiet=True,
**params)
```

Bases: *mushroom_rl.core.serialization.Serializable*

Class to interface a pytorch model to the mushroom Regressor interface. This class implements all is needed to use a generic pytorch model and train it using a specified optimizer and objective function. This class supports also minibatches.

__init__(*input_shape, output_shape, network, optimizer=None, loss=None, batch_size=0,*
n_fit_targets=1, use_cuda=False, reinitialize=False, dropout=False, quiet=True,
***params)*

Constructor.

Parameters

- **input_shape** (*tuple*) – shape of the input of the network;
- **output_shape** (*tuple*) – shape of the output of the network;
- **network** (*torch.nn.Module*) – the network class to use;
- **optimizer** (*dict*) – the optimizer used for every fit step;
- **loss** (*torch.nn.functional*) – the loss function to optimize in the fit method;
- **batch_size** (*int, 0*) – the size of each minibatch. If 0, the whole dataset is fed to the optimizer at each epoch;
- **n_fit_targets** (*int, 1*) – the number of fit targets used by the fit method of the network;
- **use_cuda** (*bool, False*) – if True, runs the network on the GPU;
- **reinitialize** (*bool, False*) – if True, the approximator is reinitialized at every fit call. To perform the initialization, the approximator must be initialized first.
- **method must be defined properly for the selected weights_init** (*weights_init*) –
- **network.** (*model*) –
- **dropout** (*bool, False*) – if True, dropout is applied only during train;
- **quiet** (*bool, True*) – if False, shows two progress bars, one for epochs and one for the minibatches;
- ****params** – dictionary of parameters needed to construct the network.

predict (*args, *output_tensor=False*, **kwargs)

Predict.

Parameters

- ***args** – input;
- **output_tensor** (*bool, False*) – whether to return the output as tensor or not;
- ****kwargs** – other parameters used by the predict method the regressor.

Returns The predictions of the model.

fit (*args, *n_epochs=None*, *weights=None*, *epsilon=None*, *patience=1*, *validation_split=1.0*, **kwargs)

Fit the model.

Parameters

- ***args** – input, where the last *n_fit_targets* elements are considered as the target, while the others are considered as input;
- **n_epochs** (*int, None*) – the number of training epochs;
- **weights** (*np.ndarray, None*) – the weights of each sample in the computation of the loss;
- **epsilon** (*float, None*) – the coefficient used for early stopping;
- **patience** (*float, 1.*) – the number of epochs to wait until stop the learning if not improving;

- **validation_split** (*float*, *1.*) – the percentage of the dataset to use as training set;
- ****kwargs** – other parameters used by the fit method of the regressor.

set_weights (*weights*)
Setter.

Parameters **w** (*np.ndarray*) – the set of weights to set.

get_weights ()
Getter.

Returns The set of weights of the approximator.

weights_size

The size of the array of weights.

Type Returns

diff (*args, **kwargs)

Compute the derivative of the output w.r.t. state, and action if provided.

Parameters

- **state** (*np.ndarray*) – the state;
- **action** (*np.ndarray*, *None*) – the action.

Returns The derivative of the output w.r.t. state, and action if provided.

_add_save_attr (**attr_dict)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load ()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path*, *string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path*, *str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ‘’) – subfolder to be used by the save method.

3.6 Distributions

class `mushroom_rl.distributions.distribution.Distribution`
 Bases: `mushroom_rl.core.serialization.Serializable`

Interface for Distributions to represent a generic probability distribution. Probability distributions are often used by black box optimization algorithms in order to perform exploration in parameter space. In literature, they are also known as high level policies.

sample()

Draw a sample from the distribution.

Returns A random vector sampled from the distribution.

log_pdf(theta)

Compute the logarithm of the probability density function in the specified point

Parameters `theta` (*np.ndarray*) – the point where the log pdf is calculated

Returns The value of the log pdf in the specified point.

__call__(theta)

Compute the probability density function in the specified point

Parameters `theta` (*np.ndarray*) – the point where the pdf is calculated

Returns The value of the pdf in the specified point.

entropy()

Compute the entropy of the distribution.

Returns The value of the entropy of the distribution.

mle(theta, weights=None)

Compute the (weighted) maximum likelihood estimate of the points, and update the distribution accordingly.

Parameters

- `theta` (*np.ndarray*) – a set of points, every row is a sample
- `weights` (*np.ndarray*, *None*) – a vector of weights. If specified the weighted maximum likelihood estimate is computed instead of the plain maximum likelihood. The number of elements of this vector must be equal to the number of rows of the theta matrix.

diff_log(theta)

Compute the derivative of the logarithm of the probability density function in the specified point.

Parameters

- `theta` (*np.ndarray*) – the point where the gradient of the log pdf is
- `computed`. –

Returns The gradient of the log pdf in the specified point.

diff(theta)

Compute the derivative of the probability density function, in the specified point. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_\rho p(\theta) = p(\theta) \nabla_\rho \log p(\theta)$$

Parameters

- **theta** (*np.ndarray*) – the point where the gradient of the pdf is
- **calculated.** –

Returns The gradient of the pdf in the specified point.

get_parameters()

Getter.

Returns The current distribution parameters.

set_parameters(rho)

Setter.

Parameters **rho** (*np.ndarray*) – the vector of the new parameters to be used by the distribution

parameters_size

Property.

Returns The size of the distribution parameters.

__init__

Initialize self. See help(type(self)) for accurate signature.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file*, *full_save*, *folder*=’’)
Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ‘ ’) – subfolder to be used by the save method.

3.6.1 Gaussian

class *mushroom_rl.distributions.gaussian.GaussianDistribution*(*mu*, *sigma*)
Bases: *mushroom_rl.distributions.distribution.Distribution*

Gaussian distribution with fixed covariance matrix. The parameters vector represents only the mean.

__init__(*mu*, *sigma*)

Constructor.

Parameters

- **mu** (*np.ndarray*) – initial mean of the distribution;
- **sigma** (*np.ndarray*) – covariance matrix of the distribution.

sample()

Draw a sample from the distribution.

Returns A random vector sampled from the distribution.

log_pdf(*theta*)

Compute the logarithm of the probability density function in the specified point

Parameters **theta** (*np.ndarray*) – the point where the log pdf is calculated

Returns The value of the log pdf in the specified point.

__call__(*theta*)

Compute the probability density function in the specified point

Parameters **theta** (*np.ndarray*) – the point where the pdf is calculated

Returns The value of the pdf in the specified point.

entropy()

Compute the entropy of the distribution.

Returns The value of the entropy of the distribution.

mle(*theta*, *weights*=*None*)

Compute the (weighted) maximum likelihood estimate of the points, and update the distribution accordingly.

Parameters

- **theta** (*np.ndarray*) – a set of points, every row is a sample
- **weights** (*np.ndarray*, *None*) – a vector of weights. If specified the weighted maximum likelihood estimate is computed instead of the plain maximum likelihood. The number of elements of this vector must be equal to the number of rows of the theta matrix.

diff_log(theta)

Compute the derivative of the logarithm of the probability density function in the specified point.

Parameters

- **theta** (*np.ndarray*) – the point where the gradient of the log pdf is
- **computed.** –

Returns The gradient of the log pdf in the specified point.

get_parameters()

Getter.

Returns The current distribution parameters.

set_parameters(rho)

Setter.

Parameters **rho** (*np.ndarray*) – the vector of the new parameters to be used by the distribution

parameters_size

Property.

Returns The size of the distribution parameters.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

diff(theta)

Compute the derivative of the probability density function, in the specified point. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_\rho p(\theta) = p(\theta) \nabla_\rho \log p(\theta)$$

Parameters

- **theta** (*np.ndarray*) – the point where the gradient of the pdf is
- **calculated.** –

Returns The gradient of the pdf in the specified point.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

class mushroom_rl.distributions.gaussian.**GaussianDiagonalDistribution** (*mu, std*)Bases: *mushroom_rl.distributions.distribution.Distribution*

Gaussian distribution with diagonal covariance matrix. The parameters vector represents the mean and the standard deviation for each dimension.

__init__ (*mu, std*)

Constructor.

Parameters

- **mu** (*np.ndarray*) – initial mean of the distribution;
- **std** (*np.ndarray*) – initial vector of standard deviations for each variable of the distribution.

sample ()

Draw a sample from the distribution.

Returns A random vector sampled from the distribution.**log_pdf** (*theta*)

Compute the logarithm of the probability density function in the specified point

Parameters **theta** (*np.ndarray*) – the point where the log pdf is calculated**Returns** The value of the log pdf in the specified point.**__call__** (*theta*)

Compute the probability density function in the specified point

Parameters **theta** (*np.ndarray*) – the point where the pdf is calculated**Returns** The value of the pdf in the specified point.**entropy** ()

Compute the entropy of the distribution.

Returns The value of the entropy of the distribution.**mle** (*theta, weights=None*)

Compute the (weighted) maximum likelihood estimate of the points, and update the distribution accordingly.

Parameters

- **theta** (*np.ndarray*) – a set of points, every row is a sample

- **weights** (*np.ndarray, None*) – a vector of weights. If specified the weighted maximum likelihood estimate is computed instead of the plain maximum likelihood. The number of elements of this vector must be equal to the number of rows of the theta matrix.

diff_log(theta)

Compute the derivative of the logarithm of the probability density function in the specified point.

Parameters

- **theta** (*np.ndarray*) – the point where the gradient of the log pdf is
- **computed.** –

Returns The gradient of the log pdf in the specified point.

get_parameters()

Getter.

Returns The current distribution parameters.

set_parameters(rho)

Setter.

Parameters **rho** (*np.ndarray*) – the vector of the new parameters to be used by the distribution

parameters_size

Property.

Returns The size of the distribution parameters.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

diff(theta)

Compute the derivative of the probability density function, in the specified point. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_\rho p(\theta) = p(\theta) \nabla_\rho \log p(\theta)$$

Parameters

- **theta** (*np.ndarray*) – the point where the gradient of the pdf is
- **calculated.** –

Returns The gradient of the pdf in the specified point.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file*, *full_save*, *folder=””*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

class *mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution*(*mu*,
sigma)

Bases: *mushroom_rl.distributions.distribution.Distribution*

Gaussian distribution with full covariance matrix. The parameters vector represents the mean and the Cholesky decomposition of the covariance matrix. This parametrization enforce the covariance matrix to be positive definite.

__init__(*mu*, *sigma*)

Constructor.

Parameters

- **mu** (*np.ndarray*) – initial mean of the distribution;
- **sigma** (*np.ndarray*) – initial covariance matrix of the distribution.

sample()

Draw a sample from the distribution.

Returns A random vector sampled from the distribution.

log_pdf(*theta*)

Compute the logarithm of the probability density function in the specified point

Parameters **theta** (*np.ndarray*) – the point where the log pdf is calculated

Returns The value of the log pdf in the specified point.

__call__(*theta*)

Compute the probability density function in the specified point

Parameters **theta** (*np.ndarray*) – the point where the pdf is calculated

Returns The value of the pdf in the specified point.

entropy()

Compute the entropy of the distribution.

Returns The value of the entropy of the distribution.

mle(*theta*, *weights=None*)

Compute the (weighted) maximum likelihood estimate of the points, and update the distribution accordingly.

Parameters

- **theta** (*np.ndarray*) – a set of points, every row is a sample
- **weights** (*np.ndarray, None*) – a vector of weights. If specified the weighted maximum likelihood estimate is computed instead of the plain maximum likelihood. The number of elements of this vector must be equal to the number of rows of the theta matrix.

diff_log(theta)

Compute the derivative of the logarithm of the probability density function in the specified point.

Parameters

- **theta** (*np.ndarray*) – the point where the gradient of the log pdf is
- **computed.** –

Returns The gradient of the log pdf in the specified point.

get_parameters()

Getter.

Returns The current distribution parameters.

set_parameters(rho)

Setter.

Parameters **rho** (*np.ndarray*) – the vector of the new parameters to be used by the distribution

parameters_size

Property.

Returns The size of the distribution parameters.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

diff(theta)

Compute the derivative of the probability density function, in the specified point. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_\rho p(\theta) = p(\theta) \nabla_\rho \log p(\theta)$$

Parameters

- **theta** (*np.ndarray*) – the point where the gradient of the pdf is
- **calculated.** –

Returns The gradient of the pdf in the specified point.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=’’*)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where the object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ‘’*) – subfolder to be used by the save method.

3.7 Environments

In mushroom_rl we distinguish between two different types of environment classes:

- proper environments
- generators

While environments directly implement the `Environment` interface, generators are a set of methods used to generate finite markov chains that represent a specific environment e.g., grid worlds.

3.7.1 Environments

Atari

class `mushroom_rl.environments.atari.MaxAndSkip` (*env, skip, max_pooling=True*)

Bases: `gym.core.Wrapper`

__init__ (*env, skip, max_pooling=True*)

Initialize self. See `help(type(self))` for accurate signature.

step (*action*)

Run one timestep of the environment’s dynamics. When end of episode is reached, you are responsible for calling `reset()` to reset this environment’s state.

Accepts an action and returns a tuple (observation, reward, done, info).

Parameters `action` (*object*) – an action provided by the agent

Returns agent’s observation of the current environment reward (float) : amount of reward returned after previous action done (bool): whether the episode has ended, in which case further step() calls will return undefined results info (dict): contains auxiliary diagnostic information (helpful for debugging, and sometimes learning)

Return type observation (object)

reset (**kwargs)

Resets the state of the environment and returns an initial observation.

Returns the initial observation.

Return type observation (object)

close ()

Override close in your subclass to perform any necessary cleanup.

Environments will automatically close() themselves when garbage collected or when the program exits.

render (mode='human', **kwargs)

Renders the environment.

The set of supported modes varies per environment. (And some environments do not support rendering at all.) By convention, if mode is:

- human: render to the current display or terminal and return nothing. Usually for human consumption.
- rgb_array: Return an numpy.ndarray with shape (x, y, 3), representing RGB values for an x-by-y pixel image, suitable for turning into a video.
- ansi: Return a string (str) or StringIO.StringIO containing a terminal-style text representation. The text can include newlines and ANSI escape sequences (e.g. for colors).

Note:

Make sure that your class's metadata 'render.modes' key includes the list of supported modes. It's recommended to call super() in implementations to use the functionality of this method.

Parameters **mode** (str) – the mode to render with

Example:

```
class MyEnv(Env): metadata = { 'render.modes': ['human', 'rgb_array'] }

def render(self, mode='human'):

    if mode == 'rgb_array': return np.array(...) # return RGB frame suitable for video
    elif mode == 'human': ... # pop up a window and render
    else: super(MyEnv, self).render(mode=mode) # just raise an exception
```

seed (seed=None)

Sets the seed for this env's random number generator(s).

Note: Some environments use multiple pseudorandom number generators. We want to capture all such seeds used in order to ensure that there aren't accidental correlations between multiple generators.

Returns

Returns the list of seeds used in this env's random number generators. The first value in the list should be the "main" seed, or the value which a reproducer should pass to 'seed'. Often, the main seed equals the provided 'seed', but this won't be true if seed=None, for example.

Return type list<bigint>

unwrapped

Completely unwrap this env.

Returns The base non-wrapped gym.Env instance

Return type gym.Env

```
class mushroom_rl.environments.atari.Atari(name, width=84, height=84,
                                             ends_at_life=False, max_pooling=True,
                                             history_length=4, max_no_op_actions=30)
```

Bases: *mushroom_rl.environments.environment.Environment*

The Atari environment as presented in: “Human-level control through deep reinforcement learning”. Mnih et al.. 2015.

```
__init__(name, width=84, height=84, ends_at_life=False, max_pooling=True, history_length=4,
        max_no_op_actions=30)
```

Constructor.

Parameters

- **name** (*str*) – id name of the Atari game in Gym;
- **width** (*int*, 84) – width of the screen;
- **height** (*int*, 84) – height of the screen;
- **ends_at_life** (*bool*, *False*) – whether the episode ends when a life is lost or not;
- **max_pooling** (*bool*, *True*) – whether to do max-pooling or average-pooling of the last two frames when using NoFrameskip;
- **history_length** (*int*, 4) – number of frames to form a state;
- **max_no_op_actions** (*int*, 30) – maximum number of no-op action to execute at the beginning of an episode.

reset (*state=None*)

Reset the current state.

Parameters **state** (*np.ndarray*, *None*) – the state to set to the current state.

Returns The current state.

step (*action*)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

static _bound (*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

seed(*seed*)

Set the seed of the environment.

Parameters **seed**(*float*) – the value of the seed.

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

set_episode_end(*ends_at_life*)

Setter.

Parameters **ends_at_life**(*bool*) – whether the episode ends when a life is lost or not.

Car on hill

class mushroom_rl.environments.car_on_hill.**CarOnHill**(*horizon=100, gamma=0.95*)

Bases: *mushroom_rl.environments.environment.Environment*

The Car On Hill environment as presented in: “Tree-Based Batch Mode Reinforcement Learning”. Ernst D. et al.. 2005.

__init__(*horizon=100, gamma=0.95*)

Constructor.

reset(*state=None*)

Reset the current state.

Parameters **state**(*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

step(*action*)

Move the agent from its current state according to the action.

Parameters **action**(*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

static _bound(*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

seed(*seed*)

Set the seed of the environment.

Parameters **seed**(*float*) – the value of the seed.

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

DeepMind Control Suite

```
class mushroom_rl.environments.dm_control_env.DMControl(domain_name, task_name,  
                                         horizon,                 gamma,  
                                         task_kwargs=None,  
                                         dt=0.01,  
                                         width_screen=480,  
                                         height_screen=480,  
                                         camera_id=0)
```

Bases: *mushroom_rl.environments.environment.Environment*

Interface for dm_control suite Mujoco environments. It makes it possible to use every dm_control suite Mujoco environment just providing the necessary information.

```
__init__(domain_name,   task_name,   horizon,   gamma,   task_kwargs=None,   dt=0.01,  
                                 width_screen=480, height_screen=480, camera_id=0)
```

Constructor.

Parameters

- **domain_name** (*str*) – name of the environment;
- **task_name** (*str*) – name of the task of the environment;
- **horizon** (*int*) – the horizon;
- **gamma** (*float*) – the discount factor;
- **task_kwargs** (*dict*, *None*) – parameters of the task;
- **dt** (*float*, *0.01*) – duration of a control step;
- **width_screen** (*int*, *480*) – width of the screen;
- **height_screen** (*int*, *480*) – height of the screen;
- **camera_id** (*int*, *0*) – position of camera to render the environment;

reset(*state=None*)

Reset the current state.

Parameters **state**(*np.ndarray*, *None*) – the state to set to the current state.

Returns The current state.

step(*action*)

Move the agent from its current state according to the action.

Parameters **action**(*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

static _bound(x, min_value, max_value)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

seed(seed)

Set the seed of the environment.

Parameters **seed** (*float*) – the value of the seed.

Finite MDP

class mushroom_rl.environments.finite_mdp.**FiniteMDP** (*p, rew, mu=None, gamma=0.9, horizon=inf*)

Bases: *mushroom_rl.environments.environment.Environment*

Finite Markov Decision Process.

__init__(p, rew, mu=None, gamma=0.9, horizon=inf)

Constructor.

Parameters

- **p** (*np.ndarray*) – transition probability matrix;
- **rew** (*np.ndarray*) – reward matrix;
- **mu** (*np.ndarray, None*) – initial state probability distribution;
- **gamma** (*float, 0*) – discount factor;
- **horizon** (*int, np.inf*) – the horizon.

reset(state=None)

Reset the current state.

Parameters **state** (*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

step(action)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

static _bound(*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns**seed**(*seed*)

Set the seed of the environment.

Parameters **seed**(*float*) – the value of the seed.

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

Grid World

class mushroom_rl.environments.grid_world.**AbstractGridWorld**(*mdp_info, height, width, start, goal*)

Bases: *mushroom_rl.environments.environment.Environment*

Abstract class to build a grid world.

__init__(*mdp_info, height, width, start, goal*)

Constructor.

Parameters

- **height** (*int*) – height of the grid;
- **width** (*int*) – width of the grid;
- **start** (*tuple*) – x-y coordinates of the goal;
- **goal** (*tuple*) – x-y coordinates of the goal.

reset(*state=None*)

Reset the current state.

Parameters **state**(*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

step(*action*)

Move the agent from its current state according to the action.

Parameters **action**(*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

static _bound(*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

seed(*seed*)

Set the seed of the environment.

Parameters **seed**(*float*) – the value of the seed.

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

class mushroom_rl.environments.grid_world.**GridWorld**(*height, width, goal, start=(0, 0)*)

Bases: *mushroom_rl.environments.grid_world.AbstractGridWorld*

Standard grid world.

__init__(*height, width, goal, start=(0, 0)*)

Constructor.

Parameters

- **height** (*int*) – height of the grid;
- **width** (*int*) – width of the grid;
- **start** (*tuple*) – x-y coordinates of the goal;
- **goal** (*tuple*) – x-y coordinates of the goal.

static _bound(*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

reset(*state=None*)

Reset the current state.

Parameters **state**(*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

seed (*seed*)

Set the seed of the environment.

Parameters **seed** (*float*) – the value of the seed.

step (*action*)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop ()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

```
class mushroom_rl.environments.grid_world.GridWorldVanHasselt (height=3,
                                                               width=3,
                                                               goal=(0, 2),
                                                               start=(2, 0))
```

Bases: *mushroom_rl.environments.grid_world.AbstractGridWorld*

A variant of the grid world as presented in: “Double Q-Learning”. Hasselt H. V.. 2010.

__init__ (*height=3, width=3, goal=(0, 2), start=(2, 0)*)

Constructor.

Parameters

- **height** (*int*) – height of the grid;
- **width** (*int*) – width of the grid;
- **start** (*tuple*) – x-y coordinates of the goal;
- **goal** (*tuple*) – x-y coordinates of the goal.

static _bound (*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

reset (*state=None*)

Reset the current state.

Parameters **state** (*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

seed (*seed*)

Set the seed of the environment.

Parameters **seed** (*float*) – the value of the seed.

step (*action*)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop ()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

Gym

class *mushroom_rl.environments.gym_env.Gym* (*name, horizon, gamma, **env_args*)

Bases: *mushroom_rl.environments.environment.Environment*

Interface for OpenAI Gym environments. It makes it possible to use every Gym environment just providing the id, except for the Atari games that are managed in a separate class.

__init__ (*name, horizon, gamma, **env_args*)

Constructor.

Parameters

- **name** (*str*) – gym id of the environment;
- **horizon** (*int*) – the horizon;
- **gamma** (*float*) – the discount factor;
- ****env_args** – other gym environment parameters.

reset (*state=None*)

Reset the current state.

Parameters **state** (*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

step (*action*)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

static _bound (*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

seed(*seed*)

Set the seed of the environment.

Parameters **seed**(*float*) – the value of the seed.

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

Inverted pendulum

```
class mushroom_rl.environments.inverted_pendulum.InvertedPendulum(random_start=False,
                                                               m=1.0,
                                                               l=1.0,
                                                               g=9.8,
                                                               mu=0.01,
                                                               max_u=5.0,
                                                               horizon=5000,
                                                               gamma=0.99)
```

Bases: *mushroom_rl.environments.environment.Environment*

The Inverted Pendulum environment (continuous version) as presented in: “Reinforcement Learning In Continuous Time and Space”. Doya K.. 2000. “Off-Policy Actor-Critic”. Degris T. et al.. 2012. “Deterministic Policy Gradient Algorithms”. Silver D. et al. 2014.

```
__init__(random_start=False, m=1.0, l=1.0, g=9.8, mu=0.01, max_u=5.0, horizon=5000,
          gamma=0.99)
```

Constructor.

Parameters

- **random_start** (*bool*, *False*) – whether to start from a random position or from the horizontal one;
- **m** (*float*, *1.0*) – mass of the pendulum;
- **l** (*float*, *1.0*) – length of the pendulum;
- **g** (*float*, *9.8*) – gravity acceleration constant;
- **mu** (*float*, *1e-2*) – friction constant of the pendulum;
- **max_u** (*float*, *5.0*) – maximum allowed input torque;
- **horizon** (*int*, *5000*) – horizon of the problem;
- **gamma** (*int*, *99*) – discount factor.

reset(*state=None*)

Reset the current state.

Parameters **state**(*np.ndarray*, *None*) – the state to set to the current state.

Returns The current state.

step(*action*)

Move the agent from its current state according to the action.

Parameters **action**(*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

static _bound(*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

seed(*seed*)

Set the seed of the environment.

Parameters **seed**(*float*) – the value of the seed.

Cart Pole

```
class mushroom_rl.environments.cart_pole.CartPole(m=2.0, M=8.0, l=0.5, g=9.8,
mu=0.01, max_u=50.0,
noise_u=10.0, horizon=3000,
gamma=0.95)
```

Bases: *mushroom_rl.environments.environment.Environment*

The Inverted Pendulum on a Cart environment as presented in: “Least-Squares Policy Iteration”. Lagoudakis M. G. and Parr R.. 2003.

```
__init__(m=2.0, M=8.0, l=0.5, g=9.8, mu=0.01, max_u=50.0, noise_u=10.0, horizon=3000,
gamma=0.95)
```

Constructor.

Parameters

- **m**(*float, 2.0*) – mass of the pendulum;
- **M**(*float, 8.0*) – mass of the cart;
- **l**(*float, 5*) – length of the pendulum;
- **g**(*float, 9.8*) – gravity acceleration constant;
- **mu**(*float, 1e-2*) – friction constant of the pendulum;
- **max_u**(*float, 50.*) – maximum allowed input torque;

- **noise_u** (*float*, *10.*) – maximum noise on the action;
- **horizon** (*int*, *3000*) – horizon of the problem;
- **gamma** (*int*, *95*) – discount factor.

reset (*state=None*)
Reset the current state.

Parameters **state** (*np.ndarray*, *None*) – the state to set to the current state.

Returns The current state.

step (*action*)
Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop ()
Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

static _bound (*x, min_value, max_value*)
Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info
An object containing the info of the environment.

Type Returns

seed (*seed*)
Set the seed of the environment.

Parameters **seed** (*float*) – the value of the seed.

LQR

```
class mushroom_rl.environments.lqr.LQR(A, B, Q, R, max_pos=inf, max_action=inf, random_init=False, episodic=False, gamma=0.9, horizon=50, initial_state=None)
```

Bases: *mushroom_rl.environments.environment.Environment*

This class implements a Linear-Quadratic Regulator. This task aims to minimize the undesired deviations from nominal values of some controller settings in control problems. The system equations in this task are:

$$x_{t+1} = Ax_t + Bu_t$$

where *x* is the state and *u* is the control signal.

The reward function is given by:

$$r_t = - (x_t^T Q x_t + u_t^T R u_t)$$

“Policy gradient approaches for multi-objective sequential decision making”. Parisi S., Pirotta M., Smacchia N., Bascetta L., Restelli M.. 2014

__init__ (*A, B, Q, R, max_pos=inf, max_action=inf, random_init=False, episodic=False, gamma=0.9, horizon=50, initial_state=None*)
Constructor.

Args: *A* (np.ndarray): the state dynamics matrix; *B* (np.ndarray): the action dynamics matrix; *Q* (np.ndarray): reward weight matrix for state; *R* (np.ndarray): reward weight matrix for action; *max_pos* (float, np.inf): maximum value of the state; *max_action* (float, np.inf): maximum value of the action; *random_init* (bool, False): start from a random state; *episodic* (bool, False): end the episode when the state goes over the threshold; *gamma* (float, 0.9): discount factor; *horizon* (int, 50): horizon of the mdp.

static generate (*dimensions=None, s_dim=None, a_dim=None, max_pos=inf, max_action=inf, eps=0.1, index=0, scale=1.0, random_init=False, episodic=False, gamma=0.9, horizon=50, initial_state=None*)
Factory method that generates an lqr with identity dynamics and symmetric reward matrices.

Parameters

- **dimensions** (*int*) – number of state-action dimensions;
- **s_dim** (*int*) – number of state dimensions;
- **a_dim** (*int*) – number of action dimensions;
- **max_pos** (*float, np.inf*) – maximum value of the state;
- **max_action** (*float, np.inf*) – maximum value of the action;
- **eps** (*double, 1*) – reward matrix weights specifier;
- **index** (*int, 0*) – selector for the principal state;
- **scale** (*float, 1.0*) – scaling factor for the reward function;
- **random_init** (*bool, False*) – start from a random state;
- **episodic** (*bool, False*) – end the episode when the state goes over the threshold;
- **gamma** (*float, 9*) – discount factor;
- **horizon** (*int, 50*) – horizon of the mdp.

reset (*state=None*)

Reset the current state.

Parameters **state** (*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

step (*action*)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

static _bound(*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns**seed**(*seed*)

Set the seed of the environment.

Parameters **seed**(*float*) – the value of the seed.

stop()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

Mujoco**class** mushroom_rl.environments.mujoco.**ObservationType**

Bases: enum.Enum

An enum indicating the type of data that should be added to the observation of the environment, can be Joint-/Body-/Site- positions and velocities.

class mushroom_rl.environments.mujoco.**MuJoCo**(*file_name, actuation_spec, observation_spec, gamma, horizon, n_substeps=1, n_intermediate_steps=1, additional_data_spec=None, collision_groups=None*)

Bases: *mushroom_rl.environments.environment.Environment*

Class to create a Mushroom environment using the MuJoCo simulator.

__init__(*file_name, actuation_spec, observation_spec, gamma, horizon, n_substeps=1, n_intermediate_steps=1, additional_data_spec=None, collision_groups=None*)

Constructor.

Parameters

- **file_name** (*string*) – The path to the XML file with which the environment should be created;
- **actuation_spec** (*list*) – A list specifying the names of the joints which should be controllable by the agent. Can be left empty when all actuators should be used;
- **observation_spec** (*list*) – A list containing the names of data that should be made available to the agent as an observation and their type (ObservationType). An entry in the list is given by: (name, type);
- **gamma** (*float*) – The discounting factor of the environment;
- **horizon** (*int*) – The maximum horizon for the environment;

- **n_substeps** (*int*) – The number of substeps to use by the MuJoCo simulator. An action given by the agent will be applied for n_substeps before the agent receives the next observation and can act accordingly;
- **n_intermediate_steps** (*int*) – The number of steps between every action taken by the agent. Similar to n_substeps but allows the user to modify, control and access intermediate states.
- **additional_data_spec** (*list*) – A list containing the data fields of interest, which should be read from or written to during simulation. The entries are given as the following tuples: (key, name, type) key is a string for later referencing in the “read_data” and “write_data” methods. The name is the name of the object in the XML specification and the type is the ObservationType;
- **collision_groups** (*list*) – A list containing groups of geoms for which collisions should be checked during simulation via check_collision. The entries are given as: (key, geom_names), where key is a string for later referencing in the “check_collision” method, and geom_names is a list of geom names in the XML specification.

seed (*seed*)

Set the seed of the environment.

Parameters **seed** (*float*) – the value of the seed.

reset (*state=None*)

Reset the current state.

Parameters **state** (*np.ndarray, None*) – the state to set to the current state.

Returns The current state.

step (*action*)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop ()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

_preprocess_action (*action*)

Compute a transformation of the action provided to the environment.

Parameters **action** (*np.ndarray*) – numpy array with the actions provided to the environment.

Returns The action to be used for the current step

_step_init (*state, action*)

Allows information to be initialized at the start of a step.

_compute_action (*action*)

Compute a transformation of the action at every intermediate step. Useful to add control signals simulated directly in python.

Parameters **action** (*np.ndarray*) – numpy array with the actions provided at every step.

Returns The action to be set in the actual mujoco simulation.

_simulation_pre_step()

Allows information to be accessed and changed at every intermediate step before taking a step in the mujoco simulation. Can be useful to apply an external force/torque to the specified bodies.

ex: apply a force over X to the torso: force = [200, 0, 0] torque = [0, 0, 0]
`self.sim.data.xfrc_applied[self.sim.model._body_name2id["torso"],:] = force + torque`

_simulation_post_step()

Allows information to be accessed at every intermediate step after taking a step in the mujoco simulation. Can be useful to average forces over all intermediate steps.

_step_finalize()

Allows information to be accessed at the end of a step.

_read_data(name)

Read data from the MuJoCo data structure.

Parameters `name` (*string*) – A name referring to an entry contained in the additional_data_spec list handed to the constructor.

Returns The desired data as a one-dimensional numpy array.

_write_data(name, value)

Write data to the MuJoCo data structure.

Parameters

- `name` (*string*) – A name referring to an entry contained in the additional_data_spec list handed to the constructor;
- `value` (*ndarray*) – The data that should be written.

_check_collision(group1, group2)

Check for collision between the specified groups.

Parameters

- `group1` (*string*) – A name referring to an entry contained in the collision_groups list handed to the constructor;
- `group2` (*string*) – A name referring to an entry contained in the collision_groups list handed to the constructor.

Returns A flag indicating whether a collision occurred between the given groups or not.

_get_collision_force(group1, group2)

Returns the collision force and torques between the specified groups.

Parameters

- `group1` (*string*) – A name referring to an entry contained in the collision_groups list handed to the constructor;
- `group2` (*string*) – A name referring to an entry contained in the collision_groups list handed to the constructor.

Returns A 6D vector specifying the collision forces/torques[3D force + 3D torque] between the given groups. Vector of 0's in case there was no collision. <http://mujoco.org/book/programming.html#siContact>

_reward(state, action, next_state)

Compute the reward based on the given transition.

Parameters

- **state** (*np.array*) – the current state of the system;
- **action** (*np.array*) – the action that is applied in the current state;
- **next_state** (*np.array*) – the state reached after applying the given action.

Returns The reward as a floating point scalar value.

_is_absorbing(state)

Check whether the given state is an absorbing state or not.

Parameters **state** (*np.array*) – the state of the system.

Returns A boolean flag indicating whether this state is absorbing or not.

_setup()

A function that allows to execute setup code after an environment reset.

_load_simulation(file_name, n_substeps)

Load mujoco model. Can be overridden to provide custom load functions.

Parameters **file_name** – The path to the XML file with which the environment should be created;

Returns The loaded mujoco model.

static _bound(x, min_value, max_value)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

Puddle World

```
class mushroom_rl.environments.puddle_world.PuddleWorld(start=None, goal=None, goal_threshold=0.1, noise_step=0.025, noise_reward=0, reward_goal=0.0, thrust=0.05, puddle_center=None, puddle_width=None, gamma=0.99, horizon=5000)
```

Bases: *mushroom_rl.environments.environment.Environment*

Puddle world as presented in: “Off-Policy Actor-Critic”. Degris T. et al.. 2012.

```
__init__(start=None, goal=None, goal_threshold=0.1, noise_step=0.025, noise_reward=0, reward_goal=0.0, thrust=0.05, puddle_center=None, puddle_width=None, gamma=0.99, horizon=5000)
```

Constructor.

Parameters

- **start** (*np.array*, *None*) – starting position of the agent;
- **goal** (*np.array*, *None*) – goal position;
- **goal_threshold** (*float*, *1*) – distance threshold of the agent from the goal to consider it reached;
- **noise_step** (*float*, *0.25*) – noise in actions;
- **noise_reward** (*float*, *0*) – standard deviation of gaussian noise in reward;
- **reward_goal** (*float*, *0*) – reward obtained reaching goal state;
- **thrust** (*float*, *0.5*) – distance walked during each action;
- **puddle_center** (*np.array*, *None*) – center of the puddle;
- **puddle_width** (*np.array*, *None*) – width of the puddle;

reset (*state=None*)

Reset the current state.

Parameters **state** (*np.ndarray*, *None*) – the state to set to the current state.

Returns The current state.

step (*action*)

Move the agent from its current state according to the action.

Parameters **action** (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop ()

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

static _bound (*x, min_value, max_value*)

Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info

An object containing the info of the environment.

Type Returns

seed (*seed*)

Set the seed of the environment.

Parameters **seed** (*float*) – the value of the seed.

Segway

```
class mushroom_rl.environments.segway.Segway(random_start=False)
Bases: mushroom_rl.environments.environment.Environment
```

The Segway environment (continuous version) as presented in: “Deep Learning for Actor-Critic Reinforcement Learning”. Xueli Jia. 2015.

```
__init__(random_start=False)
```

Constructor.

Parameters `random_start` (`bool`, `False`) – whether to start from a random position or from the horizontal one.

```
reset(state=None)
```

Reset the current state.

Parameters `state` (`np.ndarray`, `None`) – the state to set to the current state.

Returns The current state.

```
step(action)
```

Move the agent from its current state according to the action.

Parameters `action` (`np.ndarray`) – the action to execute.

Returns The state reached by the agent executing `action` in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

```
static _bound(x, min_value, max_value)
```

Method used to bound state and action variables.

Parameters

- `x` – the variable to bound;
- `min_value` – the minimum value;
- `max_value` – the maximum value;

Returns The bounded variable.

```
info
```

An object containing the info of the environment.

Type Returns

```
seed(seed)
```

Set the seed of the environment.

Parameters `seed` (`float`) – the value of the seed.

```
stop()
```

Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

Ship steering

```
class mushroom_rl.environments.ship_steering.ShipSteering(small=True,
                                                               n_steps_action=3)
Bases: mushroom_rl.environments.environment.Environment
```

The Ship Steering environment as presented in: “Hierarchical Policy Gradient Algorithms”. Ghavamzadeh M. and Mahadevan S.. 2013.

__init__(small=True, n_steps_action=3)
Constructor.

Parameters

- **small** (*bool*, *True*) – whether to use a small state space or not.
- **n_steps_action** (*int*, *3*) – number of integration intervals for each step of the mdp.

reset(state=None)
Reset the current state.

Parameters state (*np.ndarray*, *None*) – the state to set to the current state.

Returns The current state.

step(action)
Move the agent from its current state according to the action.

Parameters action (*np.ndarray*) – the action to execute.

Returns The state reached by the agent executing *action* in its current state, the reward obtained in the transition and a flag to signal if the next state is absorbing. Also an additional dictionary is returned (possibly empty).

stop()
Method used to stop an mdp. Useful when dealing with real world environments, simulators, or when using openai-gym rendering

static _bound(x, min_value, max_value)
Method used to bound state and action variables.

Parameters

- **x** – the variable to bound;
- **min_value** – the minimum value;
- **max_value** – the maximum value;

Returns The bounded variable.

info
An object containing the info of the environment.

Type Returns

seed(seed)
Set the seed of the environment.

Parameters seed (*float*) – the value of the seed.

3.7.2 Generators

Grid world

```
mushroom_rl.environments.generators.grid_world.generate_grid_world(grid, prob,
pos_rew,
neg_rew,
gamma=0.9,
hori-
zon=100)
```

This Grid World generator requires a .txt file to specify the shape of the grid world and the cells. There are five types of cells: ‘S’ is the starting position where the agent is; ‘G’ is the goal state; ‘.’ is a normal cell; ‘*’ is a hole, when the agent steps on a hole, it receives a negative reward and the episode ends; ‘#’ is a wall, when the agent is supposed to step on a wall, it actually remains in its current state. The initial states distribution is uniform among all the initial states provided.

The grid is expected to be rectangular.

Parameters

- **grid** (*str*) – the path of the file containing the grid structure;
- **prob** (*float*) – probability of success of an action;
- **pos_rew** (*float*) – reward obtained in goal states;
- **neg_rew** (*float*) – reward obtained in “hole” states;
- **gamma** (*float*, 9) – discount factor;
- **horizon** (*int*, 100) – the horizon.

Returns A FiniteMDP object built with the provided parameters.

```
mushroom_rl.environments.generators.grid_world.parse_grid(grid)
```

Parse the grid file:

Parameters **grid** (*str*) – the path of the file containing the grid structure;

Returns A list containing the grid structure.

```
mushroom_rl.environments.generators.grid_world.compute_probabilities(grid_map,
cell_list,
prob)
```

Compute the transition probability matrix.

Parameters

- **grid_map** (*list*) – list containing the grid structure;
- **cell_list** (*list*) – list of non-wall cells;
- **prob** (*float*) – probability of success of an action.

Returns The transition probability matrix;

```
mushroom_rl.environments.generators.grid_world.compute_reward(grid_map,
cell_list, pos_rew,
neg_rew)
```

Compute the reward matrix.

Parameters

- **grid_map** (*list*) – list containing the grid structure;
- **cell_list** (*list*) – list of non-wall cells;
- **pos_rew** (*float*) – reward obtained in goal states;

- **neg_rew** (*float*) – reward obtained in “hole” states;

Returns The reward matrix.

```
mushroom_rl.environments.generators.grid_world.compute_mu(grid_map, cell_list)
Compute the initial states distribution.
```

Parameters

- **grid_map** (*list*) – list containing the grid structure;
- **cell_list** (*list*) – list of non-wall cells.

Returns The initial states distribution.

Simple chain

```
mushroom_rl.environments.generators.simple_chain.generate_simple_chain(state_n,
goal_states,
prob,
rew,
mu=None,
gamma=0.9,
horizon=100)
```

Simple chain generator.

Parameters

- **state_n** (*int*) – number of states;
- **goal_states** (*list*) – list of goal states;
- **prob** (*float*) – probability of success of an action;
- **rew** (*float*) – reward obtained in goal states;
- **mu** (*np.ndarray*) – initial state probability distribution;
- **gamma** (*float*, 0.9) – discount factor;
- **horizon** (*int*, 100) – the horizon.

Returns A FiniteMDP object built with the provided parameters.

```
mushroom_rl.environments.generators.simple_chain.compute_probabilities(state_n,
prob)
```

Compute the transition probability matrix.

Parameters

- **state_n** (*int*) – number of states;
- **prob** (*float*) – probability of success of an action.

Returns The transition probability matrix;

```
mushroom_rl.environments.generators.simple_chain.compute_reward(state_n,
goal_states,
rew)
```

Compute the reward matrix.

Parameters

- **state_n** (*int*) – number of states;

- **goal_states** (*list*) – list of goal states;
- **rew** (*float*) – reward obtained in goal states.

Returns The reward matrix.

Taxi

```
mushroom_rl.environments.generators.taxi.generate_taxi(grid, prob=0.9, rew=(0, 1, 3, 15), gamma=0.99, horizon=np.inf)
```

This Taxi generator requires a .txt file to specify the shape of the grid world and the cells. There are five types of cells: ‘S’ is the starting where the agent is; ‘G’ is the goal state; ‘.’ is a normal cell; ‘F’ is a passenger, when the agent steps on a hole, it picks up it. ‘#’ is a wall, when the agent is supposed to step on a wall, it actually remains in its current state. The initial states distribution is uniform among all the initial states provided. The episode terminates when the agent reaches the goal state. The reward is always 0, except for the goal state where it depends on the number of collected passengers. Each action has a certain probability of success and, if it fails, the agent goes in a perpendicular direction from the supposed one.

The grid is expected to be rectangular.

This problem is inspired from: “Bayesian Q-Learning”. Dearden R. et al.. 1998.

Parameters

- **grid** (*str*) – the path of the file containing the grid structure;
- **prob** (*float*, 0.9) – probability of success of an action;
- **rew** (*tuple*, (0, 1, 3, 15)) – rewards obtained in goal states;
- **gamma** (*float*, 0.99) – discount factor;
- **horizon** (*int*, np.inf) – the horizon.

Returns A FiniteMDP object built with the provided parameters.

```
mushroom_rl.environments.generators.taxi.parse_grid(grid)
```

Parse the grid file:

Parameters **grid** (*str*) – the path of the file containing the grid structure.

Returns A list containing the grid structure.

```
mushroom_rl.environments.generators.taxi.compute_probabilities(grid_map, cell_list, passenger_list, prob)
```

Compute the transition probability matrix.

Parameters

- **grid_map** (*list*) – list containing the grid structure;
- **cell_list** (*list*) – list of non-wall cells;
- **passenger_list** (*list*) – list of passenger cells;
- **prob** (*float*) – probability of success of an action.

Returns The transition probability matrix;

```
mushroom_rl.environments.generators.taxi.compute_reward(grid_map, cell_list, passenger_list, rew)
```

Compute the reward matrix.

Parameters

- **grid_map** (*list*) – list containing the grid structure;
- **cell_list** (*list*) – list of non-wall cells;
- **passenger_list** (*list*) – list of passenger cells;
- **rew** (*tuple*) – rewards obtained in goal states.

Returns The reward matrix.

```
mushroom_rl.environments.generators.taxi.compute_mu(grid_map, cell_list, passenger_list)
```

Compute the initial states distribution.

Parameters

- **grid_map** (*list*) – list containing the grid structure;
- **cell_list** (*list*) – list of non-wall cells;
- **passenger_list** (*list*) – list of passenger cells.

Returns The initial states distribution.

3.8 Features

The features in MushroomRL are 1-D arrays computed applying a specified function to a raw input, e.g. polynomial features of the state of an MDP. MushroomRL supports three types of features:

- basis functions;
- tensor basis functions;
- tiles.

The tensor basis functions are a PyTorch implementation of the standard basis functions. They are less straightforward than the standard ones, but they are faster to compute as they can exploit parallel computing, e.g. GPU-acceleration and multi-core systems.

All the types of features are exposed by a single factory method `Features` that builds the one requested by the user.

```
mushroom_rl.features.features.Features(basis_list=None, tilings=None, tensor_list=None, n_outputs=None, function=None)
```

Factory method to build the requested type of features. The types are mutually exclusive.

Possible features are tilings (`tilings`), basis functions (`basis_list`), tensor basis (`tensor_list`), and functional mappings (`n_outputs` and `function`).

The difference between `basis_list` and `tensor_list` is that the former is a list of python classes each one evaluating a single element of the feature vector, while the latter consists in a list of PyTorch modules that can be used to build a PyTorch network. The use of `tensor_list` is a faster way to compute features than `basis_list` and is suggested when the computation of the requested features is slow (see the Gaussian radial basis function implementation as an example). A functional mapping applies a function to the input computing an `n_outputs`-dimensional vector, where the mapping is expressed by `function`. If `function` is not provided, the identity is used.

Parameters

- **basis_list** (*list, None*) – list of basis functions;
- **tilings** (*[object, list], None*) – single object or list of tilings;

- **tensor_list** (*list, None*) – list of dictionaries containing the instructions to build the requested tensors;
- **n_outputs** (*int, None*) – dimensionality of the feature mapping;
- **function** (*object, None*) – a callable function to be used as feature mapping. Only needed when using a functional mapping.

Returns The class implementing the requested type of features.

`mushroom_rl.features.features.get_action_features(phi_state, action, n_actions)`

Compute an array of size $\text{len}(\phi\text{phi_state}) * \text{n_actions}$ filled with zeros, except for elements from $\text{len}(\phi\text{phi_state}) * \text{action}$ to $\text{len}(\phi\text{phi_state}) * (\text{action} + 1)$ that are filled with $\phi\text{phi_state}$. This is used to compute state-action features.

Parameters

- **phi_state** (*np.ndarray*) – the feature of the state;
- **action** (*np.ndarray*) – the action whose features have to be computed;
- **n_actions** (*int*) – the number of actions.

Returns The state-action features.

The factory method returns a class that extends the abstract class `FeatureImplementation`.

The documentation for every feature type can be found here:

3.8.1 Basis

Fourier

`class mushroom_rl.features.basis.fourier.FourierBasis(low, delta, c, dimensions=None)`

Bases: `object`

Class implementing Fourier basis functions. The value of the feature is computed using the formula:

$$\sum \cos \pi(X - m) / \Delta c$$

where X is the input, m is the vector of the minimum input values (for each dimensions), Delta is the vector of maximum

`__init__(low, delta, c, dimensions=None)`

Constructor.

Parameters

- **low** (*np.ndarray*) – vector of minimum values of the input variables;
- **delta** (*np.ndarray*) – vector of the maximum difference between two values of the input variables, i.e. delta = high - low;
- **c** (*np.ndarray*) – vector of weights for the state variables;
- **dimensions** (*list, None*) – list of the dimensions of the input to be considered by the feature.

`__call__(x)`

Call self as a function.

`static generate(low, high, n, dimensions=None)`

Factory method to build a set of fourier basis.

Parameters

- **low** (*np.ndarray*) – vector of minimum values of the input variables;
- **high** (*np.ndarray*) – vector of maximum values of the input variables;
- **n** (*int*) – number of harmonics to consider for each state variable
- **dimensions** (*list, None*) – list of the dimensions of the input to be considered by the features.

Returns The list of the generated fourier basis functions.

Gaussian RBF

```
class mushroom_rl.features.basis.gaussian_rbf.GaussianRBF(mean, scale, dimensions=None)
```

Bases: *object*

Class implementing Gaussian radial basis functions. The value of the feature is computed using the formula:

$$\sum \frac{(X_i - \mu_i)^2}{\sigma_i}$$

where X is the input, mu is the mean vector and sigma is the scale parameter vector.

__init__ (*mean, scale, dimensions=None*)

Constructor.

Parameters

- **mean** (*np.ndarray*) – the mean vector of the feature;
- **scale** (*np.ndarray*) – the scale vector of the feature;
- **dimensions** (*list, None*) – list of the dimensions of the input to be considered by the feature. The number of dimensions must match the dimensionality of *mean* and *scale*.

__call__ (*x*)

Call self as a function.

static generate (*n_centers, low, high, dimensions=None*)

Factory method to build uniformly spaced gaussian radial basis functions with a 25% overlap.

Parameters

- **n_centers** (*list*) – list of the number of radial basis functions to be used for each dimension.
- **low** (*np.ndarray*) – lowest value for each dimension;
- **high** (*np.ndarray*) – highest value for each dimension;
- **dimensions** (*list, None*) – list of the dimensions of the input to be considered by the feature. The number of dimensions must match the number of elements in *n_centers* and *low*.

Returns The list of the generated radial basis functions.

Polynomial

```
class mushroom_rl.features.basis.polynomial.PolynomialBasis(dimensions=None,  
                                                               degrees=None)
```

Bases: object

Class implementing polynomial basis functions. The value of the feature is computed using the formula:

$$\prod X_i^{d_i}$$

where X is the input and d is the vector of the exponents of the polynomial.

```
__init__(dimensions=None, degrees=None)
```

Constructor. If both parameters are None, the constant feature is built.

Parameters

- **dimensions** (list, None) – list of the dimensions of the input to be considered by the feature;
- **degrees** (list, None) – list of the degrees of each dimension to be considered by the feature. It must match the number of elements of dimensions.

```
__call__(x)
```

Call self as a function.

```
static _compute_exponents(order, n_variables)
```

Find the exponents of a multivariate polynomial expression of order `order` and `n_variables` number of variables.

Parameters

- **order** (int) – the maximum order of the polynomial;
- **n_variables** (int) – the number of elements of the input vector.

Yields The current exponent of the polynomial.

```
static generate(max_degree, input_size)
```

Factory method to build a polynomial of order `max_degree` based on the first `input_size` dimensions of the input.

Parameters

- **max_degree** (int) – maximum degree of the polynomial;
- **input_size** (int) – size of the input.

Returns The list of the generated polynomial basis functions.

3.8.2 Tensors

Gaussian tensor

```
class mushroom_rl.features.tensors.gaussian_tensor.GaussianRBFTensor(mu,  
                                                               scale,  
                                                               dim,  
                                                               use_cuda)
```

Bases: sphinx.ext.autodoc.importer._MockObject

Pytorch module to implement a gaussian radial basis function.

`__init__(mu, scale, dim, use_cuda)`

Constructor.

Parameters

- **mu** (`np.ndarray`) – centers of the gaussian RBFs;
- **scale** (`np.ndarray`) – scales for the RBFs;
- **dim** (`np.ndarray`) – list of dimension to be considered for the computation of the features;
- **use_cuda** (`bool`) – whether to use cuda for the computation or not.

`static generate(n_centers, low, high, dimensions=None, use_cuda=False)`

Factory method that generates the list of dictionaries to build the tensors representing a set of uniformly spaced Gaussian radial basis functions with a 25% overlap.

Parameters

- **n_centers** (`list`) – list of the number of radial basis functions to be used for each dimension;
- **low** (`np.ndarray`) – lowest value for each dimension;
- **high** (`np.ndarray`) – highest value for each dimension;
- **dimensions** (`list, None`) – list of the dimensions of the input to be considered by the feature. The number of dimensions must match the number of elements in `n_centers` and `low`;
- **use_cuda** (`bool`) – whether to use cuda for the computation or not.

Returns The list of dictionaries as described above.

3.8.3 Tiles

`class mushroom_rl.features.tiles.tiles.Tiles(x_range, n_tiles, state_components=None)`

Bases: object

Class implementing rectangular tiling. For each point in the state space, this class can be used to compute the index of the corresponding tile.

`__init__(x_range, n_tiles, state_components=None)`

Constructor.

Parameters

- **x_range** (`list`) – list of two-elements lists specifying the range of each state variable;
- **n_tiles** (`list`) – list of the number of tiles to be used for each dimension.
- **state_components** (`list, None`) – list of the dimensions of the input to be considered by the tiling. The number of elements must match the number of elements in `x_range` and `n_tiles`.

`__call__(x)`

Call self as a function.

`static generate(n_tilings, n_tiles, low, high, uniform=False)`Factory method to build `n_tilings` tilings of `n_tiles` tiles with a range between `low` and `high` for each dimension.**Parameters**

- **n_tilings** (*int*) – number of tilings;
- **n_tiles** (*list*) – number of tiles for each tilings for each dimension;
- **low** (*np.ndarray*) – lowest value for each dimension;
- **high** (*np.ndarray*) – highest value for each dimension.
- **uniform** (*bool, False*) – if True the displacement for each tiling will be w/n_tilings, where w is the tile width. Otherwise, the displacement will be k*w/n_tilings, where k=2i+1, where i is the dimension index.

Returns The list of the generated tiles.

3.9 Policy

```
class mushroom_rl.policy.policy.Policy
Bases: mushroom_rl.core.serialization.Serializable
```

Interface representing a generic policy. A policy is a probability distribution that gives the probability of taking an action given a specified state. A policy is used by mushroom agents to interact with the environment.

__call__ (*args)
Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

draw_action (*state*)
Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

reset ()
Useful when the policy needs a special initialization at the beginning of an episode.

__init__
Initialize self. See help(type(self)) for accurate signature.

_add_save_attr (**attr_dict)
Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load ()
This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

classmethod **load** (*path*)
Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path*, *str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, '') – subfolder to be used by the save method.

class mushroom_rl.policy.policy.**ParametricPolicy**

Bases: *mushroom_rl.policy.policy.Policy*

Interface for a generic parametric policy. A parametric policy is a policy that depends on set of parameters, called the policy weights. If the policy is differentiable, the derivative of the probability for a specified state-action pair can be provided.

diff_log (*state*, *action*)

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the gradient is computed
- **action** (*np.ndarray*) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

diff (*state*, *action*)

Compute the derivative of the probability density function, in the specified state and action pair. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the derivative is computed
- **action** (*np.ndarray*) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

set_weights (*weights*)

Setter.

Parameters **weights** (*np.ndarray*) – the vector of the new weights to be used by the policy.

get_weights()

Getter.

Returns The current policy weights.

weights_size

Property.

Returns The size of the policy weights.

__call__(*args)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy. If the action space is continuous, state and action must be provided

__init__

Initialize self. See help(type(self)) for accurate signature.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=”)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, '') – subfolder to be used by the save method.

3.9.1 Deterministic policy

```
class mushroom_rl.policy.deterministic_policy.DeterministicPolicy(mu)
Bases: mushroom_rl.policy.policy.ParametricPolicy
```

Simple parametric policy representing a deterministic policy. As deterministic policies are degenerate probability functions where all the probability mass is on the deterministic action, they are not differentiable, even if the mean value approximator is differentiable.

__init__(*mu*)

Constructor.

Parameters **mu** (*Regressor*) – the regressor representing the action to select in each state.

get_regressor()

Getter.

Returns the regressor that is used to map state to actions.

__call__(*state, action*)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

draw_action(*state*)

Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

set_weights(*weights*)

Setter.

Parameters **weights** (*np.ndarray*) – the vector of the new weights to be used by the policy.

get_weights()

Getter.

Returns The current policy weights.

weights_size

Property.

Returns The size of the policy weights.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`copy()`

Returns A deepcopy of the agent.

`diff(state, action)`

Compute the derivative of the probability density function, in the specified state and action pair. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- `state` (`np.ndarray`) – the state where the derivative is computed
- `action` (`np.ndarray`) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

`diff_log(state, action)`

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- `state` (`np.ndarray`) – the state where the gradient is computed
- `action` (`np.ndarray`) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

`classmethod load(path)`

Load and deserialize the agent from the given location on disk.

Parameters `path` (`Path, string`) – Relative or absolute path to the agents save location.

Returns The loaded agent.

`reset()`

Useful when the policy needs a special initialization at the beginning of an episode.

`save(path, full_save=False)`

Serialize and save the object to the given path on disk.

Parameters

- `path` (`Path, str`) – Relative or absolute path to the object save location;
- `full_save` (`bool`) – Flag to specify the amount of data to save for MushroomRL data structures.

`save_zip(zip_file, full_save, folder=’’)`

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ‘’) – subfolder to be used by the save method.

3.9.2 Gaussian policy

class `mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy`
 Bases: `mushroom_rl.policy.policy.ParametricPolicy`

Abstract class of Gaussian policies.

__call__ (*state, action*)

Compute the probability of taking action in a certain state following the policy.

Parameters `*args` (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
 If the action space is continuous, state and action must be provided

draw_action (*state*)

Sample an action in *state* using the policy.

Parameters `state` (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

__init__

Initialize self. See help(type(self)) for accurate signature.

_add_save_attr (`**attr_dict`)

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

diff (*state, action*)

Compute the derivative of the probability density function, in the specified state and action pair. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the derivative is computed
- **action** (*np.ndarray*) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

diff_log(state, action)

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the gradient is computed
- **action** (*np.ndarray*) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

get_weights()

Getter.

Returns The current policy weights.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

set_weights(weights)

Setter.

Parameters **weights** (*np.ndarray*) – the vector of the new weights to be used by the policy.

weights_size

Property.

Returns The size of the policy weights.

class mushroom_rl.policy.gaussian_policy.**GaussianPolicy**(mu, sigma)

Bases: *mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy*

Gaussian policy. This is a differentiable policy for continuous action spaces. The policy samples an action in every state following a gaussian distribution, where the mean is computed in the state and the covariance matrix is fixed.

`__init__(mu, sigma)`

Constructor.

Parameters

- **mu** (`Regressor`) – the regressor representing the mean w.r.t. the state;
- **sigma** (`np.ndarray`) – a square positive definite matrix representing the covariance matrix. The size of this matrix must be n x n, where n is the action dimensionality.

`set_sigma(sigma)`

Setter.

Parameters **sigma** (`np.ndarray`) – the new covariance matrix. Must be a square positive definite matrix.

`diff_log(state, action)`

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (`np.ndarray`) – the state where the gradient is computed
- **action** (`np.ndarray`) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

`set_weights(weights)`

Setter.

Parameters **weights** (`np.ndarray`) – the vector of the new weights to be used by the policy.

`get_weights()`

Getter.

Returns The current policy weights.

`weights_size`

Property.

Returns The size of the policy weights.

`__call__(state, action)`

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (`list`) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

`_add_save_attr(attr_dict)`**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`copy()`

Returns A deepcopy of the agent.

diff(*state, action*)

Compute the derivative of the probability density function, in the specified state and action pair. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the derivative is computed
- **action** (*np.ndarray*) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

draw_action(*state*)

Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

classmethod load(*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file, full_save, folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

class *mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy*(*mu, std*)

Bases: *mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy*

Gaussian policy with learnable standard deviation. The Covariance matrix is constrained to be a diagonal matrix, where the diagonal is the squared standard deviation vector. This is a differentiable policy for continuous action spaces. This policy is similar to the gaussian policy, but the weights includes also the standard deviation.

__init__(*mu, std*)

Constructor.

Parameters

- **mu** ([Regressor](#)) – the regressor representing the mean w.r.t. the state;
- **std** ([np.ndarray](#)) – a vector of standard deviations. The length of this vector must be equal to the action dimensionality.

set_std (*std*)

Setter.

Parameters **std** ([np.ndarray](#)) – the new standard deviation. Must be a square positive definite matrix.

diff_log (*state, action*)

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- **state** ([np.ndarray](#)) – the state where the gradient is computed
- **action** ([np.ndarray](#)) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

set_weights (*weights*)

Setter.

Parameters **weights** ([np.ndarray](#)) – the vector of the new weights to be used by the policy.

get_weights ()

Getter.

Returns The current policy weights.

weights_size

Property.

Returns The size of the policy weights.

__call__ (*state, action*)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

_add_save_attr (**attr_dict)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load ()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

diff(state, action)

Compute the derivative of the probability density function, in the specified state and action pair. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the derivative is computed
- **action** (*np.ndarray*) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

draw_action(state)

Sample an action in `state` using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

class mushroom_rl.policy.gaussian_policy.**StateStdGaussianPolicy**(mu, std, eps=1e-06)

Bases: *mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy*

Gaussian policy with learnable standard deviation. The Covariance matrix is constrained to be a diagonal matrix, where the diagonal is the squared standard deviation, which is computed for each state. This is a differentiable policy for continuous action spaces. This policy is similar to the diagonal gaussian policy, but a parametric regressor is used to compute the standard deviation, so the standard deviation depends on the current state.

__init__(mu, std, eps=1e-06)

Constructor.

Parameters

- **mu** (`Regressor`) – the regressor representing the mean w.r.t. the state;
- **std** (`Regressor`) – the regressor representing the standard deviations w.r.t. the state.
The output dimensionality of the regressor must be equal to the action dimensionality;
- **eps** (`float, 1e-6`) – A positive constant added to the variance to ensure that is always greater than zero.

diff_log(state, action)

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (`np.ndarray`) – the state where the gradient is computed
- **action** (`np.ndarray`) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

set_weights(weights)

Setter.

Parameters **weights** (`np.ndarray`) – the vector of the new weights to be used by the policy.

get_weights()

Getter.

Returns The current policy weights.

weights_size

Property.

Returns The size of the policy weights.

__call__(state, action)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (`list`) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

diff(state, action)

Compute the derivative of the probability density function, in the specified state and action pair. Normally

it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the derivative is computed
- **action** (*np.ndarray*) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

draw_action (*state*)

Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset ()

Useful when the policy needs a special initialization at the beginning of an episode.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

class *mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy* (*mu, log_std*)

Bases: *mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy*

Gaussian policy with learnable standard deviation. The Covariance matrix is constrained to be a diagonal matrix, the diagonal is computed by an exponential transformation of the logarithm of the standard deviation computed in each state. This is a differentiable policy for continuous action spaces. This policy is similar to the State std gaussian policy, but here the regressor represents the logarithm of the standard deviation.

__init__ (*mu, log_std*)

Constructor.

Parameters

- **mu** (`Regressor`) – the regressor representing the mean w.r.t. the state;
- **log_std** (`Regressor`) – a regressor representing the logarithm of the variance w.r.t. the state. The output dimensionality of the regressor must be equal to the action dimensionality.

diff_log (*state, action*)

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (`np.ndarray`) – the state where the gradient is computed
- **action** (`np.ndarray`) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

set_weights (*weights*)

Setter.

Parameters **weights** (`np.ndarray`) – the vector of the new weights to be used by the policy.

get_weights ()

Getter.

Returns The current policy weights.

weights_size

Property.

Returns The size of the policy weights.

__call__ (*state, action*)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (`list`) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

_add_save_attr (**attr_dict)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load ()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy ()

Returns A deepcopy of the agent.

diff (*state, action*)

Compute the derivative of the probability density function, in the specified state and action pair. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the derivative is computed
- **action** (*np.ndarray*) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

draw_action (*state*)

Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset ()

Useful when the policy needs a special initialization at the beginning of an episode.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

3.9.3 Noise policy

```
class mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy (mu, sigma, theta,
dt, x0=None)
```

Bases: *mushroom_rl.policy.policy.ParametricPolicy*

Ornstein-Uhlenbeck process as implemented in: <https://github.com/openai/baselines/blob/master/baselines/ddpg/noise.py>.

This policy is commonly used in the Deep Deterministic Policy Gradient algorithm.

__init__ (*mu, sigma, theta, dt, x0=None*)

Constructor.

Parameters

- **mu** (*Regressor*) – the regressor representing the mean w.r.t. the state;

- **sigma** (*np.ndarray*) – average magnitude of the random fluctuations per square-root time;
- **theta** (*float*) – rate of mean reversion;
- **dt** (*float*) – time interval;
- **x0** (*np.ndarray*, *None*) – initial values of noise.

__call__(*state, action*)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

draw_action(*state*)

Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

set_weights(*weights*)

Setter.

Parameters **weights** (*np.ndarray*) – the vector of the new weights to be used by the policy.

get_weights()

Getter.

Returns The current policy weights.

weights_size

Property.

Returns The size of the policy weights.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

_add_save_attr(***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if *full_save* is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

diff(*state, action*)

Compute the derivative of the probability density function, in the specified state and action pair. Normally it is computed w.r.t. the derivative of the logarithm of the probability density function, exploiting the likelihood ratio trick, i.e.:

$$\nabla_{\theta} p(s, a) = p(s, a) \nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the derivative is computed
- **action** (*np.ndarray*) – the action where the derivative is computed

Returns The derivative w.r.t. the policy weights

diff_log (*state, action*)

Compute the gradient of the logarithm of the probability density function, in the specified state and action pair, i.e.:

$$\nabla_{\theta} \log p(s, a)$$

Parameters

- **state** (*np.ndarray*) – the state where the gradient is computed
- **action** (*np.ndarray*) – the action where the gradient is computed

Returns The gradient of the logarithm of the pdf w.r.t. the policy weights

classmethod load (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

3.9.4 TD policy

class mushroom_rl.policy.td_policy.**TDPolicy**

Bases: *mushroom_rl.policy.policy.Policy*

__init__()

Constructor.

set_q (*approximator*)

Parameters **approximator** (*object*) – the approximator to use.

get_q()

Returns The approximator used by the policy.

`__call__(*args)`

Compute the probability of taking action in a certain state following the policy.

Parameters `*args (list)` – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

`_add_save_attr(attr_dict)`**

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`copy()`

Returns A deepcopy of the agent.

`draw_action(state)`

Sample an action in `state` using the policy.

Parameters `state (np.ndarray)` – the state where the agent is.

Returns The action sampled from the policy.

`classmethod load(path)`

Load and deserialize the agent from the given location on disk.

Parameters `path (Path, string)` – Relative or absolute path to the agents save location.

Returns The loaded agent.

`reset()`

Useful when the policy needs a special initialization at the beginning of an episode.

`save(path, full_save=False)`

Serialize and save the object to the given path on disk.

Parameters

- `path (Path, str)` – Relative or absolute path to the object save location;
- `full_save (bool)` – Flag to specify the amount of data to save for MushroomRL data structures.

`save_zip(zip_file, full_save, folder=’’)`

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file (ZipFile)` – ZipFile where te object needs to be saved;
- `full_save (bool)` – flag to specify the amount of data to save for MushroomRL data structures;
- `folder (string, ‘’)` – subfolder to be used by the save method.

`class mushroom_rl.policy.td_policy.EpsGreedy(epsilon)`

Bases: `mushroom_rl.policy.td_policy.TDPolicy`

Epsilon greedy policy.

`__init__(epsilon)`

Constructor.

Parameters `epsilon` (`Parameter`) – the exploration coefficient. It indicates the probability of performing a random actions in the current step.

`_call_(*args)`

Compute the probability of taking action in a certain state following the policy.

Parameters `*args` (`list`) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy. If the action space is continuous, state and action must be provided

`draw_action(state)`

Sample an action in `state` using the policy.

Parameters `state` (`np.ndarray`) – the state where the agent is.

Returns The action sampled from the policy.

`set_epsilon(epsilon)`

Setter.

Parameters

- `epsilon` (`Parameter`) – the exploration coefficient. It indicates the
- `of performing a random actions in the current step.` (`probability`) –

`update(*idx)`

Update the value of the epsilon parameter at the provided index (e.g. in case of different values of epsilon for each visited state according to the number of visits).

Parameters `*idx` (`list`) – index of the parameter to be updated.

`_add_save_attr(**attr_dict)`

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`copy()`

Returns A deepcopy of the agent.

`get_q()`

Returns The approximator used by the policy.

`classmethod load(path)`

Load and deserialize the agent from the given location on disk.

Parameters `path` (`Path, string`) – Relative or absolute path to the agents save location.

Returns The loaded agent.

`reset()`

Useful when the policy needs a special initialization at the beginning of an episode.

save(*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file*, *full_save*, *folder=””*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

set_q(*approximator*)

Parameters **approximator** (*object*) – the approximator to use.

class mushroom_rl.policy.td_policy.**Boltzmann**(*beta*)

Bases: *mushroom_rl.policy.td_policy.TDPolicy*

Boltzmann softmax policy.

__init__(*beta*)

Constructor.

Parameters

- **beta** (*Parameter*) – the inverse of the temperature distribution. As
- **temperature approaches infinity, the policy becomes more and (the) –**
- **random. As the temperature approaches 0.0, the policy becomes (more) –**
- **and more greedy. (more) –**

__call__(*args)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy. If the action space is continuous, state and action must be provided

draw_action(*state*)

Sample an action in *state* using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

set_beta(*beta*)

Setter.

Parameters **beta** (*Parameter*) – the inverse of the temperature distribution.

update(*idx)

Update the value of the beta parameter at the provided index (e.g. in case of different values of beta for each visited state according to the number of visits).

Parameters ***idx**(list) – index of the parameter to be updated.

_add_save_attr(**attr_dict)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

get_q()

Returns The approximator used by the policy.

classmethod **load**(path)

Load and deserialize the agent from the given location on disk.

Parameters **path**(Path, string) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path**(Path, str) – Relative or absolute path to the object save location;
- **full_save**(bool) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder="")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file**(ZipFile) – ZipFile where te object needs to be saved;
- **full_save**(bool) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder**(string, '') – subfolder to be used by the save method.

set_q(approximator)

Parameters **approximator**(object) – the approximator to use.

class mushroom_rl.policy.td_policy.**Mellowmax**(omega, beta_min=-10.0, beta_max=10.0)

Bases: *mushroom_rl.policy.td_policy.Boltzmann*

Mellowmax policy. “An Alternative Softmax Operator for Reinforcement Learning”. Asadi K. and Littman M.L.. 2017.

__init__(omega, beta_min=-10.0, beta_max=10.0)
Constructor.

Parameters

- **omega** ([Parameter](#)) – the omega parameter of the policy from which beta of the Boltzmann policy is computed;
- **beta_min** (*float*, `-10.`) – one end of the bracketing interval for minimization with Brent’s method;
- **beta_max** (*float*, `10.`) – the other end of the bracketing interval for minimization with Brent’s method.

set_beta(beta)

Setter.

Parameters **beta** ([Parameter](#)) – the inverse of the temperature distribution.

update(*idx)

Update the value of the beta parameter at the provided index (e.g. in case of different values of beta for each visited state according to the number of visits).

Parameters ***idx** (*list*) – index of the parameter to be updated.

__call__(*args)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy.
If the action space is continuous, state and action must be provided

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

draw_action(state)

Sample an action in `state` using the policy.

Parameters **state** (`np.ndarray`) – the state where the agent is.

Returns The action sampled from the policy.

get_q()

Returns The approximator used by the policy.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ’ ’*) – subfolder to be used by the save method.

set_q(approximator)

Parameters **approximator** (*object*) – the approximator to use.

3.9.5 Torch policy

class mushroom_rl.policy.torch_policy.**TorchPolicy** (*use_cuda*)

Bases: *mushroom_rl.policy.policy.Policy*

Interface for a generic PyTorch policy. A PyTorch policy is a policy implemented as a neural network using PyTorch. Functions ending with ‘_t’ use tensors as input, and also as output when required.

__init__(use_cuda)

Constructor.

Parameters **use_cuda** (*bool*) – whether to use cuda or not.

__call__(state, action)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy. If the action space is continuous, state and action must be provided

draw_action(state)

Sample an action in state using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

distribution(state)

Compute the policy distribution in the given states.

Parameters **state** (*np.ndarray*) – the set of states where the distribution is computed.

Returns The torch distribution for the provided states.

entropy (*state=None*)

Compute the entropy of the policy.

Parameters **state** (*np.ndarray, None*) – the set of states to consider. If the entropy of the policy can be computed in closed form, then *state* can be *None*.

Returns The value of the entropy of the policy.

draw_action_t (*state*)

Draw an action given a tensor.

Parameters **state** (*torch.Tensor*) – set of states.

Returns The tensor of the actions to perform in each state.

log_prob_t (*state, action*)

Compute the logarithm of the probability of taking *action* in *state*.

Parameters

- **state** (*torch.Tensor*) – set of states.
- **action** (*torch.Tensor*) – set of actions.

Returns The tensor of log-probability.

entropy_t (*state*)

Compute the entropy of the policy.

Parameters **state** (*torch.Tensor*) – the set of states to consider. If the entropy of the policy can be computed in closed form, then *state* can be *None*.

Returns The tensor value of the entropy of the policy.

distribution_t (*state*)

Compute the policy distribution in the given states.

Parameters **state** (*torch.Tensor*) – the set of states where the distribution is computed.

Returns The torch distribution for the provided states.

set_weights (*weights*)

Setter.

Parameters **weights** (*np.ndarray*) – the vector of the new weights to be used by the policy.

get_weights ()

Getter.

Returns The current policy weights.

parameters ()

Returns the trainable policy parameters, as expected by torch optimizers.

Returns List of parameters to be optimized.

reset ()

Useful when the policy needs a special initialization at the beginning of an episode.

use_cuda

True if the policy is using cuda_tensors.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`copy()`

Returns A deepcopy of the agent.

`classmethod load(path)`

Load and deserialize the agent from the given location on disk.

Parameters `path (Path, string)` – Relative or absolute path to the agents save location.

Returns The loaded agent.

`save(path, full_save=False)`

Serialize and save the object to the given path on disk.

Parameters

- `path (Path, str)` – Relative or absolute path to the object save location;
- `full_save (bool)` – Flag to specify the amount of data to save for MushroomRL data structures.

`save_zip(zip_file, full_save, folder=’’)`

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file (ZipFile)` – ZipFile where te object needs to be saved;
- `full_save (bool)` – flag to specify the amount of data to save for MushroomRL data structures;
- `folder (string, ‘’)` – subfolder to be used by the save method.

```
class mushroom_rl.policy.torch_policy.GaussianTorchPolicy(network,           in-
                                                               put_shape,          out-
                                                               put_shape, std_0=1.0,
                                                               use_cuda=False,
                                                               **params)
```

Bases: `mushroom_rl.policy.torch_policy.TorchPolicy`

Torch policy implementing a Gaussian policy with trainable standard deviation. The standard deviation is not state-dependent.

```
__init__(network, input_shape, output_shape, std_0=1.0, use_cuda=False, **params)
    Constructor.
```

Parameters

- `network (object)` – the network class used to implement the mean regressor;
- `input_shape (tuple)` – the shape of the state space;
- `output_shape (tuple)` – the shape of the action space;
- `std_0 (float, 1.)` – initial standard deviation;
- `params (dict)` – parameters used by the network constructor.

`draw_action_t(state)`

Draw an action given a tensor.

Parameters `state` (`torch.Tensor`) – set of states.

Returns The tensor of the actions to perform in each state.

`log_prob_t(state, action)`

Compute the logarithm of the probability of taking `action` in `state`.

Parameters

- `state` (`torch.Tensor`) – set of states.
- `action` (`torch.Tensor`) – set of actions.

Returns The tensor of log-probability.

`entropy_t(state=None)`

Compute the entropy of the policy.

Parameters `state` (`torch.Tensor`) – the set of states to consider. If the entropy of the policy can be computed in closed form, then `state` can be None.

Returns The tensor value of the entropy of the policy.

`distribution_t(state)`

Compute the policy distribution in the given states.

Parameters `state` (`torch.Tensor`) – the set of states where the distribution is computed.

Returns The torch distribution for the provided states.

`set_weights(weights)`

Setter.

Parameters `weights` (`np.ndarray`) – the vector of the new weights to be used by the policy.

`get_weights()`

Getter.

Returns The current policy weights.

`parameters()`

Returns the trainable policy parameters, as expected by torch optimizers.

Returns List of parameters to be optimized.

`__call__(state, action)`

Compute the probability of taking `action` in a certain `state` following the policy.

Parameters `*args` (`list`) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy. If the action space is continuous, state and action must be provided

`_add_save_attr(**attr_dict)`

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`copy()`

Returns A deepcopy of the agent.

distribution(state)

Compute the policy distribution in the given states.

Parameters **state** (*np.ndarray*) – the set of states where the distribution is computed.

Returns The torch distribution for the provided states.

draw_action(state)

Sample an action in state using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

entropy(state=None)

Compute the entropy of the policy.

Parameters **state** (*np.ndarray, None*) – the set of states to consider. If the entropy of the policy can be computed in closed form, then state can be None.

Returns The value of the entropy of the policy.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=’’)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

use_cuda

True if the policy is using cuda_tensors.

```
class mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy(network, input_shape,
                                                          output_shape, beta,
                                                          use_cuda=False,
                                                          **params)
```

Bases: *mushroom_rl.policy.torch_policy.TorchPolicy*

Torch policy implementing a Boltzmann policy.

__init__(network, input_shape, output_shape, beta, use_cuda=False, **params)

Constructor.

Parameters

- **network** (*object*) – the network class used to implement the mean regressor;
- **input_shape** (*tuple*) – the shape of the state space;
- **output_shape** (*tuple*) – the shape of the action space;
- **beta** ([Parameter](#)) – the inverse of the temperature distribution. As the temperature approaches infinity, the policy becomes more and more random. As the temperature approaches 0.0, the policy becomes more and more greedy.
- **params** (*dict*) – parameters used by the network constructor.

draw_action_t (*state*)

Draw an action given a tensor.

Parameters **state** (*torch.Tensor*) – set of states.**Returns** The tensor of the actions to perform in each state.**log_prob_t** (*state, action*)Compute the logarithm of the probability of taking *action* in *state*.**Parameters**

- **state** (*torch.Tensor*) – set of states.
- **action** (*torch.Tensor*) – set of actions.

Returns The tensor of log-probability.**entropy_t** (*state*)

Compute the entropy of the policy.

Parameters **state** (*torch.Tensor*) – the set of states to consider. If the entropy of the policy can be computed in closed form, then *state* can be None.**Returns** The tensor value of the entropy of the policy.**distribution_t** (*state*)

Compute the policy distribution in the given states.

Parameters **state** (*torch.Tensor*) – the set of states where the distribution is computed.**Returns** The torch distribution for the provided states.**set_weights** (*weights*)

Setter.

Parameters **weights** (*np.ndarray*) – the vector of the new weights to be used by the policy.**get_weights** ()

Getter.

Returns The current policy weights.**parameters** ()

Returns the trainable policy parameters, as expected by torch optimizers.

Returns List of parameters to be optimized.**__call__** (*state, action*)

Compute the probability of taking action in a certain state following the policy.

Parameters ***args** (*list*) – list containing a state or a state and an action.

Returns The probability of all actions following the policy in the given state if the list contains only the state, else the probability of the given action in the given state following the policy. If the action space is continuous, state and action must be provided

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

distribution(state)

Compute the policy distribution in the given states.

Parameters **state** (*np.ndarray*) – the set of states where the distribution is computed.

Returns The torch distribution for the provided states.

draw_action(state)

Sample an action in state using the policy.

Parameters **state** (*np.ndarray*) – the state where the agent is.

Returns The action sampled from the policy.

entropy(state=None)

Compute the entropy of the policy.

Parameters **state** (*np.ndarray, None*) – the set of states to consider. If the entropy of the policy can be computed in closed form, then state can be None.

Returns The value of the entropy of the policy.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

reset()

Useful when the policy needs a special initialization at the beginning of an episode.

save(path, full_save=False)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(zip_file, full_save, folder=”)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;

- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string*, ' ') – subfolder to be used by the save method.

use_cuda

True if the policy is using cuda_tensors.

3.10 Solvers

3.10.1 Dynamic programming

```
mushroom_rl.solvers.dynamic_programming.value_iteration(prob, reward, gamma,
                                                       eps)
```

Value iteration algorithm to solve a dynamic programming problem.

Parameters

- **prob** (*np.ndarray*) – transition probability matrix;
- **reward** (*np.ndarray*) – reward matrix;
- **gamma** (*float*) – discount factor;
- **eps** (*float*) – accuracy threshold.

Returns The optimal value of each state.

```
mushroom_rl.solvers.dynamic_programming.policy_iteration(prob, reward, gamma)
```

Policy iteration algorithm to solve a dynamic programming problem.

Parameters

- **prob** (*np.ndarray*) – transition probability matrix;
- **reward** (*np.ndarray*) – reward matrix;
- **gamma** (*float*) – discount factor.

Returns The optimal value of each state and the optimal policy.

3.10.2 Car-On-Hill brute-force solver

```
mushroom_rl.solvers.car_on_hill.step(mdp, state, action)
```

Perform a step in the tree.

Parameters

- **mdp** ([CarOnHill](#)) – the Car-On-Hill environment;
- **state** (*np.array*) – the state;
- **action** (*np.array*) – the action.

Returns The resulting transition executing *action* in *state*.

```
mushroom_rl.solvers.car_on_hill.bfs(mdp, frontier, k, max_k)
```

Perform Breadth-First tree search.

Parameters

- **mdp** ([CarOnHill](#)) – the Car-On-Hill environment;

- **frontier** (*list*) – the state at the frontier of the BFS;
- **k** (*int*) – the current depth of the tree;
- **max_k** (*int*) – maximum depth to consider.

Returns A tuple containing a flag for the algorithm ending, and the updated depth of the tree.

```
mushroom_rl.solvers.car_on_hill.solve_car_on_hill(mdp, states, actions, gamma,
                                                 max_k=50)
```

Solver of the Car-On-Hill environment.

Parameters

- **mdp** ([CarOnHill](#)) – the Car-On-Hill environment;
- **states** (*np.ndarray*) – the states;
- **actions** (*np.ndarray*) – the actions;
- **gamma** (*float*) – the discount factor;
- **max_k** (*int*, 50) – maximum depth to consider.

Returns The Q-value for each state-action tuple.

3.10.3 LQR solver

```
mushroom_rl.solvers.lqr.compute_lqr_feedback_gain(lqr, max_iterations=100)
```

Computes the optimal gain matrix K.

Parameters

- **lqr** ([LQR](#)) – LQR environment;
- **max_iterations** (*int*) – max iterations for convergence.

Returns Feedback gain matrix K.

```
mushroom_rl.solvers.lqr.compute_lqr_P(lqr, K)
```

Computes the P matrix for a given gain matrix K.

Parameters

- **lqr** ([LQR](#)) – LQR environment;
- **K** (*np.ndarray*) – controller matrix.

Returns The P matrix of the value function.

```
mushroom_rl.solvers.lqr.compute_lqr_V(s, lqr, K)
```

Computes the value function at a state s, with the given gain matrix K.

Parameters

- **s** (*np.ndarray*) – state;
- **lqr** ([LQR](#)) – LQR environment;
- **K** (*np.ndarray*) – controller matrix.

Returns The value function at s

```
mushroom_rl.solvers.lqr.compute_lqr_V_gaussian_policy(s, lqr, K, Sigma)
```

Computes the value function at a state s, with the given gain matrix K and covariance Sigma.

Parameters

- **s** (*np.ndarray*) – state;
- **lqr** ([LQR](#)) – LQR environment;
- **K** (*np.ndarray*) – controller matrix;
- **Sigma** (*np.ndarray*) – covariance matrix.

Returns The value function at s.

`mushroom_rl.solvers.lqr.compute_lqr_Q(s, a, lqr, K)`

Computes the state-action value function Q at a state-action pair (s, a), with the given gain matrix K.

Parameters

- **s** (*np.ndarray*) – state;
- **a** (*np.ndarray*) – action;
- **lqr** ([LQR](#)) – LQR environment;
- **K** (*np.ndarray*) – controller matrix.

Returns The Q function at s, a.

`mushroom_rl.solvers.lqr.compute_lqr_Q_gaussian_policy(s, a, lqr, K, Sigma)`

Computes the state-action value function Q at a state-action pair (s, a), with the given gain matrix K and covariance Sigma.

Parameters

- **s** (*np.ndarray*) – state;
- **a** (*np.ndarray*) – action;
- **lqr** ([LQR](#)) – LQR environment;
- **K** (*np.ndarray*) – controller matrix;
- **Sigma** (*np.ndarray*) – covariance matrix.

Returns The Q function at (s, a).

`mushroom_rl.solvers.lqr.compute_lqr_V_gaussian_policy_gradient_K(s, lqr, K, Sigma)`

Computes the gradient of the objective function J (equal to the value function V) at state s, w.r.t. the controller matrix K, with the current policy parameters K and Sigma. $J(s, K, \Sigma) = \text{ValueFunction}(s, K, \Sigma)$.

Parameters

- **s** (*np.ndarray*) – state;
- **lqr** ([LQR](#)) – LQR environment;
- **K** (*np.ndarray*) – controller matrix;
- **Sigma** (*np.ndarray*) – covariance matrix.

Returns The gradient of J wrt to K.

`mushroom_rl.solvers.lqr.compute_lqr_Q_gaussian_policy_gradient_K(s, a, lqr, K, Sigma)`

Computes the gradient of the state-action Value function at state-action pair (s, a), w.r.t. the controller matrix K, with the current policy parameters K and Sigma.

Parameters

- **s** (*np.ndarray*) – state;

- **a** (*np.ndarray*) – action;
- **lqr** ([LQR](#)) – LQR environment;
- **K** (*np.ndarray*) – controller matrix;
- **Sigma** (*np.ndarray*) – covariance matrix.

Returns The gradient of Q wrt to K.

3.11 Utils

3.11.1 Angles

`mushroom_rl.utils.angles.normalize_angle_positive(angle)`

Wrap the angle between 0 and $2 * \pi$.

Parameters `angle` (*float*) – angle to wrap.

Returns The wrapped angle.

`mushroom_rl.utils.angles.normalize_angle(angle)`

Wrap the angle between $-\pi$ and π .

Parameters `angle` (*float*) – angle to wrap.

Returns The wrapped angle.

`mushroom_rl.utils.angles.shortest_angular_distance(from_angle, to_angle)`

Compute the shortest distance between two angles

Parameters

- `from_angle` (*float*) – starting angle;
- `to_angle` (*float*) – final angle.

Returns The shortest distance between from_angle and to_angle.

`mushroom_rl.utils.angles.quat_to_euler(quat)`

Convert a quaternion to euler angles.

Parameters `quat` (*np.ndarray*) – quaternion to be converted, must be in format [w, x, y, z]

Returns The euler angles [x, y, z] representation of the quaternion

`mushroom_rl.utils.angles.euler_to_quat(euler)`

Convert euler angles into a quaternion.

Parameters `euler` (*np.ndarray*) – euler angles to be converted

Returns Quaternion in format [w, x, y, z]

3.11.2 Callbacks

`class mushroom_rl.utils.callbacks.Callback`

Bases: `object`

Interface for all basic callbacks. Implements a list in which it is possible to store data and methods to query and clean the content stored by the callback.

`__init__()`
Constructor.

`__call__(dataset)`
Add samples to the samples list.

Parameters `dataset` (`list`) – the samples to collect.

`get()`

Returns The current collected data as a list.

`clean()`
Delete the current stored data list

`class mushroom_rl.utils.callbacks.CollectDataset`
Bases: `mushroom_rl.utils.callbacks.callback.Callback`

This callback can be used to collect samples during the learning of the agent.

`__call__(dataset)`
Add samples to the samples list.

Parameters `dataset` (`list`) – the samples to collect.

`class mushroom_rl.utils.callbacks.CollectQ(approximator)`
Bases: `mushroom_rl.utils.callbacks.callback.Callback`

This callback can be used to collect the action values in all states at the current time step.

`__init__(approximator)`
Constructor.

Parameters `approximator` (`[Table, EnsembleTable]`) – the approximator to use to predict the action values.

`__call__(dataset)`
Add samples to the samples list.

Parameters `dataset` (`list`) – the samples to collect.

`class mushroom_rl.utils.callbacks.CollectMaxQ(approximator, state)`
Bases: `mushroom_rl.utils.callbacks.callback.Callback`

This callback can be used to collect the maximum action value in a given state at each call.

`__init__(approximator, state)`
Constructor.

Parameters

- **`approximator`** (`[Table, EnsembleTable]`) – the approximator to use;
- **`state`** (`np.ndarray`) – the state to consider.

`__call__(dataset)`
Add samples to the samples list.

Parameters `dataset` (`list`) – the samples to collect.

`class mushroom_rl.utils.callbacks.CollectParameters(parameter, *idx)`
Bases: `mushroom_rl.utils.callbacks.callback.Callback`

This callback can be used to collect the values of a parameter (e.g. learning rate) during a run of the agent.

`__init__(parameter, *idx)`
Constructor.

Parameters

- **parameter** (`Parameter`) – the parameter whose values have to be collected;
- ***idx** (`list`) – index of the parameter when the `parameter` is tabular.

`__call__(dataset)`

Add samples to the samples list.

Parameters `dataset` (`list`) – the samples to collect.

3.11.3 Dataset

`mushroom_rl.utils.dataset.parse_dataset(dataset, features=None)`

Split the dataset in its different components and return them.

Parameters

- **dataset** (`list`) – the dataset to parse;
- **features** (`object, None`) – features to apply to the states.

Returns The `np.ndarray` of state, action, reward, next_state, absorbing flag and last step flag. Features are applied to state and next_state, when provided.

`mushroom_rl.utils.dataset.arrays_as_dataset(states, actions, rewards, next_states, absorbings, lasts)`

Creates a dataset of transitions from the provided arrays.

Parameters

- **states** (`np.ndarray`) – array of states;
- **actions** (`np.ndarray`) – array of actions;
- **rewards** (`np.ndarray`) – array of rewards;
- **next_states** (`np.ndarray`) – array of next_states;
- **absorbings** (`np.ndarray`) – array of absorbing flags;
- **lasts** (`np.ndarray`) – array of last flags.

Returns The list of transitions.

`mushroom_rl.utils.dataset.episodes_length(dataset)`

Compute the length of each episode in the dataset.

Parameters `dataset` (`list`) – the dataset to consider.

Returns A list of length of each episode in the dataset.

`mushroom_rl.utils.dataset.select_first_episodes(dataset, n_episodes, parse=False)`

Return the first `n_episodes` episodes in the provided dataset.

Parameters

- **dataset** (`list`) – the dataset to consider;
- **n_episodes** (`int`) – the number of episodes to pick from the dataset;
- **parse** (`bool, False`) – whether to parse the dataset to return.

Returns A subset of the dataset containing the first `n_episodes` episodes.

`mushroom_rl.utils.dataset.select_random_samples(dataset, n_samples, parse=False)`

Return the randomly picked desired number of samples in the provided dataset.

Parameters

- **dataset** (*list*) – the dataset to consider;
- **n_samples** (*int*) – the number of samples to pick from the dataset;
- **parse** (*bool, False*) – whether to parse the dataset to return.

Returns A subset of the dataset containing randomly picked *n_samples* samples.

`mushroom_rl.utils.dataset.compute_J(dataset, gamma=1.0)`

Compute the cumulative discounted reward of each episode in the dataset.

Parameters

- **dataset** (*list*) – the dataset to consider;
- **gamma** (*float, 1.*) – discount factor.

Returns The cumulative discounted reward of each episode in the dataset.

`mushroom_rl.utils.dataset.compute_metrics(dataset, gamma=1.0)`

Compute the metrics of each complete episode in the dataset.

Parameters

- **dataset** (*list*) – the dataset to consider;
- **gamma** (*float, 1.*) – the discount factor.

Returns

The minimum score reached in an episode, the maximum score reached in an episode, the mean score reached, the number of completed games.

If episode has not been completed, it returns 0 for all values.

3.11.4 Eligibility trace

`mushroom_rl.utils.eligibility_trace.EligibilityTrace(shape, name='replacing')`

Factory method to create an eligibility trace of the provided type.

Parameters

- **shape** (*list*) – shape of the eligibility trace table;
- **name** (*str, 'replacing'*) – type of the eligibility trace.

Returns The eligibility trace table of the provided shape and type.

`class mushroom_rl.utils.eligibility_trace.ReplacingTrace(shape, initial_value=0.0, dtype=None)`

Bases: `mushroom_rl.utils.table.Table`

Replacing trace.

`reset()`

`update(state, action)`

`__init__(shape, initial_value=0.0, dtype=None)`
Constructor.

Parameters

- **shape** (*tuple*) – the shape of the tabular regressor.

- **initial_value** (*float*, *0.*) – the initial value for each entry of the tabular regressor.
- **dtype** (*[int, float]*, *None*) – the dtype of the table array.

_add_save_attr (**attr_dict)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

static _append_folder (folder, name)**static _get_serialization_method** (class_name)**static _load_json** (zip_file, name)**classmethod _load_list** (zip_file, folder, length)**static _load_mushroom** (zip_file, name)**static _load_numpy** (zip_file, name)**static _load_pickle** (zip_file, name)**static _load_torch** (zip_file, name)**_post_load()**

This method can be overwritten to implement logic that is executed after the loading of the agent.

static _save_json (zip_file, name, obj, folder, **_)**static _save_mushroom** (zip_file, name, obj, folder, full_save)**static _save_numpy** (zip_file, name, obj, folder, **_)**static _save_pickle** (zip_file, name, obj, folder, **_)**static _save_torch** (zip_file, name, obj, folder, **_)**copy()**

Returns A deepcopy of the agent.

fit (x, y)**Parameters**

- **x** (*int*) – index of the table to be filled;
- **y** (*float*) – value to fill in the table.

classmethod load (path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

classmethod load_zip (zip_file, folder=’)**n_actions**

The number of actions considered by the table.

Type Returns

predict (*z)

Predict the output of the table given an input.

Parameters

- ***z** (*list*) – list of input of the model. If the table is a Q-table,
- **list may contain states or states and actions depending (this)** – on whether the call requires to predict all q-values or only one q-value corresponding to the provided action;

Returns The table prediction.**save** (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

shape

The shape of the table.

Type Returns

```
class mushroom_rl.utils.eligibility_trace.AccumulatingTrace(shape, initial_value=0.0, dtype=None)
```

Bases: *mushroom_rl.utils.table.Table*

Accumulating trace.

reset()**update** (*state, action*)**__init__** (*shape, initial_value=0.0, dtype=None*)

Constructor.

Parameters

- **shape** (*tuple*) – the shape of the tabular regressor.
- **initial_value** (*float, 0.*) – the initial value for each entry of the tabular regressor.
- **dtype** (*[int, float], None*) – the dtype of the table array.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

```
static _append_folder(folder, name)
static _get_serialization_method(class_name)
static _load_json(zip_file, name)
classmethod _load_list(zip_file, folder, length)
static _load_mushroom(zip_file, name)
static _load_numpy(zip_file, name)
static _load_pickle(zip_file, name)
static _load_torch(zip_file, name)
```

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

```
static _save_json(zip_file, name, obj, folder, **_)
static _save_mushroom(zip_file, name, obj, folder, full_save)
static _save_numpy(zip_file, name, obj, folder, **_)
static _save_pickle(zip_file, name, obj, folder, **_)
static _save_torch(zip_file, name, obj, folder, **_)
```

copy()

Returns A deepcopy of the agent.

fit(x, y)

Parameters

- **x** (*int*) – index of the table to be filled;
- **y** (*float*) – value to fill in the table.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

classmethod load_zip(zip_file, folder=”)

n_actions

The number of actions considered by the table.

Type Returns

predict(*z)

Predict the output of the table given an input.

Parameters

- ***z** (*list*) – list of input of the model. If the table is a Q-table,
- **list may contain states or states and actions depending (this)** – on whether the call requires to predict all q-values or only one q-value corresponding to the provided action;

Returns The table prediction.

save(*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file*, *full_save*, *folder=””*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where the object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ‘’*) – subfolder to be used by the save method.

shape

The shape of the table.

Type Returns

3.11.5 Features

mushroom_rl.utils.features.uniform_grid(*n_centers*, *low*, *high*)

This function is used to create the parameters of uniformly spaced radial basis functions with 25% of overlap. It creates a uniformly spaced grid of *n_centers[i]* points in each *ranges[i]*. Also returns a vector containing the appropriate scales of the radial basis functions.

Parameters

- **n_centers** (*list*) – number of centers of each dimension;
- **low** (*np.ndarray*) – lowest value for each dimension;
- **high** (*np.ndarray*) – highest value for each dimension.

Returns The uniformly spaced grid and the scale vector.

3.11.6 Folder

mushroom_rl.utils.folder.mk_dir_recursive(*dir_path*)

Create a directory and, if needed, all the directory tree. Differently from os.mkdir, this function does not raise exception when the directory already exists.

Parameters **dir_path** (*str*) – the path of the directory to create.

mushroom_rl.utils.folder.force_symlink(*src*, *dst*)

Create a symlink deleting the previous one, if it already exists.

Parameters

- **src** (*str*) – source;
- **dst** (*str*) – destination.

3.11.7 Frames

```
class mushroom_rl.utils.frames.LazyFrames(frames, history_length)
    Bases: object
```

From OpenAI Baseline. https://github.com/openai/baselines/blob/master/baselines/common/atari_wrappers.py

This class provides a solution to optimize the use of memory when concatenating different frames, e.g. Atari frames in DQN. The frames are individually stored in a list and, when numpy arrays containing them are created, the reference to each frame is used instead of a copy.

```
__init__(frames, history_length)
```

Initialize self. See help(type(self)) for accurate signature.

```
mushroom_rl.utils.frames.preprocess_frame(obs, img_size)
```

Convert a frame from rgb to grayscale and resize it.

Parameters

- **obs** (`np.ndarray`) – array representing an rgb frame;
- **img_size** (`tuple`) – target size for images.

Returns The transformed frame as 8 bit integer array.

3.11.8 Minibatches

```
mushroom_rl.utils.minibatches.minibatch_number(size, batch_size)
```

Function to retrieve the number of batches, given a batch sizes.

Parameters

- **size** (`int`) – size of the dataset;
- **batch_size** (`int`) – size of the batches.

Returns The number of minibatches in the dataset.

```
mushroom_rl.utils.minibatches.minibatch_generator(batch_size, *dataset)
```

Generator that creates a minibatch from the full dataset.

Parameters

- **batch_size** (`int`) – the maximum size of each minibatch;
- **dataset** – the dataset to be splitted.

Returns The current minibatch.

3.11.9 Numerical gradient

```
mushroom_rl.utils.numerical_gradient.numerical_diff_policy(policy, state, action,
                                                               eps=1e-06)
```

Compute the gradient of a policy in (state, action) numerically.

Parameters

- **policy** (`Policy`) – the policy whose gradient has to be returned;
- **state** (`np.ndarray`) – the state;
- **action** (`np.ndarray`) – the action;

- **eps** (*float*, $1e-6$) – the value of the perturbation.

Returns The gradient of the provided policy in (state, action) computed numerically.

`mushroom_rl.utils.numerical_gradient.numerical_diff_dist(dist, theta, eps=1e-06)`

Compute the gradient of a distribution in theta numerically.

Parameters

- **dist** (*Distribution*) – the distribution whose gradient has to be returned;
- **theta** (*np.ndarray*) – the parametrization where to compute the gradient;
- **eps** (*float*, $1e-6$) – the value of the perturbation.

Returns The gradient of the provided distribution theta computed numerically.

`mushroom_rl.utils.numerical_gradient.numerical_diff_function(function, params, eps=1e-06)`

Compute the gradient of a function in theta numerically.

Parameters

- **function** – a function whose gradient has to be returned;
- **params** – parameter vector w.r.t. we need to compute the gradient;
- **eps** (*float*, $1e-6$) – the value of the perturbation.

Returns The numerical gradient of the function computed w.r.t. parameters params.

3.11.10 Parameters

`class mushroom_rl.utils.parameters.Parameter(value, min_value=None, max_value=None, size=(1,))`

Bases: object

This class implements function to manage parameters, such as learning rate. It also allows to have a single parameter for each state of state-action tuple.

`__init__(value, min_value=None, max_value=None, size=(1,))`

Constructor.

Parameters

- **value** (*float*) – initial value of the parameter;
- **min_value** (*float*, *None*) – minimum value that the parameter can reach when decreasing;
- **max_value** (*float*, *None*) – maximum value that the parameter can reach when increasing;
- **size** (*tuple*, $(1,)$) – shape of the matrix of parameters; this shape can be used to have a single parameter for each state or state-action tuple.

`__call__(*idx, **kwargs)`

Update and return the parameter in the provided index.

Parameters ***idx** (*list*) – index of the parameter to return.

Returns The updated parameter in the provided index.

`get_value(*idx, **kwargs)`

Return the current value of the parameter in the provided index.

Parameters `*idx`(*list*) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

`_compute(*idx, **kwargs)`

Returns The value of the parameter in the provided index.

`update(*idx, **kwargs)`

Updates the number of visit of the parameter in the provided index.

Parameters `*idx`(*list*) – index of the parameter whose number of visits has to be updated.

shape

The shape of the table of parameters.

Type Returns

`class mushroom_rl.utils.parameters.LinearParameter(value, threshold_value, n, size=(1,))`

Bases: *mushroom_rl.utils.parameters.Parameter*

This class implements a linearly changing parameter according to the number of times it has been used.

`__init__(value, threshold_value, n, size=(1,))`

Constructor.

Parameters

- `value` (*float*) – initial value of the parameter;
- `min_value` (*float, None*) – minimum value that the parameter can reach when decreasing;
- `max_value` (*float, None*) – maximum value that the parameter can reach when increasing;
- `size` (*tuple, (1,)*) – shape of the matrix of parameters; this shape can be used to have a single parameter for each state or state-action tuple.

`_compute(*idx, **kwargs)`

Returns: The value of the parameter in the provided index.

`__call__(*idx, **kwargs)`

Update and return the parameter in the provided index.

Parameters `*idx`(*list*) – index of the parameter to return.

Returns The updated parameter in the provided index.

`get_value(*idx, **kwargs)`

Return the current value of the parameter in the provided index.

Parameters `*idx`(*list*) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

shape

The shape of the table of parameters.

Type Returns

`update(*idx, **kwargs)`

Updates the number of visit of the parameter in the provided index.

Parameters `*idx`(*list*) – index of the parameter whose number of visits has to be updated.

```
class mushroom_rl.utils.parameters.ExponentialParameter(value, exp=1.0,  

min_value=None,  

max_value=None, size=(1,  

))
```

Bases: *mushroom_rl.utils.parameters.Parameter*

This class implements a exponentially changing parameter according to the number of times it has been used.

__init__(*value*, *exp*=1.0, *min_value*=None, *max_value*=None, *size*=(1,))
Constructor.

Parameters

- **value** (*float*) – initial value of the parameter;
- **min_value** (*float*, *None*) – minimum value that the parameter can reach when decreasing;
- **max_value** (*float*, *None*) – maximum value that the parameter can reach when increasing;
- **size** (*tuple*, (1,)) – shape of the matrix of parameters; this shape can be used to have a single parameter for each state or state-action tuple.

_compute(**idx*, ***kwargs*)

Returns: The value of the parameter in the provided index.

__call__(**idx*, ***kwargs*)

Update and return the parameter in the provided index.

Parameters ***idx**(*list*) – index of the parameter to return.

Returns The updated parameter in the provided index.

get_value(**idx*, ***kwargs*)

Return the current value of the parameter in the provided index.

Parameters ***idx**(*list*) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

shape

The shape of the table of parameters.

Type Returns

update(**idx*, ***kwargs*)

Updates the number of visit of the parameter in the provided index.

Parameters ***idx**(*list*) – index of the parameter whose number of visits has to be updated.

```
class mushroom_rl.utils.parameters.AdaptiveParameter(value)
```

Bases: *object*

This class implements a basic adaptive gradient step. Instead of moving of a step proportional to the gradient, takes a step limited by a given metric. To specify the metric, the natural gradient has to be provided. If natural gradient is not provided, the identity matrix is used.

The step rule is:

$$\Delta\theta = \underset{\Delta\vartheta}{\operatorname{argmax}} \Delta\vartheta^t \nabla_{\theta} J \\ s.t. : \Delta\vartheta^T M \Delta\vartheta \leq \varepsilon$$

Lecture notes, Neumann G. <http://www.ias.informatik.tu-darmstadt.de/uploads/Geri/lecture-notes-constraint.pdf>

__init__(value)
Initialize self. See help(type(self)) for accurate signature.

__call__(*args, **kwargs)
Call self as a function.

3.11.11 Replay memory

class `mushroom_rl.utils.replay_memory.ReplayMemory(initial_size, max_size)`
Bases: `mushroom_rl.core.serialization.Serializable`

This class implements function to manage a replay memory as the one used in “Human-Level Control Through Deep Reinforcement Learning” by Mnih V. et al..

__init__(initial_size, max_size)
Constructor.

Parameters

- **initial_size (int)** – initial number of elements in the replay memory;
- **max_size (int)** – maximum number of elements that the replay memory can contain.

add(dataset)

Add elements to the replay memory.

Parameters `dataset (list)` – list of elements to add to the replay memory.

get(n_samples)

Returns the provided number of states from the replay memory.

Parameters `n_samples (int)` – the number of samples to return.

Returns The requested number of samples.

reset()

Reset the replay memory.

initialized

Whether the replay memory has reached the number of elements that allows it to be used.

Type Returns

size

The number of elements contained in the replay memory.

Type Returns

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

_add_save_attr(attr_dict)**

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

copy()

Returns A deepcopy of the agent.

classmethod load(path)

Load and deserialize the agent from the given location on disk.

Parameters `path` (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save (*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- `path` (*Path, str*) – Relative or absolute path to the object save location;
- `full_save` (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file, full_save, folder=’’*)

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file` (*ZipFile*) – ZipFile where the object needs to be saved;
- `full_save` (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- `folder` (*string, ‘’*) – subfolder to be used by the save method.

class `mushroom_rl.utils.replay_memory.SumTree(max_size)`

Bases: `object`

This class implements a sum tree data structure. This is used, for instance, by `PrioritizedReplayMemory`.

__init__ (*max_size*)

Constructor.

Parameters `max_size` (*int*) – maximum size of the tree.

add (*dataset, priority*)

Add elements to the tree.

Parameters

- `dataset` (*list*) – list of elements to add to the tree;
- `p` (*np.ndarray*) – priority of each sample in the dataset.

get (*s*)

Returns the provided number of states from the replay memory.

Parameters `s` (*float*) – the value of the samples to return.

Returns The requested sample.

update (*idx, priorities*)

Update the priority of the sample at the provided index in the dataset.

Parameters

- `idx` (*np.ndarray*) – indexes of the transitions in the dataset;
- `priorities` (*np.ndarray*) – priorities of the transitions.

size

The current size of the tree.

Type Returns

max_p

The maximum priority among the ones in the tree.

Type Returns

total_p

The sum of the priorities in the tree, i.e. the value of the root node.

Type Returns

```
class mushroom_rl.utils.replay_memory.PrioritizedReplayMemory(initial_size,
                                                               max_size,      al-
                                                               pha,   beta,   ep-
                                                               silon=0.01)
```

Bases: *mushroom_rl.core.serialization.Serializable*

This class implements function to manage a prioritized replay memory as the one used in “Prioritized Experience Replay” by Schaul et al., 2015.

__init__ (initial_size, max_size, alpha, beta, epsilon=0.01)

Constructor.

Parameters

- **initial_size** (*int*) – initial number of elements in the replay memory;
- **max_size** (*int*) – maximum number of elements that the replay memory can contain;
- **alpha** (*float*) – prioritization coefficient;
- **beta** (*float*) – importance sampling coefficient;
- **epsilon** (*float*, 01) – small value to avoid zero probabilities.

add (dataset, p)

Add elements to the replay memory.

Parameters

- **dataset** (*list*) – list of elements to add to the replay memory;
- **p** (*np.ndarray*) – priority of each sample in the dataset.

get (n_samples)

Returns the provided number of states from the replay memory.

Parameters **n_samples** (*int*) – the number of samples to return.

Returns The requested number of samples.

update (error, idx)

Update the priority of the sample at the provided index in the dataset.

Parameters

- **error** (*np.ndarray*) – errors to consider to compute the priorities;
- **idx** (*np.ndarray*) – indexes of the transitions in the dataset.

initialized

Whether the replay memory has reached the number of elements that allows it to be used.

Type Returns

max_priority

The maximum value of priority inside the replay memory.

Type Returns

`_post_load()`

This method can be overwritten to implement logic that is executed after the loading of the agent.

`_add_save_attr(attr_dict)`**

Add attributes that should be saved for an agent.

Parameters `**attr_dict` – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if `full_save` is set to True.

`copy()`

Returns A deepcopy of the agent.

`classmethod load(path)`

Load and deserialize the agent from the given location on disk.

Parameters `path (Path, string)` – Relative or absolute path to the agents save location.

Returns The loaded agent.

`save(path, full_save=False)`

Serialize and save the object to the given path on disk.

Parameters

- `path (Path, str)` – Relative or absolute path to the object save location;
- `full_save (bool)` – Flag to specify the amount of data to save for MushroomRL data structures.

`save_zip(zip_file, full_save, folder="")`

Serialize and save the agent to the given path on disk.

Parameters

- `zip_file (ZipFile)` – ZipFile where te object needs to be saved;
- `full_save (bool)` – flag to specify the amount of data to save for MushroomRL data structures;
- `folder (string, '')` – subfolder to be used by the save method.

3.11.12 Spaces

`class mushroom_rl.utils.spaces.Box(low, high, shape=None)`

Bases: `object`

This class implements functions to manage continuous states and action spaces. It is similar to the `Box` class in `gym.spaces.box`.

`__init__(low, high, shape=None)`

Constructor.

Parameters

- `low ([float, np.ndarray])` – the minimum value of each dimension of the space. If a scalar value is provided, this value is considered as the minimum one for each dimension. If a np.ndarray is provided, each i-th element is considered the minimum value of the i-th dimension;
- `high ([float, np.ndarray])` – the maximum value of dimensions of the space. If a scalar value is provided, this value is considered as the maximum one for each dimension.

If a np.ndarray is provided, each i-th element is considered the maximum value of the i-th dimension;

- **shape** (*np.ndarray, None*) – the dimension of the space. Must match the shape of low and high, if they are np.ndarray.

low

The minimum value of each dimension of the space.

Type Returns

high

The maximum value of each dimension of the space.

Type Returns

shape

The dimensions of the space.

Type Returns

class mushroom_rl.utils.spaces.**Discrete** (*n*)

Bases: object

This class implements functions to manage discrete states and action spaces. It is similar to the Discrete class in gym.spaces.discrete.

__init__ (*n*)

Constructor.

Parameters *n* (*int*) – the number of values of the space.

size

The number of elements of the space.

Type Returns

shape

The shape of the space that is always (1,).

Type Returns

3.11.13 Table

class mushroom_rl.utils.table.**Table** (*shape, initial_value=0.0, dtype=None*)

Bases: mushroom_rl.core.serialization.Serializable

Table regressor. Used for discrete state and action spaces.

__init__ (*shape, initial_value=0.0, dtype=None*)

Constructor.

Parameters

- **shape** (*tuple*) – the shape of the tabular regressor.
- **initial_value** (*float, 0.*) – the initial value for each entry of the tabular regressor.
- **dtype** (*[int, float], None*) – the dtype of the table array.

fit (*x, y*)

Parameters

- **x** (*int*) – index of the table to be filled;
- **y** (*float*) – value to fill in the table.

predict(**z*)

Predict the output of the table given an input.

Parameters

- ***z** (*list*) – list of input of the model. If the table is a Q-table,
- **list may contain states or states and actions depending (this)** – on whether the call requires to predict all q-values or only one q-value corresponding to the provided action;

Returns The table prediction.

n_actions

The number of actions considered by the table.

Type Returns**shape**

The shape of the table.

Type Returns**_add_save_attr**(***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

classmethod load(*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path, string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

save(*path, full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip(*zip_file, full_save, folder=”*)

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;

- **folder** (*string*, ' ') – subfolder to be used by the save method.

```
class mushroom_rl.utils.table.EnsembleTable (n_models, shape)
Bases: mushroom_rl.approximators._implementations.ensemble.Ensemble
```

This class implements functions to manage table ensembles.

__init__ (*n_models*, *shape*)

Constructor.

Parameters

- **n_models** (*int*) – number of models in the ensemble;
- **shape** (*np.ndarray*) – shape of each table in the ensemble.

_add_save_attr (***attr_dict*)

Add attributes that should be saved for an agent.

Parameters ****attr_dict** – dictionary of attributes mapped to the method that should be used to save and load them. If a “!” character is added at the end of the method, the field will be saved only if full_save is set to True.

_post_load()

This method can be overwritten to implement logic that is executed after the loading of the agent.

copy()

Returns A deepcopy of the agent.

fit (**z*, *idx=None*, ***fit_params*)

Fit the *idx*-th model of the ensemble if *idx* is provided, every model otherwise.

Parameters

- ***z** – a list containing the inputs to use to predict with each regressor of the ensemble;
- **idx** (*int*, *None*) – index of the model to fit;
- ****fit_params** – other params.

classmethod **load** (*path*)

Load and deserialize the agent from the given location on disk.

Parameters **path** (*Path*, *string*) – Relative or absolute path to the agents save location.

Returns The loaded agent.

model

The list of the models in the ensemble.

Type Returns

predict (**z*, *idx=None*, *prediction='mean'*, *compute_variance=False*, ***predict_params*)

Predict.

Parameters

- ***z** – a list containing the inputs to use to predict with each regressor of the ensemble;
- **idx** (*int*, *None*) – index of the model to use for prediction;
- **prediction** (*str*, 'mean') – the type of prediction to make. It can be a ‘mean’ of the ensembles, or a ‘sum’;
- **compute_variance** (*bool*, *False*) – whether to compute the variance of the prediction or not;

- ****predict_params** – other parameters used by the predict method the regressor.

Returns The predictions of the model.

reset()

Reset the model parameters.

save (*path*, *full_save=False*)

Serialize and save the object to the given path on disk.

Parameters

- **path** (*Path, str*) – Relative or absolute path to the object save location;
- **full_save** (*bool*) – Flag to specify the amount of data to save for MushroomRL data structures.

save_zip (*zip_file*, *full_save*, *folder=*"")

Serialize and save the agent to the given path on disk.

Parameters

- **zip_file** (*ZipFile*) – ZipFile where te object needs to be saved;
- **full_save** (*bool*) – flag to specify the amount of data to save for MushroomRL data structures;
- **folder** (*string, ''*) – subfolder to be used by the save method.

3.11.14 Torch

`mushroom_rl.utils.torch.set_weights(parameters, weights, use_cuda)`

Function used to set the value of a set of torch parameters given a vector of values.

Parameters

- **parameters** (*list*) – list of parameters to be considered;
- **weights** (*numpy.ndarray*) – array of the new values for the parameters;
- **use_cuda** (*bool*) – whether the parameters are cuda tensors or not;

`mushroom_rl.utils.torch.get_weights(parameters)`

Function used to get the value of a set of torch parameters as a single vector of values.

Parameters **parameters** (*list*) – list of parameters to be considered.

Returns A numpy vector consisting of all the values of the vectors.

`mushroom_rl.utils.torch.zero_grad(parameters)`

Function used to set to zero the value of the gradient of a set of torch parameters.

Parameters **parameters** (*list*) – list of parameters to be considered.

`mushroom_rl.utils.torch.get_gradient(params)`

Function used to get the value of the gradient of a set of torch parameters.

Parameters **parameters** (*list*) – list of parameters to be considered.

`mushroom_rl.utils.torch.to_float_tensor(x, use_cuda=False)`

Function used to convert a numpy array to a float torch tensor.

Parameters

- **x** (*np.ndarray*) – numpy array to be converted as torch tensor;

- **use_cuda** (*bool*) – whether to build a cuda tensors or not.

Returns A float tensor build from the values contained in the input array.

`mushroom_rl.utils.torch.to_int_tensor(x, use_cuda=False)`

Function used to convert a numpy array to a float torch tensor.

Parameters

- **x** (*np.ndarray*) – numpy array to be converted as torch tensor;
- **use_cuda** (*bool*) – whether to build a cuda tensors or not.

Returns A float tensor build from the values contained in the input array.

3.11.15 Value Functions

`mushroom_rl.utils.value_functions.compute_advantage_montecarlo(V, s, ss, r, absorbing, gamma)`

Function to estimate the advantage and new value function target over a dataset. The value function is estimated using rollouts (monte carlo estimation).

Parameters

- **V** (*Regressor*) – the current value function regressor;
- **s** (*numpy.ndarray*) – the set of states in which we want to evaluate the advantage;
- **ss** (*numpy.ndarray*) – the set of next states in which we want to evaluate the advantage;
- **r** (*numpy.ndarray*) – the reward obtained in each transition from state s to state ss;
- **absorbing** (*numpy.ndarray*) – an array of boolean flags indicating if the reached state is absorbing;
- **gamma** (*float*) – the discount factor of the considered problem.

Returns The new estimate for the value function of the next state and the advantage function.

`mushroom_rl.utils.value_functions.compute_advantage(V, s, ss, r, absorbing, gamma)`

Function to estimate the advantage and new value function target over a dataset. The value function is estimated using bootstrapping.

Parameters

- **V** (*Regressor*) – the current value function regressor;
- **s** (*numpy.ndarray*) – the set of states in which we want to evaluate the advantage;
- **ss** (*numpy.ndarray*) – the set of next states in which we want to evaluate the advantage;
- **r** (*numpy.ndarray*) – the reward obtained in each transition from state s to state ss;
- **absorbing** (*numpy.ndarray*) – an array of boolean flags indicating if the reached state is absorbing;
- **gamma** (*float*) – the discount factor of the considered problem.

Returns The new estimate for the value function of the next state and the advantage function.

`mushroom_rl.utils.value_functions.compute_gae(V, s, ss, r, absorbing, last, gamma, lam)`

Function to compute Generalized Advantage Estimation (GAE) and new value function target over a dataset.

“High-Dimensional Continuous Control Using Generalized Advantage Estimation”. Schulman J. et al.. 2016.

Parameters

- **v** (`Regressor`) – the current value function regressor;
- **s** (`numpy.ndarray`) – the set of states in which we want to evaluate the advantage;
- **ss** (`numpy.ndarray`) – the set of next states in which we want to evaluate the advantage;
- **r** (`numpy.ndarray`) – the reward obtained in each transition from state s to state ss;
- **absorbing** (`numpy.ndarray`) – an array of boolean flags indicating if the reached state is absorbing;
- **last** (`numpy.ndarray`) – an array of boolean flags indicating if the reached state is the last of the trajectory;
- **gamma** (`float`) – the discount factor of the considered problem;
- **lam** (`float`) – the value for the lambda coefficient used by GEA algorithm.

Returns The new estimate for the value function of the next state and the estimated generalized advantage.

3.11.16 Variance parameters

```
class mushroom_rl.utils.variance_parameters.VarianceParameter(value, exponential=False, min_value=None, tol=1.0, size=(1, ))
```

Bases: `mushroom_rl.utils.parameters.Parameter`

Abstract class to implement variance-dependent parameters. A target parameter is expected.

```
__init__(value, exponential=False, min_value=None, tol=1.0, size=(1, ))
```

Constructor.

Parameters `tol` (`float`) – value of the variance of the target variable such that The parameter value is 0.5.

```
_compute(*idx, **kwargs)
```

Returns: The value of the parameter in the provided index.

```
update(*idx, **kwargs)
```

Updates the value of the parameter in the provided index.

Parameters

- ***idx** (`list`) – index of the parameter whose number of visits has to be updated.
- **target** (`float`) – Value of the target variable;
- **factor** (`float`) – Multiplicative factor for the parameter value, useful when the parameter depend on another parameter value.

```
__call__(*idx, **kwargs)
```

Update and return the parameter in the provided index.

Parameters `*idx` (`list`) – index of the parameter to return.

Returns The updated parameter in the provided index.

```
get_value(*idx, **kwargs)
```

Return the current value of the parameter in the provided index.

Parameters `*idx` (*list*) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

shape

The shape of the table of parameters.

Type Returns

```
class mushroom_rl.utils.variance_parameters.VarianceIncreasingParameter(value,
                                                                      ex-
                                                                      po-
                                                                      nen-
                                                                      tial=False,
                                                                      min_value=None,
                                                                      tol=1.0,
                                                                      size=(1,
                                                                      ))
```

Bases: *mushroom_rl.utils.variance_parameters.VarianceParameter*

Class implementing a parameter that increases with the target variance.

__call__ (**idx*, ***kwargs*)

Update and return the parameter in the provided index.

Parameters `*idx` (*list*) – index of the parameter to return.

Returns The updated parameter in the provided index.

__init__ (*value*, *exponential=False*, *min_value=None*, *tol=1.0*, *size=(1,)*)

Constructor.

Parameters `tol` (*float*) – value of the variance of the target variable such that The parameter value is 0.5.

_compute (**idx*, ***kwargs*)

Returns: The value of the parameter in the provided index.

get_value (**idx*, ***kwargs*)

Return the current value of the parameter in the provided index.

Parameters `*idx` (*list*) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

shape

The shape of the table of parameters.

Type Returns

update (**idx*, ***kwargs*)

Updates the value of the parameter in the provided index.

Parameters

- **idx** (*list*) – index of the parameter whose number of visits has to be updated.
- **target** (*float*) – Value of the target variable;
- **factor** (*float*) – Multiplicative factor for the parameter value, useful when the parameter depend on another parameter value.

```
class mushroom_rl.utils.variance_parameters.VarianceDecreasingParameter(value,  

    ex-  

    po-  

    nen-  

    tial=False,  

    min_value=None,  

    tol=1.0,  

    size=(1,  

    ))
```

Bases: *mushroom_rl.utils.variance_parameters.VarianceParameter*

Class implementing a parameter that decreases with the target variance.

__call__(**idx*, ***kwargs*)

Update and return the parameter in the provided index.

Parameters ***idx**(*list*) – index of the parameter to return.

Returns The updated parameter in the provided index.

__init__(*value*, *exponential=False*, *min_value=None*, *tol=1.0*, *size=(1,)*)

Constructor.

Parameters **tol**(*float*) – value of the variance of the target variable such that The parameter value is 0.5.

_compute(**idx*, ***kwargs*)

Returns: The value of the parameter in the provided index.

get_value(**idx*, ***kwargs*)

Return the current value of the parameter in the provided index.

Parameters ***idx**(*list*) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

shape

The shape of the table of parameters.

Type Returns

update(**idx*, ***kwargs*)

Updates the value of the parameter in the provided index.

Parameters

- ***idx**(*list*) – index of the parameter whose number of visits has to be updated.
- **target**(*float*) – Value of the target variable;
- **factor**(*float*) – Multiplicative factor for the parameter value, useful when the parameter depend on another parameter value.

```
class mushroom_rl.utils.variance_parameters.WindowedVarianceParameter(value,  

    expo-  

    nen-  

    tial=False,  

    min_value=None,  

    tol=1.0,  

    win-  

    dow=100,  

    size=(1,  

    ))
```

Bases: *mushroom_rl.utils.parameters.Parameter*

Abstract class to implement variance-dependent parameters. A target parameter is expected. differently from the “Variance Parameter” class the variance is computed in a window interval.

__init__ (*value*, *exponential=False*, *min_value=None*, *tol=1.0*, *window=100*, *size=(1,)*)
Constructor.

Parameters

- **tol** (*float*) – value of the variance of the target variable such that the parameter value is 0.5.
- **window** (*int*) –

_compute (**idx*, ***kwargs*)

Returns: The value of the parameter in the provided index.

update (**idx*, ***kwargs*)

Updates the value of the parameter in the provided index.

Parameters

- ***idx** (*list*) – index of the parameter whose number of visits has to be updated.
- **target** (*float*) – Value of the target variable;
- **factor** (*float*) – Multiplicative factor for the parameter value, useful when the parameter depend on another parameter value.

__call__ (**idx*, ***kwargs*)

Update and return the parameter in the provided index.

Parameters ***idx** (*list*) – index of the parameter to return.

Returns The updated parameter in the provided index.

get_value (**idx*, ***kwargs*)

Return the current value of the parameter in the provided index.

Parameters ***idx** (*list*) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

shape

The shape of the table of parameters.

Type Returns

```
class mushroom_rl.utils.variance_parameters.WindowedVarianceIncreasingParameter(value,
                                                                                 ex-
                                                                                 po-
                                                                                 nen-
                                                                                 tial=False,
                                                                                 min_value=None,
                                                                                 tol=1.0,
                                                                                 win-
                                                                                 dow=100,
                                                                                 size=(1,
                                                                                 ))
```

Bases: *mushroom_rl.utils.variance_parameters.WindowedVarianceParameter*

Class implementing a parameter that decreases with the target variance, where the variance is computed in a fixed length window.

__call__(*idx, **kwargs)

Update and return the parameter in the provided index.

Parameters ***idx**(list) – index of the parameter to return.

Returns The updated parameter in the provided index.

__init__(value, exponential=False, min_value=None, tol=1.0, window=100, size=(1,))

Constructor.

Parameters

- **tol**(float) – value of the variance of the target variable such that the parameter value is 0.5.

- **window**(int) –

_compute(*idx, **kwargs)

Returns: The value of the parameter in the provided index.

get_value(*idx, **kwargs)

Return the current value of the parameter in the provided index.

Parameters ***idx**(list) – index of the parameter to return.

Returns The current value of the parameter in the provided index.

shape

The shape of the table of parameters.

Type Returns

update(*idx, **kwargs)

Updates the value of the parameter in the provided index.

Parameters

- ***idx**(list) – index of the parameter whose number of visits has to be updated.
- **target**(float) – Value of the target variable;
- **factor**(float) – Multiplicative factor for the parameter value, useful when the parameter depend on another parameter value.

3.11.17 Viewer

class mushroom_rl.utils.viewer.ImageViewer(size, dt)

Bases: object

Interface to pygame for visualizing plain images.

__init__(size, dt)

Constructor.

Parameters

- **size**([list, tuple]) – size of the displayed image;
- **dt**(float) – duration of a control step.

display(img)

Display given frame.

Parameters **img** – image to display.

```
class mushroom_rl.utils.viewer.Viewer(env_width, env_height, width=500, height=500, background=(0, 0, 0))
```

Bases: object

Interface to pygame for visualizing mushroom native environments.

```
__init__(env_width, env_height, width=500, height=500, background=(0, 0, 0))
```

Constructor.

Parameters

- **env_width** (*int*) – The x dimension limit of the desired environment;
- **env_height** (*int*) – The y dimension limit of the desired environment;
- **width** (*int*, 500) – width of the environment window;
- **height** (*int*, 500) – height of the environment window;
- **background** (*tuple*, (0, 0, 0)) – background color of the screen.

screen

Property.

Returns The screen created by this viewer.

size

Property.

Returns The size of the screen.

```
line(start, end, color=(255, 255, 255), width=1)
```

Draw a line on the screen.

Parameters

- **start** (*np.ndarray*) – starting point of the line;
- **end** (*np.ndarray*) – end point of the line;
- **color** (*tuple* (255, 255, 255)) – color of the line;
- **width** (*int*, 1) – width of the line.

```
square(center, angle, edge, color=(255, 255, 255), width=0)
```

Draw a square on the screen and apply a roto-translation to it.

Parameters

- **center** (*np.ndarray*) – the center of the polygon;
- **angle** (*float*) – the rotation to apply to the polygon;
- **edge** (*float*) – length of an edge;
- **color** (*tuple*, (255, 255, 255)) – the color of the polygon;
- **width** (*int*, 0) – the width of the polygon line, 0 to fill the polygon.

```
polygon(center, angle, points, color=(255, 255, 255), width=0)
```

Draw a polygon on the screen and apply a roto-translation to it.

Parameters

- **center** (*np.ndarray*) – the center of the polygon;
- **angle** (*float*) – the rotation to apply to the polygon;
- **points** (*list*) – the points of the polygon w.r.t. the center;

- **color** (*tuple, (255, 255, 255)*) – the color of the polygon;
- **width** (*int, 0*) – the width of the polygon line, 0 to fill the polygon.

circle (*center, radius, color=(255, 255, 255), width=0*)

Draw a circle on the screen.

Parameters

- **center** (*np.ndarray*) – the center of the circle;
- **radius** (*float*) – the radius of the circle;
- **color** (*tuple, (255, 255, 255)*) – the color of the circle;
- **width** (*int, 0*) – the width of the circle line, 0 to fill the circle.

arrow_head (*center, scale, angle, color=(255, 255, 255)*)

Draw an arrow head.

Parameters

- **center** (*np.ndarray*) – the position of the arrow head;
- **scale** (*float*) – scale of the arrow, correspond to the length;
- **angle** (*float*) – the angle of rotation of the arrow head;
- **color** (*tuple, (255, 255, 255)*) – the color of the arrow.

force_arrow (*center, direction, force, max_force, max_length, color=(255, 255, 255), width=1*)

Draw a force arrow, i.e. an arrow representing a force. The length of the arrow is directly proportional to the force value.

Parameters

- **center** (*np.ndarray*) – the point where the force is applied;
- **direction** (*np.ndarray*) – the direction of the force;
- **force** (*float*) – the applied force value;
- **max_force** (*float*) – the maximum force value;
- **max_length** (*float*) – the length to use for the maximum force;
- **color** (*tuple, (255, 255, 255)*) – the color of the arrow;
- **width** (*int, 1*) – the width of the force arrow.

torque_arrow (*center, torque, max_torque, max_radius, color=(255, 255, 255), width=1*)

Draw a torque arrow, i.e. a circular arrow representing a torque. The radius of the arrow is directly proportional to the torque value.

Parameters

- **center** (*np.ndarray*) – the point where the torque is applied;
- **torque** (*float*) – the applied torque value;
- **max_torque** (*float*) – the maximum torque value;
- **max_radius** (*float*) – the radius to use for the maximum torque;
- **color** (*tuple, (255, 255, 255)*) – the color of the arrow;
- **width** (*int, 1*) – the width of the torque arrow.

background_image(*img*)

Use the given image as background for the window, rescaling it appropriately.

Parameters **img** – the image to be used.

function(*x_s, x_e, f, n_points=100, width=1, color=(255, 255, 255)*)

Draw the graph of a function in the image.

Parameters

- **x_s** (*float*) – starting x coordinate;
- **x_e** (*float*) – final x coordinate;
- **f** (*function*) – the function that maps x coordinates into y coordinates;
- **n_points** (*int, 100*) – the number of segments used to approximate the function to draw;
- **width** (*int, 1*) – the width of the line drawn;
- **color** (*tuple, (255, 255, 255)*) – the color of the line.

display(*s*)

Display current frame and initialize the next frame to the background color.

Parameters **s** – time to wait in visualization.

close()

Close the viewer, destroy the window.

3.12 How to make a simple experiment

The main purpose of MushroomRL is to simplify the scripting of RL experiments. A standard example of a script to run an experiment in MushroomRL, consists of:

- an **initial part** where the setting of the experiment are specified;
- a **middle part** where the experiment is run;
- a **final part** where operations like evaluation, plot and save can be done.

A RL experiment consists of:

- a **MDP**;
- an **agent**;
- a **core**.

A **MDP** is the problem to be solved by the agent. It contains the function to move the agent in the environment according to the provided action. The MDP can be simply created with:

```
import numpy as np
from sklearn.ensemble import ExtraTreesRegressor

from mushroom_rl.algorithms.value import FQI
from mushroom_rl.core import Core
from mushroom_rl.environments import CarOnHill
from mushroom_rl.policy import EpsGreedy
from mushroom_rl.utils.dataset import compute_J
from mushroom_rl.utils.parameters import Parameter
```

(continues on next page)

(continued from previous page)

```
mdp = CarOnHill()
```

A MushroomRL **agent** is the algorithm that is run to learn in the MDP. It consists of a policy approximator and of the methods to improve the policy during the learning. It also contains the features to extract in the case of MDP with continuous state and action spaces. An agent can be defined this way:

```
# Policy
epsilon = Parameter(value=1.)
pi = EpsGreedy(epsilon=epsilon)

# Approximator
approximator_params = dict(input_shape=mdp.info.observation_space.shape,
                            n_actions=mdp.info.action_space.n,
                            n_estimators=50,
                            min_samples_split=5,
                            min_samples_leaf=2)
approximator = ExtraTreesRegressor

# Agent
agent = FQI(mdp.info, pi, approximator, n_iterations=20,
            approximator_params=approximator_params)
```

This piece of code creates the policy followed by the agent (e.g. ϵ -greedy) with $\epsilon = 1$. Then, the policy approximator is created specifying the parameters to create it and the class (in this case, the `ExtraTreesRegressor` class of scikit-learn is used). Eventually, the agent is created calling the algorithm class and providing the approximator and the policy, together with parameters used by the algorithm.

To run the experiment, the `core` module has to be used. This module requires the agent and the MDP object and contains the function to learn in the MDP and evaluate the learned policy. It can be created with:

```
core = Core(agent, mdp)
```

Once the core has been created, the agent can be trained collecting a dataset and fitting the policy:

```
core.learn(n_episodes=1000, n_episodes_per_fit=1000)
```

In this case, the agent's policy is fitted only once, after that 1000 episodes have been collected. This is a common practice in batch RL algorithms such as FQI where, initially, samples are randomly collected and then the policy is fitted using the whole dataset of collected samples.

Eventually, some operations to evaluate the learned policy can be done. This way the user can, for instance, compute the performance of the agent through the collected rewards during an evaluation run. Fixing $\epsilon = 0$, the greedy policy is applied starting from the provided initial states, then the average cumulative discounted reward is returned.

```
pi.set_epsilon(Parameter(0.))
initial_state = np.array([[-.5, 0.]])
dataset = core.evaluate(initial_states=initial_state)

print(compute_J(dataset, gamma=mdp.info.gamma))
```

3.13 How to make an advanced experiment

Continuous MDPs are a challenging class of problems to solve in RL. In these problems, a tabular regressor is not enough to approximate the Q-function, since there are an infinite number of states/actions. The solution to solve them

is to use a function approximator (e.g. neural network) fed with the raw values of states and actions. In the case a linear approximator is used, it is convenient to enlarge the input space with the space of non-linear **features** extracted from the raw values. This way, the linear approximator is often able to solve the MDPs, despite its simplicity. Many RL algorithms rely on the use of a linear approximator to solve a MDP, therefore the use of features is very important. This tutorial shows how to solve a continuous MDP in MushroomRL using an algorithm that requires the use of a linear approximator.

Initially, the MDP and the policy are created:

```
import numpy as np

from mushroom_rl.algorithms.value import SARSALambdaContinuous
from mushroom_rl.approximators.parametric import LinearApproximator
from mushroom_rl.core import Core
from mushroom_rl.features import Features
from mushroom_rl.features.tiles import Tiles
from mushroom_rl.policy import EpsGreedy
from mushroom_rl.utils.callbacks import CollectDataset
from mushroom_rl.utils.parameters import Parameter
from mushroom_rl.environments import Gym

# MDP
mdp = Gym(name='MountainCar-v0', horizon=np.inf, gamma=1.)

# Policy
epsilon = Parameter(value=0.)
pi = EpsGreedy(epsilon=epsilon)
```

This is an environment created with the MushroomRL interface to the OpenAI Gym library. Each environment offered by OpenAI Gym can be created this way simply providing the corresponding id in the `name` parameter, except for the Atari that are managed by a separate class. After the creation of the MDP, the tiles features are created:

```
n_tilings = 10
tilings = Tiles.generate(n_tilings, [10, 10],
                        mdp.info.observation_space.low,
                        mdp.info.observation_space.high)
features = Features(tilings=tilings)

approximator_params = dict(input_shape=(features.size,),
                            output_shape=(mdp.info.action_space.n,),
                            n_actions=mdp.info.action_space.n)
```

In this example, we use sparse coding by means of **tiles** features. The `generate` method generates `n_tilings` grids of 10x10 tilings evenly spaced (the way the tilings are created is explained in “*Reinforcement Learning: An Introduction*”, Sutton & Barto, 1998). Eventually, the grid is passed to the `Features` factory method that returns the `features` class.

MushroomRL offers other type of features such a **radial basis functions** and **polynomial** features. The former have also a faster implementation written in Tensorflow that can be used transparently.

Then, the agent is created as usual, but this time passing the feature to it. It is important to notice that the learning rate is divided by the number of tilings for the correctness of the update (see “*Reinforcement Learning: An Introduction*”, Sutton & Barto, 1998 for details). After that, the learning is run as usual:

```
learning_rate = Parameter(.1 / n_tilings)
```

(continues on next page)

(continued from previous page)

```

agent = SARSALambdaContinuous(mdp.info, pi, LinearApproximator,
                               approximator_params=approximator_params,
                               learning_rate=learning_rate,
                               lambda_coeff=.9, features=features)

# Algorithm
collect_dataset = CollectDataset()
callbacks = [collect_dataset]
core = Core(agent, mdp, callbacks_fit=callbacks)

# Train
core.learn(n_episodes=100, n_steps_per_fit=1)

```

To visualize the learned policy the rendering method of OpenAI Gym is used. To activate the rendering in the environments that supports it, it is necessary to set `render=True`.

```
core.evaluate(n_episodes=1, render=True)
```

3.14 How to create a regressor

MushroomRL offers a high-level interface to build function regressors. Indeed, it transparently manages regressors for generic functions and Q-function regressors. The user should not care about the low-level implementation of these regressors and should only use the `Regressor` interface. This interface creates a Q-function regressor or a `GenericRegressor` depending on whether the `n_actions` parameter is provided to the constructor or not.

3.14.1 Usage of the Regressor interface

When the action space of RL problems is finite and the adopted approach is value-based, we want to compute the Q-function of each action. In MushroomRL, this is possible using:

- a Q-function regressor with a different approximator for each action (`ActionRegressor`);
- a single Q-function regressor with a different output for each action (`QRegressor`).

The `QRegressor` is suggested when the number of discrete actions is high, due to memory reasons.

The user can create create a `QRegressor` or an `ActionRegressor`, setting the `output_shape` parameter of the `Regressor` interface. If it is set to `(1,)`, an `ActionRegressor` is created; otherwise if it is set to the number of discrete actions, a `QRegressor` is created.

3.14.2 Example

Initially, the MDP, the policy and the features are created:

```

import numpy as np

from mushroom_rl.algorithms.value import SARSALambdaContinuous
from mushroom_rl.approximators.parametric import LinearApproximator
from mushroom_rl.core import Core
from mushroom_rl.environments import *
from mushroom_rl.features import Features

```

(continues on next page)

(continued from previous page)

```

from mushroom_rl.features.tiles import Tiles
from mushroom_rl.policy import EpsGreedy
from mushroom_rl.utils.callbacks import CollectDataset
from mushroom_rl.utils.parameters import Parameter

# MDP
mdp = Gym(name='MountainCar-v0', horizon=np.inf, gamma=1.)

# Policy
epsilon = Parameter(value=0.)
pi = EpsGreedy(epsilon=epsilon)

# Q-function approximator
n_tilings = 10
tilings = Tiles.generate(n_tilings, [10, 10],
                        mdp.info.observation_space.low,
                        mdp.info.observation_space.high)
features = Features(tilings=tilings)

# Agent
learning_rate = Parameter(.1 / n_tilings)

```

The following snippet, sets the output shape of the regressor to the number of actions, creating a QRegressor:

```

approximator_params = dict(input_shape=(features.size,),
                           output_shape=(mdp.info.action_space.n,),
                           n_actions=mdp.info.action_space.n)

```

If you prefer to use an ActionRegressor, simply set the number of actions to (1,):

```

approximator_params = dict(input_shape=(features.size,),
                           output_shape=(1,),
                           n_actions=mdp.info.action_space.n)

```

Then, the rest of the code fits the approximator and runs the evaluation rendering the behaviour of the agent:

```

agent = SARSAContinuous(mdp.info, pi, LinearApproximator,
                        approximator_params=approximator_params,
                        learning_rate=learning_rate,
                        lambda_coeff=.9, features=features)

# Algorithm
collect_dataset = CollectDataset()
callbacks = [collect_dataset]
core = Core(agent, mdp, callbacks_fit=callbacks)

# Train
core.learn(n_episodes=100, n_steps_per_fit=1)

# Evaluate
core.evaluate(n_episodes=1, render=True)

```

3.14.3 Generic regressor

Whenever the `n_actions` parameter is not provided, the `Regressor` interface creates a `GenericRegressor`. This regressor can be used for general purposes and it is more flexible to be used. It is commonly used in policy search algorithms.

Example

Create a dataset of points distributed on a line with random gaussian noise.

```
import numpy as np
from matplotlib import pyplot as plt

from mushroom_rl.approximators import Regressor
from mushroom_rl.approximators.parametric import LinearApproximator

x = np.arange(10).reshape(-1, 1)

intercept = 10
noise = np.random.randn(10, 1) * 1
y = 2 * x + intercept + noise
```

To fit the intercept, polynomial features of degree 1 are created by hand:

```
phi = np.concatenate((np.ones(10).reshape(-1, 1), x), axis=1)
```

The regressor is then created and fit (note that `n_actions` is not provided):

```
regressor = Regressor(LinearApproximator,
                      input_shape=(2,),
                      output_shape=(1,))

regressor.fit(phi, y)
```

Eventually, the approximated function of the regressor is plotted together with the target points. Moreover, the weights and the gradient in point 5 of the linear approximator are printed.

```
print('Weights: ' + str(regressor.get_weights()))
print('Gradient: ' + str(regressor.diff(np.array([[5.]])))))

plt.scatter(x, y)
plt.plot(x, regressor.predict(phi))
plt.show()
```

3.15 How to make a deep RL experiment

The usual script to run a deep RL experiment does not significantly differ from the one for a shallow RL experiment. This tutorial shows how to solve `Atari` games in MushroomRL using `DQN`, and how to solve `MuJoCo` tasks using `DDPG`. This tutorial will not explain some technicalities that are already described in the previous tutorials, and will only briefly explain how to run deep RL experiments. Be sure to read the previous tutorials before starting this one.

3.15.1 Solving Atari with DQN

This script runs the experiment to solve the Atari Breakout game as described in the DQN paper “*Human-level control through deep reinforcement learning*”, Mnih V. et al., 2015). We start creating the neural network to learn the action-value function:

```
import numpy as np
import torch
import torch.nn as nn
import torch.optim as optim
import torch.nn.functional as F

from mushroom_rl.algorithms.value import DQN
from mushroom_rl.approximators.parametric import TorchApproximator
from mushroom_rl.core import Core
from mushroom_rl.environments import Atari
from mushroom_rl.policy import EpsGreedy
from mushroom_rl.utils.dataset import compute_metrics
from mushroom_rl.utils.parameters import LinearParameter, Parameter

class Network(nn.Module):
    n_features = 512

    def __init__(self, input_shape, output_shape, **kwargs):
        super().__init__()

        n_input = input_shape[0]
        n_output = output_shape[0]

        self._h1 = nn.Conv2d(n_input, 32, kernel_size=8, stride=4)
        self._h2 = nn.Conv2d(32, 64, kernel_size=4, stride=2)
        self._h3 = nn.Conv2d(64, 64, kernel_size=3, stride=1)
        self._h4 = nn.Linear(3136, self.n_features)
        self._h5 = nn.Linear(self.n_features, n_output)

        nn.init.xavier_uniform_(self._h1.weight,
                               gain=nn.init.calculate_gain('relu'))
        nn.init.xavier_uniform_(self._h2.weight,
                               gain=nn.init.calculate_gain('relu'))
        nn.init.xavier_uniform_(self._h3.weight,
                               gain=nn.init.calculate_gain('relu'))
        nn.init.xavier_uniform_(self._h4.weight,
                               gain=nn.init.calculate_gain('relu'))
        nn.init.xavier_uniform_(self._h5.weight,
                               gain=nn.init.calculate_gain('linear'))

    def forward(self, state, action=None):
        h = F.relu(self._h1(state.float() / 255.))
        h = F.relu(self._h2(h))
        h = F.relu(self._h3(h))
        h = F.relu(self._h4(h.view(-1, 3136)))
        q = self._h5(h)

        if action is None:
            return q
        else:
            q_acted = torch.squeeze(q.gather(1, action.long()))
```

(continues on next page)

(continued from previous page)

```
    return q_acted
```

Note that the forward function may return all the action-values of state, or only the one for the provided action. This network will be used later in the script. Now, we define useful functions, set some hyperparameters, and create the mdp and the policy pi:

```
def print_epoch(epoch):
    print('#####')
    print('Epoch: ', epoch)
    print('-----')

def get_stats(dataset):
    score = compute_metrics(dataset)
    print(('min_reward: %f, max_reward: %f, mean_reward: %f,' +
          ' games_completed: %d' % score))

    return score

scores = list()

optimizer = dict()
optimizer['class'] = optim.Adam
optimizer['params'] = dict(lr=.00025)

# Settings
width = 84
height = 84
history_length = 4
train_frequency = 4
evaluation_frequency = 250000
target_update_frequency = 10000
initial_replay_size = 50000
max_replay_size = 500000
test_samples = 125000
max_steps = 50000000

# MDP
mdp = Atari('BreakoutDeterministic-v4', width, height, ends_at_life=True,
            history_length=history_length, max_no_op_actions=30)

# Policy
epsilon = LinearParameter(value=1.,
                           threshold_value=.1,
                           n=1000000)
epsilon_test = Parameter(value=.05)
epsilon_random = Parameter(value=1)
pi = EpsGreedy(epsilon=epsilon_random)
```

Differently from the literature, we use Adam as the optimizer.

Then, the approximator:

```
# Approximator
input_shape = (history_length, height, width)
```

(continues on next page)

(continued from previous page)

```
approximator_params = dict(
    network=Network,
    input_shape=input_shape,
    output_shape=(mdp.info.action_space.n,),
    n_actions=mdp.info.action_space.n,
    n_features=Network.n_features,
    optimizer=optimizer,
    loss=F.smooth_l1_loss
)

approximator = TorchApproximator
```

Finally, the agent and the core:

```
# Agent
algorithm_params = dict(
    batch_size=32,
    target_update_frequency=target_update_frequency // train_frequency,
    replay_memory=None,
    initial_replay_size=initial_replay_size,
    max_replay_size=max_replay_size
)

agent = DQN(mdp.info, pi, approximator,
            approximator_params=approximator_params,
            **algorithm_params)

# Algorithm
core = Core(agent, mdp)
```

Eventually, the learning loop is performed. As done in literature, learning and evaluation steps are alternated:

```
# RUN

# Fill replay memory with random dataset
print_epoch(0)
core.learn(n_steps=initial_replay_size,
           n_steps_per_fit=initial_replay_size)

# Evaluate initial policy
pi.set_epsilon(epsilon_test)
mdp.set_episode_end(False)
dataset = core.evaluate(n_steps=test_samples)
scores.append(get_stats(dataset))

for n_epoch in range(1, max_steps // evaluation_frequency + 1):
    print_epoch(n_epoch)
    print('- Learning:')
    # learning step
    pi.set_epsilon(epsilon)
    mdp.set_episode_end(True)
    core.learn(n_steps=evaluation_frequency,
               n_steps_per_fit=train_frequency)

    print('- Evaluation:')
    # evaluation step
    pi.set_epsilon(epsilon_test)
```

(continues on next page)

(continued from previous page)

```
mdp.set_episode_end(False)
dataset = core.evaluate(n_steps=test_samples)
scores.append(get_stats(dataset))
```

3.15.2 Solving MuJoCo with DDPG

This script runs the experiment to solve the Walker-Stand MuJoCo task, as implemented in [MuJoCo](#). As with DQN, we start creating the neural networks. For DDPG, we need an actor and a critic network:

```
import numpy as np

import torch
import torch.nn as nn
import torch.optim as optim
import torch.nn.functional as F

from mushroom_rl.algorithms.actor_critic import DDPG
from mushroom_rl.core import Core
from mushroom_rl.environments.dmc_control_env import DMControl
from mushroom_rl.policy import OrnsteinUhlenbeckPolicy
from mushroom_rl.utils.dataset import compute_J


class CriticNetwork(nn.Module):
    def __init__(self, input_shape, output_shape, n_features, **kwargs):
        super().__init__()

        n_input = input_shape[-1]
        n_output = output_shape[0]

        self._h1 = nn.Linear(n_input, n_features)
        self._h2 = nn.Linear(n_features, n_features)
        self._h3 = nn.Linear(n_features, n_output)

        nn.init.xavier_uniform_(self._h1.weight,
                               gain=nn.init.calculate_gain('relu'))
        nn.init.xavier_uniform_(self._h2.weight,
                               gain=nn.init.calculate_gain('relu'))
        nn.init.xavier_uniform_(self._h3.weight,
                               gain=nn.init.calculate_gain('linear'))

    def forward(self, state, action):
        state_action = torch.cat((state.float(), action.float()), dim=1)
        features1 = F.relu(self._h1(state_action))
        features2 = F.relu(self._h2(features1))
        q = self._h3(features2)

        return torch.squeeze(q)

class ActorNetwork(nn.Module):
    def __init__(self, input_shape, output_shape, n_features, **kwargs):
        super(ActorNetwork, self).__init__()

        n_input = input_shape[-1]
```

(continues on next page)

(continued from previous page)

```

n_output = output_shape[0]

self._h1 = nn.Linear(n_input, n_features)
self._h2 = nn.Linear(n_features, n_features)
self._h3 = nn.Linear(n_features, n_output)

nn.init.xavier_uniform_(self._h1.weight,
                       gain=nn.init.calculate_gain('relu'))
nn.init.xavier_uniform_(self._h2.weight,
                       gain=nn.init.calculate_gain('relu'))
nn.init.xavier_uniform_(self._h3.weight,
                       gain=nn.init.calculate_gain('linear'))

def forward(self, state):
    features1 = F.relu(self._h1(torch.squeeze(state, 1).float()))
    features2 = F.relu(self._h2(features1))
    a = self._h3(features2)

    return a

```

We create the mdp, the policy, and set some hyperparameters:

```

# MDP
horizon = 500
gamma = 0.99
gamma_eval = 1.
mdp = DMControl('walker', 'stand', horizon, gamma)

# Policy
policy_class = OrnsteinUhlenbeckPolicy
policy_params = dict(sigma=np.ones(1) * .2, theta=.15, dt=1e-2)

# Settings
initial_replay_size = 500
max_replay_size = 5000
batch_size = 200
n_features = 80
tau = .001

```

Note that the policy is not instantiated in the script, since in DDPG the instantiation is done inside the algorithm constructor.

We create the actor and the critic approximators:

```

# Approximator
actor_input_shape = mdp.info.observation_space.shape
actor_params = dict(network=ActorNetwork,
                     n_features=n_features,
                     input_shape=actor_input_shape,
                     output_shape=mdp.info.action_space.shape)

actor_optimizer = {'class': optim.Adam,
                  'params': {'lr': 1e-5}}

critic_input_shape = (actor_input_shape[0] + mdp.info.action_space.shape[0],)
critic_params = dict(network=CriticNetwork,
                     optimizer={'class': optim.Adam,

```

(continues on next page)

(continued from previous page)

```
'params': {'lr': 1e-3},
loss=F.mse_loss,
n_features=n_features,
input_shape=critic_input_shape,
output_shape=(1,))
```

Finally, we create the agent and the core:

```
# Agent
agent = DDPG(mdp.info, policy_class, policy_params,
              actor_params, actor_optimizer, critic_params,
              batch_size, initial_replay_size, max_replay_size,
              tau)

# Algorithm
core = Core(agent, mdp)
```

As in DQN, we alternate learning and evaluation steps:

```
# Fill the replay memory with random samples
core.learn(n_steps=initial_replay_size, n_steps_per_fit=initial_replay_size)

# RUN
n_epochs = 40
n_steps = 1000
n_steps_test = 2000

dataset = core.evaluate(n_steps=n_steps_test, render=False)
J = compute_J(dataset, gamma_eval)
print('Epoch: 0')
print('J: ', np.mean(J))

for n in range(n_epochs):
    print('Epoch: ', n+1)
    core.learn(n_steps=n_steps, n_steps_per_fit=1)
    dataset = core.evaluate(n_steps=n_steps_test, render=False)
```

Python Module Index

m

mushroom_rl.environments.gym_env, 90
mushroom_rl.algorithms.actor_critic.classic_maze_env, 91
mushroom_rl.algorithms.actor_critic.deep_maze_env, 93
mushroom_rl.environments.lqr, 93
mushroom_rl.environments.mujoco, 95
mushroom_rl.environments.puddle_world, 98
mushroom_rl.environments.segway, 100
mushroom_rl.environments.ship_steering, 100
mushroom_rl.environments.tiles.tiles, 109
mushroom_rl.features._implementations.features_implementations, 106
mushroom_rl.features.basis.fourier, 106
mushroom_rl.features.basis.gaussian_rbf, 107
mushroom_rl.features.basis.polynomial, 108
mushroom_rl.features.torch_approximator, 108
mushroom_rl.features.features, 105
mushroom_rl.features.tensors.gaussian_tensor, 108
mushroom_rl.policy.deterministic_policy, 113
mushroom_rl.policy.gaussian_policy, 115
mushroom_rl.policy.noise_policy, 124
mushroom_rl.policy.policy, 110
mushroom_rl.policy.td_policy, 126
mushroom_rl.policy.torch_policy, 132
mushroom_rl.solvers.car_on_hill, 139
mushroom_rl.solvers.dynamic_programming, 139
mushroom_rl.solvers.lqr, 140
mushroom_rl.utils.angles, 142
mushroom_rl.utils.callbacks, 142
mushroom_rl.utils.dataset, 144
mushroom_rl.utils.eligibility_trace, 145
mushroom_rl.utils.features, 149
mushroom_rl.utils.folder, 149
mushroom_rl.utils.frames, 150
mushroom_rl.utils.minibatches, 150

mushroom_rl.utils.numerical_gradient,
150
mushroom_rl.utils.parameters, 151
mushroom_rl.utils.replay_memory, 154
mushroom_rl.utils.spaces, 157
mushroom_rl.utils.table, 158
mushroom_rl.utils.torch, 161
mushroom_rl.utils.value_functions, 162
mushroom_rl.utils.variance_parameters,
163
mushroom_rl.utils.viewer, 167

Symbols

__call__(mushroom_rl.approximators.regressor.Regressor method), 67
__call__(mushroom_rl.distributions.distribution.Distribution method), 73
__call__(mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution method), 79
__call__(mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution method), 77
__call__(mushroom_rl.distributions.gaussian.GaussianDistribution method), 75
__call__(mushroom_rl.features.basis.fourier.FourierBasis method), 106
__call__(mushroom_rl.features.basis.gaussian_rbf.GaussianRBF method), 107
__call__(mushroom_rl.features.basis.polynomial.PolynomialBasis method), 108
__call__(mushroom_rl.features.tiles.tiles.Tiles method), 109
__call__(mushroom_rl.policy.deterministic_policy.DeterministicPolicy method), 113
__call__(mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy method), 115
__call__(mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy method), 119
__call__(mushroom_rl.policy.gaussian_policy.GaussianPolicy method), 117
__call__(mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy method), 123
__call__(mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy method), 121
__call__(mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy method), 125
__call__(mushroom_rl.policy.policy.ParametricPolicy method), 112
__call__(mushroom_rl.policy.policy.Policy method), 110
__call__(mushroom_rl.policy.td_policy.Boltzmann method), 129
__call__(mushroom_rl.policy.td_policy.EpsGreedy method), 128
__call__(mushroom_rl.policy.td_policy.Mellowmax method), 131
__call__(mushroom_rl.policy.td_policy.TDPolicy method), 126
__call__(mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy method), 137
__call__(mushroom_rl.policy.torch_policy.GaussianTorchPolicy method), 135
__call__(mushroom_rl.utils.callbacks.Callback method), 143
__call__(mushroom_rl.utils.callbacks.CollectDataset method), 143
__call__(mushroom_rl.utils.callbacks.CollectMaxQ method), 143
__call__(mushroom_rl.utils.callbacks.CollectParameters method), 144
__call__(mushroom_rl.utils.callbacks.CollectQ method), 144
__call__(mushroom_rl.utils.parameters.AdaptiveParameter method), 154
__call__(mushroom_rl.utils.parameters.ExponentialParameter method), 154
__call__(mushroom_rl.utils.parameters.LinearParameter method), 153
__call__(mushroom_rl.utils.variance_parameters.VarianceDecreasing method), 151
__call__(mushroom_rl.utils.variance_parameters.VarianceIncreasing method), 165
__call__(mushroom_rl.utils.variance_parameters.VarianceParameter method), 164
__call__(mushroom_rl.utils.variance_parameters.WindowedVariance method), 163
__call__(mushroom_rl.utils.variance_parameters.WindowedVariance method), 166
__call__(mushroom_rl.utils.variance_parameters.WindowedVariance method), 166

```

__init__(mushroom_rl.core.serialization.Serializable __init__() (mushroom_rl.algorithms.value.dqn.DQN
    attribute), 10 method), 59
__init__(mushroom_rl.distributions.distribution.Distribution __init__() (mushroom_rl.algorithms.value.dqn.DoubleDQN
    attribute), 74 method), 61
__init__(mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy (mushroom_rl.algorithms.value.td.DoubleQLearning
    attribute), 115 method), 45
__init__(mushroom_rl.policy.policy.ParametricPolicy __init__() (mushroom_rl.algorithms.value.td.ExpectedSARSA
    attribute), 112 method), 40
__init__(mushroom_rl.policy.policy.Policy attribute), __init__() (mushroom_rl.algorithms.value.td.QLambda
    110 method), 43
__init__() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.CORDACorQ __init__() (mushroom_rl.algorithms.value.td.QLearning
    method), 11 method), 42
__init__() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.SochasticACrl __init__() (mushroom_rl.algorithms.value.td.RLearning
    method), 12 method), 48
__init__() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.SochasticACrlAM __init__() (mushroom_rl.algorithms.value.td.RQLearning
    method), 14 method), 51
__init__() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2G __init__() (mushroom_rl.algorithms.value.td.SARSA
    method), 17 method), 37
__init__() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.QDN __init__() (mushroom_rl.algorithms.value.td.SARSA
    method), 18 method), 39
__init__() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepA __init__() (mushroom_rl.algorithms.value.td.SARSA
    method), 15 method), 52
__init__() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.PP __init__() (mushroom_rl.algorithms.value.td.SpeedyQLearning
    method), 26 method), 46
__init__() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.QAG __init__() (mushroom_rl.algorithms.value.td.TrueOnlineSARSA
    method), 22 method), 54
__init__() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD __init__() (mushroom_rl.algorithms.value.td.WeightedQLearning
    method), 20 method), 49
__init__() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TR __init__() (mushroom_rl.approximators.parametric.linear.LinearApproximator
    method), 24 method), 68
__init__(mushroom_rl.algorithms.agent.Agent __init__() (mushroom_rl.approximators.parametric.torch_approximator
    method), 6 method), 70
__init__(mushroom_rl.algorithms.policy_search.black_box_optimization.REPS __init__() (mushroom_rl.approximators.regressor.Regressor
    method), 34 method), 66
__init__(mushroom_rl.algorithms.policy_search.black_box_optimization.REPS __init__() (mushroom_rl.core.core.Core
    method), 36 method), 8
__init__(mushroom_rl.algorithms.policy_search.black_box_optimization.RWR __init__() (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution
    method), 33 method), 77
__init__(mushroom_rl.algorithms.policy_search.policy_gradient.GDMDP __init__() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution
    method), 29 method), 77
__init__(mushroom_rl.algorithms.policy_search.policy_gradient.RLINFORCE __init__() (mushroom_rl.environments.atari.Atari
    method), 28 method), 77
__init__(mushroom_rl.algorithms.policy_search.policy_gradient.NAC __init__() (mushroom_rl.environments.atari.MaxAndSkip
    method), 31 method), 83
__init__(mushroom_rl.algorithms.value.batch_td.DoubleFQI __init__() (mushroom_rl.environments.car_on_hill.CarOnHill
    method), 57 method), 81
__init__(mushroom_rl.algorithms.value.batch_td.FQI __init__() (mushroom_rl.environments.cart_pole.CartPole
    method), 55 method), 84
__init__(mushroom_rl.algorithms.value.batch_td.LSPI __init__() (mushroom_rl.environments.dmc_control_env.DMControl
    method), 58 method), 92
__init__(mushroom_rl.algorithms.value.dqn.AveragedDQN __init__() (mushroom_rl.environments.environment.Environment
    method), 63 method), 85
__init__(mushroom_rl.algorithms.value.dqn.CategoricalDQN __init__() (mushroom_rl.environments.environment.MDPInfo
    method), 65 method), 7

```

`method), 7`
`__init__(mushroom_rl.environments.finite_mdp.FiniteMDP, method), 86`
`__init__(mushroom_rl.environments.grid_world.AbstractGridWorld, method), 87`
`__init__(mushroom_rl.environments.grid_world.GridWorld, method), 88`
`__init__(mushroom_rl.environments.grid_world.GridWorldVanHasselt, method), 89`
`__init__(mushroom_rl.environments.gym_env.Gym, method), 90`
`__init__(mushroom_rl.environments.inverted_pendulum.InvertedPendulum, method), 91`
`__init__(mushroom_rl.environments.lqr.LQR, method), 94`
`__init__(mushroom_rl.environments.mujoco.MuJoCo, method), 95`
`__init__(mushroom_rl.environments.puddle_world.PuddleWorld, method), 98`
`__init__(mushroom_rl.environments.segway.Segway, method), 100`
`__init__(mushroom_rl.environments.ship_steering.ShipSteering, method), 101`
`__init__(mushroom_rl.features.basis.fourier.FourierBasis, method), 106`
`__init__(mushroom_rl.features.basis.gaussian_rbf.GaussianRBF, method), 107`
`__init__(mushroom_rl.features.basis.polynomial.PolynomialBasis, method), 108`
`__init__(mushroom_rl.features.tensors.gaussian_tensor.GaussianTensor, method), 108`
`__init__(mushroom_rl.features.tiles.tiles.Tiles, method), 109`
`__init__(mushroom_rl.policy.deterministic_policy.DeterministicPolicy, method), 113`
`__init__(mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy, method), 118`
`__init__(mushroom_rl.policy.gaussian_policy.GaussianPolicy, method), 116`
`__init__(mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy, method), 122`
`__init__(mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy, method), 120`
`__init__(mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy, method), 124`
`__init__(mushroom_rl.policy.td_policy.Boltzmann, method), 129`
`__init__(mushroom_rl.policy.td_policy.EpsGreedy, method), 127`
`__init__(mushroom_rl.policy.td_policy.Mellowmax, method), 130`
`__init__(mushroom_rl.policy.td_policy.TDPolicy, method), 126`
`__init__(mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy, method), 136`
`method), 134`
`method), 132`
`method), 142`
`mushroom_rl.utils.callbacks.Callback, method), 143`
`mushroom_rl.utils.callbacks.CollectMaxQ, method), 143`
`mushroom_rl.utils.callbacks.CollectParameters, method), 143`
`mushroom_rl.utils.callbacks.CollectQ, method), 143`
`mushroom_rl.utils.eligibility_trace.AccumulatingTrace, method), 147`
`mushroom_rl.utils.eligibility_trace.ReplacingTrace, method), 145`
`mushroom_rl.utils.frames.LazyFrames, method), 150`
`mushroom_rl.utils.parameters.AdaptiveParameter, method), 153`
`mushroom_rl.utils.parameters.ExponentialParameter, method), 153`
`mushroom_rl.utils.parameters.LinearParameter, method), 152`
`mushroom_rl.utils.parameters.Parameter, method), 151`
`mushroom_rl.utils.replay_memory.PrioritizedReplayMemory, method), 156`
`mushroom_rl.utils.replay_memory.ReplayMemory, method), 154`
`mushroom_rl.utils.replay_memory.SumTree, method), 155`
`mushroom_rl.utils.spaces.Box, method), 157`
`mushroom_rl.utils.spaces.Discrete, method), 158`
`mushroom_rl.utils.table.EnsembleTable, method), 160`
`mushroom_rl.utils.table.Table, method), 158`
`mushroom_rl.utils.variance_parameters.VarianceDecreasing, method), 165`
`mushroom_rl.utils.variance_parameters.VarianceIncreasing, method), 164`
`mushroom_rl.utils.variance_parameters.VarienceParameter, method), 163`
`mushroom_rl.utils.variance_parameters.WindowedVarience, method), 167`
`mushroom_rl.utils.variance_parameters.WindowedVarience, method), 166`
`mushroom_rl.utils.viewer.ImageViewer, method), 167`
`mushroom_rl.utils.viewer.Viewer, method), 167`

```

        method), 168
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.classic_actor_critic.COPDAGOr.rl.algorithms.value.batch_td.FQI
    method), 11                  method), 56
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.classic_actor_critic.StochasticACrl.algorithms.value.batch_td.LSPI
    method), 13                  method), 58
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.classic_actor_critic.StochasticACrl.algorithms.value.dqn.AveragedDQN
    method), 14                  method), 63
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.deep_actor_critic.A2C   room_rl.algorithms.value.dqn.CategoricalDQN
    method), 17                  method), 65
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.deep_actor_critic.DDPG   room_rl.algorithms.value.dqn.DQN   method),
    method), 19                  60
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.deep_actor_critic.DeepAC room_rl.algorithms.value.dqn.DoubleDQN
    method), 15                  method), 62
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.deep_actor_critic.PPO   room_rl.algorithms.value.td.DoubleQLearning
    method), 26                  method), 45
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.deep_actor_critic.SAC   room_rl.algorithms.value.td.ExpectedSARSA
    method), 23                  method), 40
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.deep_actor_critic.TD3   room_rl.algorithms.value.td.QLambda
    method), 21                  method), 43
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.actor_critic.deep_actor_critic.TRPO  room_rl.algorithms.value.td.QLearning
    method), 25                  method), 42
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.agent.Agent      room_rl.algorithms.value.td.RLearning
    method), 6                   method), 48
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.policy_search.black_box_optimization.RGDE_rl.algorithms.value.td.RQLearning
    method), 35                  method), 51
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.policy_search.black_box_optimization.REDS_rl.algorithms.value.td.SARSA   method),
    method), 36                  38
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.policy_search.black_box_optimization.RWRL_rl.algorithms.value.td.SARSALambda
    method), 33                  method), 39
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.policy_search.policy_gradient.GPOMDRoom_rl.algorithms.value.td.SARSAContinuous
    method), 30                  method), 53
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.policy_search.policy_gradient.REINFORGE_rl.algorithms.value.td.SpeedyQLearning
    method), 28                  method), 46
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.policy_search.policy_gradient.eNAC   room_rl.algorithms.value.td.TrueOnlineSARSALambda
    method), 31                  method), 54
__add_save_attr()           (mush- __add_save_attr()           (mush-
    room_rl.algorithms.value.batch_td.DoubleFQI            room_rl.algorithms.value.td.WeightedQLearning

```

```

        method), 49
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.approximators.parametric.linear.LinearApproximatb28
        method), 69
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.approximators.parametric.torch_approximator.TorchApproximator
        method), 72
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.approximators.regressor.Regressor
        method), 67
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.core.serialization.Serializable
        method), 10
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.distributions.distribution.Distribution
        method), 74
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.distributions.gaussian.GaussianCholeskyDistributionmethod), 133
        method), 80
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.distributions.gaussian.GaussianDiagonalDistributionmethod), 147
        method), 78
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.distributions.gaussian.GaussianDistribution
        method), 76
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.policy.deterministic_policy.DeterministicPolicy
        method), 113
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.policy.gaussian_policy.AbstractGaussianPolicy
        method), 115
__add_save_attr()           (mush- _add_save_attr()          (mush-
    room_rl.policy.gaussian_policy.DiagonalGaussianPolicy
        method), 119
__add_save_attr()           (mush- _add_save_attr()          (mushroom_rl.utils.table.Table
    room_rl.policy.gaussian_policy.GaussianPolicy
        method), 117
__add_save_attr()           (mush- _append_folder()          (mush-
    room_rl.policy.gaussian_policy.StateLogStdGaussianPolicy
        method), 123
__add_save_attr()           (mush- _append_folder()          (mush-
    room_rl.policy.gaussian_policy.StateStdGaussianPolicy
        method), 121
__add_save_attr()           (mush- _bound()          (mushroom_rl.environments.atari.Atari
    room_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy
        method), 125
__add_save_attr()           (mush- _bound()          (mushroom_rl.environments.cart_pole.CartPole
    room_rl.policy.policy.ParametricPolicy
        method), 112
__add_save_attr()           (mush- _bound()          (mushroom_rl.environments.dm_control_env.DMControl
    room_rl.policy.policy.Policy method), 110
__add_save_attr()           (mush- _bound()          (mushroom_rl.environments.environment.Environment
    room_rl.policy.td_policy.Boltzmann
        method), 130
__add_save_attr()           (mush- _bound()          (mushroom_rl.environments.finite_mdp.FiniteMDP
        method), 86
__add_save_attr()           (mush- _bound()          (mushroom_rl.environments.grid_world.AbstractGridWorld
        method), 86

```

```

    static method), 87
_bound() (mushroom_rl.environments.grid_world.GridWorld
    static method), 88
_bound() (mushroom_rl.environments.grid_world.GridWorldVanHasselt
    static method), 89
_bound() (mushroom_rl.environments.gym_env.Gym
    static method), 90
_bound() (mushroom_rl.environments.inverted_pendulum.InvertedPendulum
    static method), 92
_bound() (mushroom_rl.environments.lqr.LQR
    static method), 94
_bound() (mushroom_rl.environments.mujoco.MuJoCo
    static method), 98
_bound() (mushroom_rl.environments.puddle_world.PuddleWorld
    static method), 99
_bound() (mushroom_rl.environments.segway.Segway
    static method), 100
_bound() (mushroom_rl.environments.ship_steering.ShipSteering
    static method), 101
_check_collision() (mush-
    room_rl.environments.mujoco.MuJoCo
    method), 97
_compute() (mushroom_rl.utils.parameters.ExponentialParameter
    static method), 153
_compute() (mushroom_rl.utils.parameters.LinearParameter
    static method), 152
_compute() (mushroom_rl.utils.parameters.Parameter
    static method), 152
_compute() (mushroom_rl.utils.variance_parameters.VarianceDecreasingParameter
    static method), 165
_compute() (mushroom_rl.utils.variance_parameters.VarianceIncreasingParameter
    static method), 164
_compute() (mushroom_rl.utils.variance_parameters.VarianceParameter
    static method), 163
_compute() (mushroom_rl.utils.variance_parameters.WindowedVariance
    static method), 167
_compute() (mushroom_rl.utils.variance_parameters.WindowedVarianceParameter
    static method), 166
_compute_action() (mush-
    room_rl.environments.mujoco.MuJoCo
    method), 96
_compute_exponents() (mush-
    room_rl.features.basis.polynomial.PolynomialBasis
    static method), 108
_compute_gradient() (mush-
    room_rl.algorithms.policy_search.policy_gradient.GPOMDP
    static method), 29
_compute_gradient() (mush-
    room_rl.algorithms.policy_search.policy_gradient.REINFORCE
    static method), 28
_compute_gradient() (mush-
    room_rl.algorithms.policy_search.policy_gradient.eNAC
    static method), 31
_episode_end_update() (mush-
    room_rl.algorithms.policy_search.policy_gradient.GPOMDP
    static method), 30
    _episode_end_update()
        (mush-
            room_rl.algorithms.policy_search.policy_gradient.REINFORCE
            static method), 28
    _episode_end_update()
        (mush-
            room_rl.algorithms.policy_search.policy_gradient.eNAC
            static method), 31
    _fit() (mushroom_rl.algorithms.value.batch_td.DoubleFQI
        static method), 57
    _fit() (mushroom_rl.algorithms.value.batch_td.FQI
        static method), 56
    _fit_boosted()
        (mush-
            room_rl.algorithms.value.batch_td.DoubleFQI
            static method), 57
    _fit_boosted()
        (mush-
            room_rl.algorithms.value.batch_td.FQI
            static method), 56
    _get_collision_force()
        (mush-
            room_rl.environments.mujoco.MuJoCo
            method), 97
    _get_serialization_method()
        (mush-
            room_rl.utils.eligibility_trace.AccumulatingTrace
            static method), 148
    _get_serialization_method()
        (mush-
            room_rl.utils.eligibility_trace.ReplacingTrace
            static method), 146
    _init_update()
        (mush-
            room_rl.algorithms.policy_search.policy_gradient.GPOMDP
            static method), 30
    _init_update()
        (mush-
            room_rl.algorithms.policy_search.policy_gradient.REINFORCE
            static method), 28
    _init_update()
        (mush-
            room_rl.environments.mujoco.MuJoCo
            method), 98
    _load_json()
        (mush-
            room_rl.utils.eligibility_trace.AccumulatingTrace
            static method), 148
    _load_json()
        (mush-
            room_rl.utils.eligibility_trace.ReplacingTrace
            static method), 146
    _load_json()
        (mush-
            room_rl.utils.eligibility_trace.AccumulatingTrace
            static method), 148
    _load_json()
        (mush-
            room_rl.utils.eligibility_trace.ReplacingTrace
            static method), 146
    _load_json()
        (mush-
            room_rl.utils.eligibility_trace.AccumulatingTrace
            static method), 148
    _load_json()
        (mush-
            room_rl.utils.eligibility_trace.ReplacingTrace
            static method), 146
    _load_mushroom()
        (mush-
            room_rl.utils.eligibility_trace.AccumulatingTrace
            static method), 148

```

_load_mushroom() (mushroom_rl.utils.eligibility_trace.ReplacingTrace static method), 146

_load_numpy() (mushroom_rl.utils.eligibility_trace.AccumulatingTrace static method), 148

_load_numpy() (mushroom_rl.utils.eligibility_trace.ReplacingTrace static method), 146

_load_pickle() (mushroom_rl.utils.eligibility_trace.AccumulatingTrace static method), 148

_load_pickle() (mushroom_rl.utils.eligibility_trace.ReplacingTrace static method), 146

_load_simulation() (mushroom_rl.environments.mujoco.MuJoCo method), 98

_load_torch() (mushroom_rl.utils.eligibility_trace.AccumulatingTrace static method), 148

_load_torch() (mushroom_rl.utils.eligibility_trace.ReplacingTrace static method), 146

_next_q() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG method), 39

_next_q() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC method), 53

_next_q() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3 method), 47

_next_q() (mushroom_rl.algorithms.value.dqn.AveragedDQN method), 54

_next_q() (mushroom_rl.algorithms.value.dqn.CategoricalDQN method), 50

_next_q() (mushroom_rl.algorithms.value.dqn.DQN method), 60

_next_q() (mushroom_rl.algorithms.value.dqn.DoubleDQN method), 61

_next_q() (mushroom_rl.algorithms.value.td.RQLearning method), 52

_next_q() (mushroom_rl.algorithms.value.td.WeightedQLearning method), 49

_optimize_actor_parameters() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C method), 17

_optimize_actor_parameters() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG method), 19

_optimize_actor_parameters() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC method), 15

_optimize_actor_parameters() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC method), 23

_optimize_actor_parameters() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3 method), 21

_parse() (mushroom_rl.algorithms.policy_search.policy_gradient.GPOM method), 30

_parse() (mushroom_rl.algorithms.policy_search.policy_gradient.REINFORCE method), 28

_parse() (mushroom_rl.algorithms.policy_search.policy_gradient.eNAC method), 32

_parse() (mushroom_rl.algorithms.value.td.DoubleQLearning static method), 45

_parse() (mushroom_rl.algorithms.value.td.ExpectedSARSA static method), 41

_parse() (mushroom_rl.algorithms.value.td.QLambda static method), 44

_parse() (mushroom_rl.algorithms.value.td.QLearning static method), 42

_parse() (mushroom_rl.algorithms.value.td.RLearning static method), 48

_parse() (mushroom_rl.algorithms.value.td.RQLearning static method), 51

_parse() (mushroom_rl.algorithms.value.td.SARSA static method), 38

_parse() (mushroom_rl.algorithms.value.td.SARSALambda static method), 39

_parse() (mushroom_rl.algorithms.value.td.SARSAContinuous static method), 53

_parse() (mushroom_rl.algorithms.value.td.SpeedyQLearning static method), 47

_parse() (mushroom_rl.algorithms.value.td.TrueOnlineSARSA static method), 54

_post_load() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPDAC_Q method), 11

_post_load() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.StochasticAC method), 13

_post_load() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.StochasticAC method), 14

_post_load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C method), 17

_post_load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG method), 19

_post_load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC method), 16

_post_load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPO method), 26

```

__post_load()                               (mush-      room_rl.algorithms.value.td.ExpectedSARSA
    room_rl.algorithms.actor_critic.deep_actor_critic.SAC   method), 41
    method), 24                                         __post_load()                               (mush-
                                                    room_rl.algorithms.value.td.QLambda
                                                    method), 44
__post_load()                               (mush-      room_rl.algorithms.value.td.QLearning
    room_rl.algorithms.actor_critic.deep_actor_critic.TD3   method), 42
    method), 21                                         __post_load()                               (mush-
                                                    room_rl.algorithms.value.td.QLearning
                                                    method), 48
__post_load()                               (mush-      room_rl.algorithms.value.td.RLearning
    room_rl.algorithms.actor_critic.deep_actor_critic.TRPO  method), 48
    method), 25                                         __post_load()                               (mush-
                                                    room_rl.algorithms.value.td.RLearning
                                                    method), 51
__post_load() (mushroom_rl.algorithms.agent.Agent   __post_load()                               (mush-
    method), 6                                         room_rl.algorithms.value.td.RQLearning
                                                    method), 51
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.policy_search.black_box_optimization.PGDE_rl.algorithms.value.td.RQLearning
    method), 35                                         method), 51
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.policy_search.black_box_optimization.REPS_rl.algorithms.value.td.SARSA
    method), 36                                         method), 38
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.policy_search.black_box_optimization.RWRL_rl.algorithms.value.td.SARSA
    method), 33                                         method), 39
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.policy_search.policy_gradient.GPOMDRoom_rl.algorithms.value.td.SARSA
    method), 30                                         LambdaContinuous
                                                    method), 53
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.policy_search.policy_gradient.REINFORCERl.algorithms.value.td.SpeedyQLearning
    method), 28                                         method), 47
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.policy_search.policy_gradient.eNAC   room_rl.algorithms.value.td.TrueOnlineSARSA
    method), 32                                         Lambda
                                                    method), 54
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.batch_td.DoubleFQI   room_rl.algorithms.value.td.WeightedQLearning
    method), 57                                         method), 50
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.batch_td.FQI    room_rl.approximators.parametric.linear.LinearApproximator
    method), 56                                         method), 69
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.batch_td.LSPI   room_rl.approximators.parametric.torch_approximator.TorchApp
    method), 58                                         method), 72
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.dqn.AveragedDQN   room_rl.approximators.regressor.Regressor
    method), 63                                         method), 68
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.dqn.CategoricalDQN   room_rl.core.serialization.Serializable
    method), 65                                         method), 10
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.dqn.DQN    room_rl.distributions.distribution.Distribution
    method), 60                                         method), 74
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.dqn.DoubleDQN   room_rl.distributions.gaussian.GaussianCholeskyDistribution
    method), 62                                         method), 80
__post_load()                               (mush-      __post_load()                               (mush-
    room_rl.algorithms.value.td.DoubleQLearning   room_rl.distributions.gaussian.GaussianDiagonalDistribution
    method), 45                                         method), 78
__post_load()                               (mush-      __post_load()                               (mush-
                                                    room_rl.distributions.gaussian.GaussianDiagonalDistribution
                                                    method), 78

```

```

    room_rl.distributions.gaussian.GaussianDistribution      method), 146
    method), 76                                         _post_load()          (mush-
__post_load()                                (mush-   room_rl.utils.replay_memory.PrioritizedReplayMemory
    room_rl.policy.deterministic_policy.DeterministicPolicy   method), 157
    method), 114                                         _post_load()          (mush-
__post_load()                                (mush-   room_rl.utils.replay_memory.ReplayMemory
    room_rl.policy.gaussian_policy.AbstractGaussianPolicy   method), 154
    method), 115                                         _post_load()          (mush-
__post_load()                                (mush-   room_rl.utils.table.EnsembleTable   method),
    room_rl.policy.gaussian_policy.DiagonalGaussianPolicy  160
    method), 119                                         _post_load()          (mushroom_rl.utils.table.Table
__post_load()                                (mush-   method), 159
    room_rl.policy.gaussian_policy.GaussianPolicy   _preprocess()        (mushroom_rl.core.core.Core
    method), 117                                         method), 9
__post_load()                                (mush-   _preprocess_action()       (mush-
    room_rl.policy.gaussian_policy.StateLogStdGaussianPolicy room_rl.environments.mujoco.MuJoCo
    method), 123                                         method), 96
__post_load()                                (mush-   _read_data()           (mush-
    room_rl.policy.gaussian_policy.StateStdGaussianPolicy  room_rl.environments.mujoco.MuJoCo
    method), 121                                         method), 97
__post_load()                                (mush-   _reward()             (mush-
    room_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy   method), 97
    method), 125                                         _save_json()          (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.AccumulatingTrace
    room_rl.policy.policy.ParametricPolicy   static method), 148
    method), 112                                         _save_json()          (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.ReplacingTrace
    mushroom_rl.policy.policy.Policy   static method), 146
    method), 110                                         _save_mushroom()       (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.AccumulatingTrace
    room_rl.policy.td_policy.Boltzmann   method), 148
    130                                         _save_mushroom()       (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.ReplacingTrace
    room_rl.policy.td_policy.EpsGreedy  method), 146
    128                                         _save_numpy()          (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.AccumulatingTrace
    room_rl.policy.td_policy.Mellowmax  method), 148
    131                                         _save_numpy()          (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.ReplacingTrace
    room_rl.policy.td_policy.TDPolicy   method), 146
    127                                         _save_pickle()         (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.AccumulatingTrace
    room_rl.policy.torch_policy.BoltzmannTorchPolicy   static method), 148
    method), 138                                         _save_pickle()         (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.ReplacingTrace
    room_rl.policy.torch_policy.GaussianTorchPolicy   static method), 146
    method), 135                                         _save_torch()          (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.AccumulatingTrace
    room_rl.policy.torch_policy.TorchPolicy   static method), 148
    method), 134                                         _save_torch()          (mush-
__post_load()                                (mush-   room_rl.utils.eligibility_trace.ReplacingTrace
    room_rl.utils.eligibility_trace.AccumulatingTrace   static method), 146
    method), 148                                         _setup()              (mushroom_rl.environments.mujoco.MuJoCo
__post_load()                                (mush-   method), 98
    room_rl.utils.eligibility_traceReplacingTrace

```

```

__simulation_post_step()           (mush-      method), 30
    room_rl.environments.mujoco.MuJoCo
        method), 97
__simulation_pre_step()           (mush-      _update_parameters()
    room_rl.environments.mujoco.MuJoCo
        method), 96
__step() (mushroom_rl.core.Core method), 9
__step_finalize()                 (mush-      (mush-
    room_rl.environments.mujoco.MuJoCo
        method), 97
__step_init()                     (mush-      _update_target()
    room_rl.environments.mujoco.MuJoCo
        method), 96
__step_update()                   (mush-      _update_target()
    room_rl.algorithms.policy_search.policy_gradient.GPOMDP
        method), 29
__step_update()                   (mush-      _update_target()
    room_rl.algorithms.policy_search.policy_gradient.REINFORCE
        method), 28
__step_update()                   (mush-      _update_target()
    room_rl.algorithms.policy_search.policy_gradient.eNAC
        method), 31
__step_update()                   (mush-      _update_target()
    room_rl.algorithms.policy_search.policy_gradient.REINFORCE
        method), 34
__step_update()                   (mush-      _update_target()
    room_rl.algorithms.policy_search.black_box_optimization.PGPE
        method), 36
__step_update()                   (mush-      _EPS in mushroom_
    room_rl.algorithms.policy_search.black_box_optimization.RPS
        method), 36
__step_update()                   (mush-      room_rl.algorithms.actor_critic.deep_actor_critic),
    room_rl.algorithms.policy_search.black_box_optimization.RWR
        method), 33
__update() (mushroom_rl.algorithms.policy_search.black_box_optimization.PGPE
    method), 34
A
__update() (mushroom_rl.algorithms.policy_search.black_box_optimization.RPS
    method), 36
__update() (mushroom_rl.algorithms.value.td.DoubleQLearning
    room_rl.policy.gaussian_policy), 115
    AbstractGaussianPolicy (class in mushroom_
        method), 45
    AbstractGridWorld (class in mushroom_
        method), 40
    AccumulatingTrace (class in mushroom_
        method), 43
    AdaptiveParameter (class in mushroom_
        method), 42
    room_rl.utils.eligibility_trace), 147
    room_rl.utils.parameters), 153
    add() (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory
        method), 156
__update() (mushroom_rl.algorithms.value.td.RLearning
    room_rl.utils.replay_memory.ReplayMemory
        method), 48
    add() (mushroom_rl.utils.replay_memory.ReplayMemory
        method), 51
    add() (mushroom_rl.utils.replay_memory.SumTree
        method), 37
    Agent (class in mushroom_rl.algorithms.agent), 6
__update() (mushroom_rl.algorithms.value.td.SARSALambda
    room_rl.utils.dataset() (in module mushroom_
        method), 39
    room_rl.utils.dataset), 144
__update() (mushroom_rl.algorithms.value.td.SARSALambdaContinuous()
    room_rl.utils.viewer.Viewer
        method), 52
    add() (mushroom_rl.utils.replay_memory.SumTree
        method), 169
__update() (mushroom_rl.algorithms.value.td.SpeedyQLearning
    class in mushroom_rl.environments.atari), 83
        method), 46
    AverageDQN (class in mushroom_
        method), 54
__update() (mushroom_rl.algorithms.value.td.TrueOnlineSARSALambda
    room_rl.algorithms.value.dqn), 63
    room_rl.algorithms.value.dqn), 169
__update() (mushroom_rl.algorithms.value.td.WeightedQBarnard
    room_rl.algorithms.policy_search.policy_gradient.GPOMDP
        method), 49
    background_image() (mush-
        room_rl.utils.viewer.Viewer method), 169
__update_parameters()             (mush-
    room_rl.algorithms.policy_search.policy_gradient.GPOMDP
        method), 97

```

bfs() (in module `mushroom_rl.solvers.car_on_hill`), 139
`Boltzmann` (class in `mushroom_rl.policy.td_policy`), 129
`BoltzmannTorchPolicy` (class in `mushroom_rl.policy.torch_policy`), 136
`Box` (class in `mushroom_rl.utils.spaces`), 157

C

`Callback` (class in `mushroom_rl.utils.callbacks`), 142
`CarOnHill` (class in `mushroom_rl.environments.car_on_hill`), 84
`CartPole` (class in `mushroom_rl.environments.cart_pole`), 92
`CategoricalDQN` (class in `mushroom_rl.algorithms.value.dqn`), 65
`circle()` (`mushroom_rl.utils.viewer`.Viewer method), 169
`clean()` (`mushroom_rl.utils.callbacks.Callback` method), 143
`close()` (`mushroom_rl.environments.atari`.*MaxAndSkip* method), 82
`close()` (`mushroom_rl.utils.viewer`.Viewer method), 170
`CollectDataset` (class in `mushroom_rl.utils.callbacks`), 143
`CollectMaxQ` (class in `mushroom_rl.utils.callbacks`), 143
`CollectParameters` (class in `mushroom_rl.utils.callbacks`), 143
`CollectQ` (class in `mushroom_rl.utils.callbacks`), 143
`compute_advantage()` (in module `mushroom_rl.utils.value_functions`), 162
`compute_advantage_montecarlo()` (in module `mushroom_rl.utils.value_functions`), 162
`compute_gae()` (in module `mushroom_rl.utils.value_functions`), 162
`compute_J()` (in module `mushroom_rl.utils.dataset`), 145
`compute_lqr_feedback_gain()` (in module `mushroom_rl.solvers.lqr`), 140
`compute_lqr_P()` (in module `mushroom_rl.solvers.lqr`), 140
`compute_lqr_Q()` (in module `mushroom_rl.solvers.lqr`), 141
`compute_lqr_Q_gaussian_policy()` (in module `mushroom_rl.solvers.lqr`), 141
`compute_lqr_Q_gaussian_policy_gradient_K()` (in module `mushroom_rl.solvers.lqr`), 141
`compute_lqr_V()` (in module `mushroom_rl.solvers.lqr`), 140
`compute_lqr_V_gaussian_policy()` (in module `mushroom_rl.solvers.lqr`), 140
`compute_lqr_V_gaussian_policy_gradient_K()` (in module `mushroom_rl.solvers.lqr`), 141
`compute_mu()` (in module `mushroom_rl.environments.generators.grid_world`), 103
`compute_mu()` (in module `mushroom_rl.environments.generators.taxis`), 105
`compute_probabilities()` (in module `mushroom_rl.environments.generators.grid_world`), 102
`compute_probabilities()` (in module `mushroom_rl.environments.generators.simple_chain`), 103
`compute_probabilities()` (in module `mushroom_rl.environments.generators.taxis`), 104
`compute_reward()` (in module `mushroom_rl.environments.generators.grid_world`), 102
`compute_reward()` (in module `mushroom_rl.environments.generators.simple_chain`), 103
`compute_reward()` (in module `mushroom_rl.environments.generators.taxis`), 104
`COPDAC_Q` (class in `mushroom_rl.algorithms.actor_critic.classic_actor_critic`), 11
`copy()` (`mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPDAC` method), 11
`copy()` (`mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic` method), 13
`copy()` (`mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic` method), 14
`copy()` (`mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C` method), 17
`copy()` (`mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG` method), 19
`copy()` (`mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC` method), 16
`copy()` (`mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPO` method), 26
`copy()` (`mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC` method), 23
`copy()` (`mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3` method), 21
`copy()` (`mushroom_rl.algorithms.actor_critic.deep_actor_critic.TRPO` method), 25
`copy()` (`mushroom_rl.algorithms.agent.Agent` method), 6
`copy()` (`mushroom_rl.algorithms.policy_search.black_box_optimization`.*method*), 35
`copy()` (`mushroom_rl.algorithms.policy_search.black_box_optimization`.*method*), 36

```
copy () (mushroom_rl.algorithms.policy_search.black_box_optimizations.RWM_distributions.distribution.Distribution
         method), 33
copy () (mushroom_rl.algorithms.policy_search.policy_gradient.eNAUGaussian_distributions.gaussian.GaussianCholeskyDistribution
         method), 80
copy () (mushroom_rl.algorithms.policy_search.policy_gradient.GROMD_distributions.gaussian.GaussianDiagonalDistribution
         method), 78
copy () (mushroom_rl.algorithms.policy_search.policy_gradient.REINFORCE_distributions.gaussian.GaussianDistribution
         method), 76
copy () (mushroom_rl.algorithms.value.batch_td.DoubleFQI_distributions.gaussian.GaussianPolicy
         method), 57
copy () (mushroom_rl.algorithms.value.batch_td.FQI_distributions.gaussian.GaussianPolicy
         method), 56
copy () (mushroom_rl.algorithms.value.batch_td.LSPI_distributions.gaussian.GaussianPolicy
         method), 58
copy () (mushroom_rl.algorithms.value.dqn.AveragedDQN_distributions.gaussian.GaussianPolicy
         method), 64
copy () (mushroom_rl.algorithms.value.dqn.CategoricalDQN_distributions.gaussian.GaussianPolicy
         method), 65
copy () (mushroom_rl.algorithms.value.dqn.DoubleDQN_distributions.gaussian.GaussianPolicy
         method), 62
copy () (mushroom_rl.algorithms.value.dqn.DQN_distributions.gaussian.GaussianPolicy
         method), 60
copy () (mushroom_rl.algorithms.value.td.DoubleQLearning_distributions.gaussian.GaussianPolicy
         method), 45
copy () (mushroom_rl.algorithms.value.td.ExpectedSARSA_distributions.gaussian.GaussianPolicy
         method), 41
copy () (mushroom_rl.algorithms.value.td.QLambda_distributions.gaussian.GaussianPolicy
         method), 44
copy () (mushroom_rl.algorithms.value.td.QLearning_distributions.gaussian.GaussianPolicy
         method), 42
copy () (mushroom_rl.algorithms.value.td.RLearning_distributions.gaussian.GaussianPolicy
         method), 48
copy () (mushroom_rl.algorithms.value.td.RQLearning_distributions.gaussian.GaussianPolicy
         method), 51
copy () (mushroom_rl.algorithms.value.td.SARSA_distributions.gaussian.GaussianPolicy
         method), 38
copy () (mushroom_rl.algorithms.value.td.SARSALambda_distributions.gaussian.GaussianPolicy
         method), 39
copy () (mushroom_rl.algorithms.value.td.SARSALambdaContinuum_distributions.gaussian.GaussianPolicy
         method), 53
copy () (mushroom_rl.algorithms.value.td.SpeedyQLearning_distributions.gaussian.GaussianPolicy
         method), 47
copy () (mushroom_rl.algorithms.value.td.TrueOnlineSARSALambda_distributions.gaussian.GaussianPolicy
         method), 54
copy () (mushroom_rl.algorithms.value.td.WeightedQLearning_distributions.gaussian.GaussianPolicy
         method), 50
copy () (mushroom_rl.approximators.parametric.linear.LinearApproximator_distributions.gaussian.GaussianPolicy
         method), 69
copy () (mushroom_rl.approximators.parametric.torch_Approximator_distributions.gaussian.GaussianPolicy
         method), 72
copy () (mushroom_rl.approximators.regressor.RegressorCore_distributions.gaussian.GaussianPolicy
         method), 68
copy () (mushroom_rl.core.serialization.Serializable_distributions.gaussian.GaussianPolicy
         method), 10
```

```

    room_rl.algorithms.actor_critic.deep_actor_critic),           method), 117
    18                               diff_log() (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy
DeepAC      (class      in      mush-      method), 123
    room_rl.algorithms.actor_critic.deep_actor_critic), diff_log() (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy
    15                               method), 121
DeterministicPolicy  (class      in      mush-      diff_log() (mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy
    room_rl.policy.deterministic_policy), 113               method), 126
DiagonalGaussianPolicy (class      in      mush-      diff_log() (mushroom_rl.policy.policy.ParametricPolicy
    room_rl.policy.gaussian_policy), 118               method), 111
diff() (mushroom_rl.approximators.parametric.linear.LinearApproximator in mushroom_rl.utils.spaces), 158
    method), 69                               display() (mushroom_rl.utils.viewer.ImageViewer
diff() (mushroom_rl.approximators.parametric.torch_Approximator in mushroom_rl.utils.viewer.TorchApproximator
    method), 72                               display() (mushroom_rl.utils.viewer.Viewer method),
diff() (mushroom_rl.approximators.regressor.Regressor      170
    method), 67                               Distribution (class      in      mush-
diff() (mushroom_rl.distributions.distribution.Distribution      room_rl.distributions.distribution), 73
    method), 73                               distribution() (mush-
diff() (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution in mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy
    method), 80                               method), 138
diff() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution () (mush-
    method), 78                               room_rl.policy.torch_policy.GaussianTorchPolicy
diff() (mushroom_rl.distributions.gaussian.GaussianDistribution method), 135
    method), 76                               distribution() (mush-
diff() (mushroom_rl.policy.deterministic_policy.DeterministicPolicy in mushroom_rl.policy.torch_policy.TorchPolicy
    method), 114                               method), 132
diff() (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy in mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy
    method), 115
diff() (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy in mushroom_rl.policy.torch_policy.TorchPolicy
    method), 119                               method), 137
diff() (mushroom_rl.policy.gaussian_policy.GaussianPolicy      room_rl.policy.torch_policy.GaussianTorchPolicy
    method), 118                               method), 135
diff() (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy in mushroom_rl.policy.torch_policy.TorchPolicy
    method), 123                               method), 132
diff() (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy in mushroom_rl.policy.torch_policy.TorchPolicy
    method), 121                               DMControl (class      in      mush-
diff() (mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy in mushroom_rl.environments.dm_control_env),
    method), 125                               85
diff() (mushroom_rl.policy.policy.ParametricPolicy DoubleDQN (class      in      mush-
    method), 111                               room_rl.algorithms.value.dqn), 61
diff_log() (mushroom_rl.distributions.distribution.Distribution in mushroom_rl.algorithms.value.batch_td), 57
    method), 73                               draw_action() (mush-
diff_log() (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution (class      in      mush-
    method), 80                               room_rl.algorithms.value.td), 44
diff_log() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution in mushroom_rl.algorithms.value.dqn), 59
    method), 78                               draw_action() (mush-
diff_log() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution in mushroom_rl.algorithms.value.dqn), 59
    method), 75                               draw_action() (mush-
diff_log() (mushroom_rl.policy.deterministic_policy.DeterministicPolicy) (mush-
    method), 114                               room_rl.algorithms.actor_critic.classic_actor_critic.COPDAC_Q
diff_log() (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy), 13
    method), 115                               draw_action() (mush-
diff_log() (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy in mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPDAC_Q
    method), 119                               method), 14
diff_log() (mushroom_rl.policy.gaussian_policy.GaussianPolicy) (mush-
    method), 115                               draw_action() (mush-

```

<code>room_rl.algorithms.actor_critic.deep_actor_critic.A2C method), 17</code>	<code>(mush- room_rl.algorithms.value.dqn.CategoricalDQN method), 65</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.actor_critic.deep_actor_critic.DDPG method), 19</code>	<code>room_rl.algorithms.value.dqn.DoubleDQN method), 62</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.actor_critic.deep_actor_critic.DeepAC method), 16</code>	<code>room_rl.algorithms.value.dqn.DQN method), 60</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.actor_critic.deep_actor_critic.PPO method), 27</code>	<code>room_rl.algorithms.value.td.DoubleQLearning method), 45</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.actor_critic.deep_actor_critic.SAC method), 23</code>	<code>room_rl.algorithms.value.td.ExpectedSARSA method), 41</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.actor_critic.deep_actor_critic.TD3 method), 21</code>	<code>room_rl.algorithms.value.td.QLambda method), 44</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.actor_critic.deep_actor_critic.TRPO method), 25</code>	<code>room_rl.algorithms.value.td.QLearning method), 42</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.agent.Agent 6</code>	<code>room_rl.algorithms.value.td.RLearning method), 48</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.policy_search.black_box_optimization.PGDE method), 35</code>	<code>room_rl.algorithms.value.td.RQLearning method), 51</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.policy_search.black_box_optimization.REPS method), 36</code>	<code>room_rl.algorithms.value.td.SARSA method), 38</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.policy_search.black_box_optimization.RWRL method), 33</code>	<code>room_rl.algorithms.value.td.SARSALambda method), 39</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.policy_search.policy_gradient.eNAC method), 32</code>	<code>room_rl.algorithms.value.td.SARSAContinuous method), 53</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.policy_search.policy_gradient.GPOMD method), 30</code>	<code>room_rl.algorithms.value.td.SpeedyQLearning method), 47</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.policy_search.policy_gradient.REINFORGE method), 28</code>	<code>room_rl.algorithms.value.td.TrueOnlineSARSALambda method), 54</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.value.batch_td.DoubleFQI method), 57</code>	<code>room_rl.algorithms.value.td.WeightedQLearning method), 50</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.value.batch_td.FQI method), 56</code>	<code>room_rl.policy.deterministic_policy.DeterministicPolicy method), 113</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.value.batch_td.LSPI method), 59</code>	<code>room_rl.policy.gaussian_policy.AbstractGaussianPolicy method), 115</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>
<code>room_rl.algorithms.value.dqn.AveragedDQN method), 64</code>	<code>room_rl.policy.gaussian_policy.DiagonalGaussianPolicy method), 120</code>
<code>draw_action()</code>	<code>(mush- draw_action() (mush-</code>

`room_rl.policy.gaussian_policy.GaussianPolicy` `EnsembleTable` (class in `mushroom_rl.utils.table`),
`method`, 118
`draw_action()` (mush-
`room_rl.policy.gaussian_policy.StateLogStdGaussianPolicy``method`), 73
`method`, 124
`draw_action()` (mush-
`room_rl.policy.gaussian_policy.StateStdGaussianPolicy``method`), 79
`method`, 122
`draw_action()` (mush-
`room_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy``method`), 75
`method`, 125
`draw_action()` (mush-
`room_rl.policy.policy.ParametricPolicy``method`), 138
`method`, 112
`draw_action()` (mush-
`room_rl.policy.policy.Policy``method`), 132
`method`, 110
`draw_action()` (mush-
`room_rl.policy.td_policy.Boltzmann``method`),
`129`
`draw_action()` (mush-
`room_rl.policy.td_policy.EpsGreedy``method`),
`128`
`draw_action()` (mush-
`room_rl.policy.td_policy.Mellowmax``method`),
`131`
`draw_action()` (mush-
`room_rl.policy.td_policy.TDPolicy``method`),
`127`
`draw_action()` (mush-
`room_rl.policy.torch_policy.BoltzmannTorchPolicy``method`),
`138`
`draw_action()` (mush-
`room_rl.policy.torch_policy.GaussianTorchPolicy``method`),
`136`
`draw_action()` (mush-
`room_rl.policy.torch_policy.TorchPolicy``method`),
`132`
`draw_action_t()` (mush-
`room_rl.policy.torch_policy.BoltzmannTorchPolicy``method`),
`137`
`draw_action_t()` (mush-
`room_rl.policy.torch_policy.GaussianTorchPolicy``method`),
`134`
`draw_action_t()` (mush-
`room_rl.policy.torch_policy.TorchPolicy``method`),
`133`
E
`EligibilityTrace()` (in module `room_rl.utils.eligibility_trace`), 145
`eNAC` (class in `room_rl.algorithms.policy_search.policy_gradient`),
`31`
`entropy()` (mush-
`room_rl.distributions.distribution.Distribution`
`method`), 160
`entropy()` (mush-
`room_rl.distributions.gaussian.GaussianCholeskyDistr`
`method`), 77
`entropy()` (mush-
`room_rl.distributions.gaussian.GaussianDiagonalDistr`
`method`), 79
`entropy()` (mush-
`room_rl.distributions.gaussian.GaussianDistribution`
`method`), 75
`entropy()` (mush-
`room_rl.policy.torch_policy.BoltzmannTorchPolicy`
`method`), 136
`entropy()` (mush-
`room_rl.policy.torch_policy.GaussianTorchPolicy`
`method`), 132
`entropy_t()` (mush-
`room_rl.policy.torch_policy.BoltzmannTorchPolicy`
`method`), 137
`entropy_t()` (mush-
`room_rl.policy.torch_policy.GaussianTorchPolicy`
`method`), 135
`entropy_t()` (mush-
`room_rl.policy.torch_policy.TorchPolicy`
`method`), 133
`Environment` (class in `room_rl.environments.environment`), 7
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.classic_actor_critic.COPDAC_Q`
`method`), 12
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.classic_actor_critic.StochasticAC`
`method`), 13
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.classic_actor_critic.StochasticAC`
`method`), 14
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.deep_actor_critic.A2C`
`method`), 17
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.deep_actor_critic.DDPG`
`method`), 19
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.deep_actor_critic.DeepAC`
`method`), 16
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.deep_actor_critic.PPO`
`method`), 27
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.deep_actor_critic.SAC`
`method`), 23
`episode_start()` (mush-
`room_rl.algorithms.actor_critic.deep_actor_critic.TD3`
`method`), 21

episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.actor_critic.deep_actor_critic.TRPO	room_rl.algorithms.value.td.QLearning	room_rl.algorithms.value.td.QLearning)	
method), 25	method), 42	method), 42		
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.agent.Agent	method),	room_rl.algorithms.value.td.RLearning)	
6	method),	method), 48		
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.policy_search.black_box_optimization.PGPIE	room_rl.algorithms.value.td.RQLearning	room_rl.algorithms.value.td.RQLearning)	
method), 35	method), 51	method), 51		
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.policy_search.black_box_optimization.REPS	room_rl.algorithms.value.td.SARSA	room_rl.algorithms.value.td.SARSA)	
method), 36	method), 38	method), 38		
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.policy_search.black_box_optimization.RWRL	room_rl.algorithms.value.td.SARSA	room_rl.algorithms.value.td.SARSA)	
method), 33	method), 39	method), 39		
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.policy_search.policy_gradient.eNAC	room_rl.algorithms.value.td.SARSA	room_rl.algorithms.value.td.SARSA)	
method), 32	method), 53	method), 53		
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.policy_search.policy_gradient.GPOMD	room_rl.algorithms.value.td.SpeedyQ	room_rl.algorithms.value.td.SpeedyQ)	
method), 30	Learning	Learning)	
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.policy_search.policy_gradient.REINFORGE	room_rl.algorithms.value.td.TrueOnlineSARSA	room_rl.algorithms.value.td.TrueOnlineSARSA)	
method), 28	Lambda	Lambda)	
episode_start()	(mush-	episode_start()	(mush-	
room_rl.algorithms.value.batch_td.DoubleFQI	room_rl.algorithms.value.td.WeightedQ	room_rl.algorithms.value.td.WeightedQ)	
method), 57	Learning	Learning)	
episode_start()	(mush-	episodes_length()	(in module mush-	
room_rl.algorithms.value.batch_td.FQI	room_rl.utils.dataset),	room_rl.utils.dataset),		
method), 56	144	144		
episode_start()	(mush-	EpsGreedy	(class in mushroom_rl.policy.td_policy),	
room_rl.algorithms.value.batch_td.LSPI	127	127		
method), 59				
episode_start()	(mush-	euler_to_quat()	(in module mush-	
room_rl.algorithms.value.dqn.AveragedDQN	room_rl.utils.angles),	room_rl.utils.angles),		
method), 64	142	142		
episode_start()	(mush-	evaluate()	(mushroom_rl.core.core.Core method), 9	
room_rl.algorithms.value.dqn.CategoricalDQN				
method), 65	ExpectedSARSA	(class in mushroom_rl.algorithms.value.td), 40		
episode_start()	(mush-	ExponentialParameter	(class in mushroom_rl.utils.parameters), 152	
room_rl.algorithms.value.dqn.DoubleDQN				
method), 62				
episode_start()	(mush-	F		
room_rl.algorithms.value.dqn.DQN				
method), 60	Features()	(in module room_rl.features.features), 105		
episode_start()	(mush-	FiniteMDP	(class in room_rl.environmentsFINITE_MDP), 86	
room_rl.algorithms.value.td.DoubleQLearning	method),	method),		
method), 45	fit()	(mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPDA		
episode_start()	(mush-	method), 11	method), 11	
room_rl.algorithms.value.td.ExpectedSARSA		fit()	(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic	
method), 41		method), 13	method), 13	
episode_start()	(mush-	fit()	(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic	
room_rl.algorithms.value.td.QLambda	method),	method), 14	method), 14	
method), 43	fit()	(mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C)	
		method), 17	method), 17	
		fit()	(mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG	
		method), 19	method), 19	

```

fit() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAChod), 53
    method), 15
fit() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPOmethod), 47
    method), 26
fit() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC method), 55
    method), 23
fit() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3 method), 50
    method), 21
fit() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TRPOmethod), 69
    method), 25
fit() (mushroom_rl.algorithms.agent.Agent method), 6
    method), 71
fit() (mushroom_rl.algorithms.policy_search.black_box_optimization.PGPErl.approximators.regressor.Regressor
    method), 35
fit() (mushroom_rl.algorithms.policy_search.black_box_optimization.REDDrl.utils.eligibility_trace.AccumulatingTrace
    method), 36
fit() (mushroom_rl.algorithms.policy_search.black_box_optimization.RWDRl.utils.eligibility_trace.ReplacingTrace
    method), 33
fit() (mushroom_rl.algorithms.policy_search.policy_gradient.eNAC (mushroom_rl.utils.table.EnsembleTable
    method), 32
method), 160
fit() (mushroom_rl.algorithms.policy_search.policy_gradient.GPOMDProom_rl.utils.table.Table method), 158
    method), 30
force_arrow() (mushroom_rl.utils.viewer.Viewer
method), 169
fit() (mushroom_rl.algorithms.policy_search.policy_gradient.REINFORCE, 169
    method), 29
force_symlink() (in module mushroom_
method), 149
fit() (mushroom_rl.algorithms.value.batch_td.DoubleFQI room_rl.utils.folder), 149
    method), 57
FourierBasis (class in mushroom_
method), 106
FQI (class in mushroom_rl.algorithms.value.batch_td),
    55
function() (mushroom_rl.utils.viewer.Viewer
method), 170
fit() (mushroom_rl.algorithms.value.dqn.AveragedDQN
    method), 64
fit() (mushroom_rl.algorithms.value.dqn.CategoricalDQN
    method), 65
G
fit() (mushroom_rl.algorithms.value.dqn.DoubleDQN
    method), 62
fit() (mushroom_rl.algorithms.value.dqn.DQN
    method), 60
fit() (mushroom_rl.algorithms.value.td.DoubleQLearning
    method), 45
fit() (mushroom_rl.algorithms.value.td.ExpectedSARSA
    method), 41
fit() (mushroom_rl.algorithms.value.td.QLambda
    method), 44
fit() (mushroom_rl.algorithms.value.td.QLearning
    method), 42
fit() (mushroom_rl.algorithms.value.td.RLearning
    method), 48
fit() (mushroom_rl.algorithms.value.td.RQLearning
    method), 51
fit() (mushroom_rl.algorithms.value.td.SARSA
    method), 38
fit() (mushroom_rl.algorithms.value.td.SARSALambda
    method), 39
fit() (mushroom_rl.algorithms.value.td.SARSALambdaContinuous
    method), 107
fit() (mushroom_rl.algorithms.value.td.SpeedyQLearning
    method), 47
fit() (mushroom_rl.algorithms.value.td.TrueOnlineSARSALambda
    method), 55
fit() (mushroom_rl.algorithms.value.td.WeightedQLearning
    method), 69
fit() (mushroom_rl.approximators.parametric.linear.LinearApproximator
    method), 107
fit() (mushroom_rl.approximators.parametric.torch_approximator.Torch
    method), 71
fit() (mushroom_rl.algorithms.policy_search.black_box_optimization.PGPErl.approximators.regressor.Regressor
    method), 67
fit() (mushroom_rl.algorithms.policy_search.black_box_optimization.REDDrl.utils.eligibility_trace.AccumulatingTrace
    method), 148
fit() (mushroom_rl.algorithms.policy_search.black_box_optimization.RWDRl.utils.eligibility_trace.ReplacingTrace
    method), 146
fit() (mushroom_rl.algorithms.policy_search.policy_gradient.eNAC (mushroom_rl.utils.table.EnsembleTable
    method), 160
method), 158
force_arrow() (mushroom_rl.utils.viewer.Viewer
method), 169
force_symlink() (in module mushroom_
method), 149
FourierBasis (class in mushroom_
method), 106
FQI (class in mushroom_rl.algorithms.value.batch_td),
    55
function() (mushroom_rl.utils.viewer.Viewer
method), 170
GaussianCholeskyDistribution (class in mushroom_
    room_rl.distributions.gaussian), 79
GaussianDiagonalDistribution (class in mushroom_
    room_rl.distributions.gaussian), 77
GaussianDistribution (class in mushroom_
    room_rl.distributions.gaussian), 75
GaussianPolicy (class in mushroom_
    room_rl.policy.gaussian_policy), 116
GaussianRBF (class in mushroom_
    room_rl.features.basis.gaussian_rbf), 107
GaussianRBFTensor (class in mushroom_
    room_rl.features.tensors.gaussian_tensor),
    108
GaussianTorchPolicy (class in mushroom_
    room_rl.policy.torch_policy), 134
generate() (mushroom_rl.environments.lqr.LQR
    static method), 94
generate() (mushroom_rl.features.basis.fourier.FourierBasis
    static method), 106
generate() (mushroom_rl.features.basis.gaussian_rbf.GaussianRBF
    static method), 107

```

```

generate() (mushroom_rl.features.basis.polynomial.PolynomialBasisMethod), 152
    static method), 108                                         get_value() (mush-
generate() (mushroom_rl.features.tensors.gaussian_tensor:GaussianTensorParameter method),
    static method), 109                                         151
generate() (mushroom_rl.features.tiles.tiles.Tiles get_value() (mush-
    static method), 109                                         room_rl.utils.variance_parameters.VarianceDecreasingParamete
generate_grid_world() (in module mushroom_rl.environments.generators.grid_world), 151
    102                                         get_value() (mush-
generate_simple_chain() (in module mushroom_rl.environments.generators.simple_chain), 165
    103                                         room_rl.utils.variance_parameters.VarianceIncreasingParameter
get_value() (mushroom_rl.environments.generators.taxi), 164
    104                                         get_value() (mush-
get() (mushroom_rl.utils.callbacks.Callback method), 163
    143                                         room_rl.utils.variance_parameters.VarianceParameter
get() (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory get_value() (mush-
    method), 156                                         room_rl.utils.variance_parameters.WindowedVarianceParameter
get() (mushroom_rl.utils.replay_memory.ReplayMemory get_value() (mush-
    method), 154                                         room_rl.utils.variance_parameters.WindowedVarianceParameter
get() (mushroom_rl.utils.replay_memory.SumTree get_weights() (in module mushroom_rl.utils.torch),
    method), 155                                         161
get_action_features() (in module mushroom_rl.features.features), 106
    106                                         get_weights() (mush-
get_gradient() (in module mushroom_rl.utils.torch), 161
    161                                         room_rl.approximators.parametric.linear.LinearApproximator
get_parameters() (mush- get_weights() (mush-
    room_rl.distributions.distribution.Distribution method), 69
    method), 74                                         room_rl.approximators.parametric.torch_Approximator.TorchApp
get_parameters() (mush- get_weights() (mush-
    room_rl.distributions.gaussian.GaussianCholeskyDistribution weights() (mush-
    method), 80                                         room_rl.policy.deterministic_policy.DeterministicPolicy
get_parameters() (mush- get_weights() (mush-
    room_rl.distributions.gaussian.GaussianDiagonalDistribution weights() (mush-
    method), 78                                         room_rl.policy.gaussian_policy.AbstractGaussianPolicy
get_parameters() (mush- get_weights() (mush-
    room_rl.distributions.gaussian.GaussianDistribution weights() (mush-
    method), 76                                         room_rl.policy.gaussian_policy.DiagonalGaussianPolicy
get_q() (mushroom_rl.policy.td_policy.Boltzmann get_weights() (mush-
    method), 130                                         room_rl.policy.gaussian_policy.GaussianPolicy
get_q() (mushroom_rl.policy.td_policy.EpsGreedy get_weights() (mush-
    method), 128                                         room_rl.policy.gaussian_policy.GaussianPolicy
get_q() (mushroom_rl.policy.td_policy.Mellowmax get_weights() (mush-
    method), 131                                         room_rl.policy.gaussian_policy.StateLogStdGaussianPolicy
get_q() (mushroom_rl.policy.td_policy.TDPolicy get_weights() (mush-
    method), 126                                         room_rl.policy.gaussian_policy.StateStdGaussianPolicy
get_regressor() (mush- get_weights() (mush-
    room_rl.policy.deterministic_policy.DeterministicPolicy method), 121
    method), 113                                         room_rl.policy.gaussian_policy.StateStdGaussianPolicy
get_value() (mush- get_weights() (mush-
    room_rl.utils.parameters.ExponentialParameter method), 153                                         room_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy
get_value() (mush- get_weights() (mush-
    room_rl.utils.parameters.LinearParameter method), 153                                         room_rl.policy.policy.ParametricPolicy
    method), 111

```

get_weights() (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy method), 137

get_weights() (mushroom_rl.policy.torch_policy.GaussianTorchPolicy method), 135

get_weights() (mushroom_rl.policy.torch_policy.TorchPolicy method), 133

GPOMDP (class in mushroom_rl.algorithms.policy_search.policy_gradient), 29

GridWorld (class in mushroom_rl.environments.grid_world), 88

GridWorldVanHasselt (class in mushroom_rl.environments.grid_world), 89

Gym (class in mushroom_rl.environments.gym_env), 90

H

high (mushroom_rl.utils.spaces.Box attribute), 158

I

ImageViewer (class in mushroom_rl.utils.viewer), 167

info (mushroom_rl.environments.atari.Atari attribute), 83

info (mushroom_rl.environments.car_on_hill.CarOnHill attribute), 84

info (mushroom_rl.environments.cart_pole.CartPole attribute), 93

info (mushroom_rl.environments.dmc_control_env.DMControl attribute), 86

info (mushroom_rl.environments.environment.Environment attribute), 8

info (mushroom_rl.environments.finite_mdp.FiniteMDP attribute), 87

info (mushroom_rl.environments.grid_world.AbstractGridWorld attribute), 88

info (mushroom_rl.environments.grid_world.GridWorld attribute), 88

info (mushroom_rl.environments.grid_world.GridWorldVanHasselt attribute), 89

info (mushroom_rl.environments.gym_env.Gym attribute), 91

info (mushroom_rl.environments.inverted_pendulum.InvertedPendulum attribute), 92

info (mushroom_rl.environments.lqr.LQR attribute), 95

info (mushroom_rl.environments.mujoco.MuJoCo attribute), 98

info (mushroom_rl.environments.puddle_world.PuddleWorld attribute), 99

info (mushroom_rl.environments.segway.Segway attribute), 100

info (mushroom_rl.environments.ship_steering.ShipSteering attribute), 101

(mushroom_rl.initialized attribute), 156

(mushroom_rl.utils.replay_memory.PrioritizedReplayMemory attribute), 154

(mushroom_rl.initialized attribute), 154

(mushroom_rl.input_shape attribute), 67

InvertedPendulum (class in mushroom_rl.environments.inverted_pendulum), 91

L

LazyFrames (class in mushroom_rl.utils.frames), 150

learn() (mushroom_rl.core.core.Core method), 9

line() (mushroom_rl.utils.viewer.Viewer method), 168

LinearApproximator (class in mushroom_rl.approximators.parametric.linear), 68

LinearParameter (class in mushroom_rl.utils.parameters), 152

load() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPD class method), 12

load() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic class method), 13

load() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic class method), 14

load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C class method), 17

load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG class method), 19

load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC class method), 16

load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPO class method), 27

load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC class method), 23

load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3 class method), 21

load() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TRPO class method), 25

load() (mushroom_rl.algorithms.agent.Agent class method), 6

load() (mushroom_rl.algorithms.policy_search.black_box_optimization.I class method), 35

load() (mushroom_rl.algorithms.policy_search.black_box_optimization.I class method), 37

load() (mushroom_rl.algorithms.policy_search.black_box_optimization.I class method), 34

load() (mushroom_rl.algorithms.policy_search.black_box_optimization.I class method), 32

load() (mushroom_rl.algorithms.policy_search.policy_gradient.eNAC class method), 32

load() (mushroom_rl.algorithms.policy_search.policy_gradient.GPOMD class method), 30

```

load() (mushroom_rl.algorithms.policy_search.policy_gradient.REINFORCE) REINFORCE_rl.distributions.gaussian.GaussianDistribution
       class method), 29                                         class method), 76
load() (mushroom_rl.algorithms.value.batch_td.DoubleFQI) load() (mushroom_rl.policy.deterministic_policy.DeterministicPolicy
       class method), 58                                         class method), 114
load() (mushroom_rl.algorithms.value.batch_td.FQI)   load() (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy
       class method), 56                                         class method), 116
load() (mushroom_rl.algorithms.value.batch_td.LSPI)  load() (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy
       class method), 59                                         class method), 120
load() (mushroom_rl.algorithms.value.dqn.AveragedDQN) load() (mushroom_rl.policy.gaussian_policy.GaussianPolicy
       class method), 64                                         class method), 118
load() (mushroom_rl.algorithms.value.dqn.CategoricalDQN) load() (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy
       class method), 65                                         class method), 124
load() (mushroom_rl.algorithms.value.dqn.DoubleDQN)  load() (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy
       class method), 62                                         class method), 122
load() (mushroom_rl.algorithms.value.dqn.DQN class   load() (mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy
       method), 61                                         class method), 126
load() (mushroom_rl.algorithms.value.td.DoubleQLearning) load() (mushroom_rl.policy.policy.ParametricPolicy
       class method), 45                                         class method), 112
load() (mushroom_rl.algorithms.value.td.ExpectedSARSA) load() (mushroom_rl.policy.policy.Policy      class
       class method), 41                                         method), 110
load() (mushroom_rl.algorithms.value.td.QLambda)    load() (mushroom_rl.policy.td_policy.Boltzmann class
       class method), 44                                         method), 130
load() (mushroom_rl.algorithms.value.td.QLearning)  load() (mushroom_rl.policy.td_policy.EpsGreedy class
       class method), 43                                         method), 128
load() (mushroom_rl.algorithms.value.td.RLearning)  load() (mushroom_rl.policy.td_policy.Mellowmax
       class method), 48                                         class method), 131
load() (mushroom_rl.algorithms.value.td.RQLearning) load() (mushroom_rl.policy.td_policy.TDPolicy  class
       class method), 52                                         method), 127
load() (mushroom_rl.algorithms.value.td.SARSA class  load() (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy
       method), 38                                         class method), 138
load() (mushroom_rl.algorithms.value.td.SARSALambda) load() (mushroom_rl.policy.torch_policy.GaussianTorchPolicy
       class method), 40                                         class method), 136
load() (mushroom_rl.algorithms.value.td.SARSALambdaCorruption) (mushroom_rl.policy.torch_policy.TorchPolicy
       class method), 53                                         class method), 134
load() (mushroom_rl.algorithms.value.td.SpeedyQLearning) load() (mushroom_rl.utils.eligibility_trace.AccumulatingTrace
       class method), 47                                         class method), 148
load() (mushroom_rl.algorithms.value.td.TrueOnlineSARSA)  load() (mushroom_rl.utils.eligibility_trace.ReplacingTrace
       class method), 55                                         class method), 146
load() (mushroom_rl.algorithms.value.td.WeightedQLearning) load() (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory
       class method), 50                                         class method), 157
load() (mushroom_rl.approximators.parametric.linear.LinearApproximator) (mushroom_rl.utils.replay_memory.ReplayMemory
       class method), 70                                         class method), 154
load() (mushroom_rl.approximators.parametric.torch_ApproximatorToTorchApproximatableTable) EnsembleTable  class
       class method), 72                                         method), 160
load() (mushroom_rl.approximators.regressorRegressor) load() (mushroom_rl.utils.table.Table  class method),
       class method), 68                                         159
load() (mushroom_rl.core.serialization.Serializable)  load_zip() (mushroom_rl.utils.eligibility_trace.AccumulatingTrace
       class method), 10                                         class method), 148
load() (mushroom_rl.distributions.distribution.Distribution) load_zip() (mushroom_rl.utils.eligibility_trace.ReplacingTrace
       class method), 74                                         class method), 146
load() (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution) (mushroom_rl.distributions.distribution.Distribution
       class method), 80                                         method), 73
load() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution) (mushroom_rl.distributions.gaussian.GaussianCholeskyDistr
       class method), 78                                         method), 79

```

```
log_pdf() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution.algorithms.agent (module), 6
           method), 77
           mushroom_rl.algorithms.policy_search.black_box_optimizers (module), 33
log_pdf() (mushroom_rl.distributions.gaussian.GaussianDistributions.algorithms.agent (module), 6
           method), 75
           mushroom_rl.algorithms.policy_search.policy_gradient.algorithms.agent (module), 27
           mushroom_rl.algorithms.value.batch_td.algorithms.agent (module), 55
log_prob_t() (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy.algorithms.value.dqn (module), 59
              method), 137
              mushroom_rl.algorithms.value.td (module), 37
log_prob_t() (mushroom_rl.policy.torch_policy.GaussianTorchPolicy.algorithms.value.dqn (module), 59
              method), 135
              mushroom_rl.algorithms.value.td (module), 37
log_prob_t() (mushroom_rl.policy.torch_policy.TorchPolicy.algorithms.value.dqn (module), 68
              method), 133
              mushroom_rl.approximators.parametric.linear (module), 68
low (mushroom_rl.utils.spaces.Box attribute), 158
LQR (class in mushroom_rl.environments.lqr), 93
LSPI (class in mushroom_rl.algorithms.value.batch_td), 58

M
max_p (mushroom_rl.utils.replay_memory.SumTree attribute), 155
max_priority (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory attribute), 156
MaxAndSkip (class in mushroom_rl.environments.atari), 81
MDPInfo (class in mushroom_rl.environments.environment), 7
Mellowmax (class in mushroom_rl.policy.td_policy), 130
minibatch_generator() (in module mushroom_rl.utils.minibatches), 150
minibatch_number() (in module mushroom_rl.utils.minibatches), 150
mk_dir_recursive() (in module mushroom_rl.utils.folder), 149
mle() (mushroom_rl.distributions.distribution.Distribution method), 73
mle() (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution method), 79
mle() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution method), 77
mle() (mushroom_rl.distributions.gaussian.GaussianDistribution method), 75
model (mushroom_rl.approximators.regressor.Regressor attribute), 67
model (mushroom_rl.utils.table.EnsembleTable attribute), 160
MuJoCo (class in mushroom_rl.environments.mujoco), 95
mushroom_rl.algorithms.actor_critic.classic_actor (module), 11
mushroom_rl.algorithms.actor_critic.deep_actor (module), 15
mushroom_rl.algorithms.actor_critic.classic_actor.critic (module), 95
mushroom_rl.algorithms.actor_critic.deep_actor.critic (module), 98
mushroom_rl.algorithms.actor_critic.classic_actor.critic.algorithms.value.puddle_world (module), 98
mushroom_rl.algorithms.actor_critic.deep_actor.critic.algorithms.value.puddle_world (module), 98
mushroom_rl.core.core (module), 8
mushroom_rl.core.serialization (module), 10
mushroom_rl.distributions.distribution (module), 73
mushroom_rl.environments.atari (module), 81
mushroom_rl.environments.car_on_hill (module), 84
mushroom_rl.environments.cart_pole (module), 92
mushroom_rl.environments.dm_control_env (module), 85
mushroom_rl.environments.environment (module), 7
mushroom_rl.environments.finite_mdp (module), 86
mushroom_rl.environments.grid_world (module), 102
mushroom_rl.environments.grid_world (module), 103
mushroom_rl.environments.grid_world (module), 104
mushroom_rl.environments.grid_world (module), 87
mushroom_rl.environments.gym_env (module), 90
mushroom_rl.environments.inverted_pendulum (module), 91
mushroom_rl.environments.lqr (module), 93
mushroom_rl.environments.mujoco (module), 93
mushroom_rl.environments.puddle_world (module), 98
mushroom_rl.environments.segway (module), 98
```

100
mushroom_rl.environments.ship_steering
 (*module*), 100
mushroom_rl.features._implementations.features.~~implementation~~
 (*module*), 106
mushroom_rl.features.basis.fourier (*mod-
ule*), 106
mushroom_rl.features.basis.gaussian_rbf
 (*module*), 107
mushroom_rl.features.basis.polynomial
 (*module*), 108
mushroom_rl.features.features (*module*),
 105
mushroom_rl.features.tensors.gaussian_ten-
 sor~~s~~
 (*module*), 108
mushroom_rl.features.tiles.tiles (*mod-
ule*), 109
mushroom_rl.policy.deterministic_policy
 (*module*), 113
mushroom_rl.policy.gaussian_policy (*mod-
ule*), 115
mushroom_rl.policy.noise_policy (*module*),
 124
mushroom_rl.policy.policy (*module*), 110
mushroom_rl.policy.td_policy (*module*), 126
mushroom_rl.policy.torch_policy (*module*),
 132
mushroom_rl.solvers.car_on_hill (*module*),
 139
mushroom_rl.solvers.dynamic_programming
 (*module*), 139
mushroom_rl.solvers.lqr (*module*), 140
mushroom_rl.utils.angles (*module*), 142
mushroom_rl.utils.callbacks (*module*), 142
mushroom_rl.utils.dataset (*module*), 144
mushroom_rl.utils.eligibility_trace
 (*module*), 145
mushroom_rl.utils.features (*module*), 149
mushroom_rl.utils.folder (*module*), 149
mushroom_rl.utils.frames (*module*), 150
mushroom_rl.utils.minibatches (*module*),
 150
mushroom_rl.utils.numerical_gradient
 (*module*), 150
mushroom_rl.utils.parameters (*module*), 151
mushroom_rl.utils.replay_memory (*module*),
 154
mushroom_rl.utils.spaces (*module*), 157
mushroom_rl.utils.table (*module*), 158
mushroom_rl.utils.torch (*module*), 161
mushroom_rl.utils.value_functions (*mod-
ule*), 162
mushroom_rl.utils.variance_parameters
 (*module*), 163

mushroom_rl.utils.viewer (*module*), 167

N

~~features~~
mushroom_rl.utils.eligibility_trace.AccumulatingTrace
 attribute), 148
n_actions (*mushroom_rl.utils.eligibility_trace.ReplacingTrace*
 attribute), 146
n_actions (*mushroom_rl.utils.table.Table* attribute),
 159
normalize_angle () (in *module* mush-
 room_rl.utils.angles), 142
normalize_angle_positive () (in *module* mush-
 room_rl.utils.angles), 142
numerical_diff_dist () (in *module* mush-
 room_rl.utils.numerical_gradient), 151
numerical_diff_function () (in *module* mush-
 room_rl.utils.numerical_gradient), 151
numerical_diff_policy () (in *module* mush-
 room_rl.utils.numerical_gradient), 150

O

ObservationType (class in *mush-
 room_rl.environments.mujoco*), 95
OrnsteinUhlenbeckPolicy (class in *mush-
 room_rl.policy.noise_policy*), 124
output_shape (mush-
 room_rl.approximators.regressor.Regressor
 attribute), 67

P

Parameter (class in *mushroom_rl.utils.parameters*),
 151
parameters () (mush-
 room_rl.policy.torch_policy.BoltzmannTorchPolicy
 method), 137
parameters () (mush-
 room_rl.policy.torch_policy.GaussianTorchPolicy
 method), 135
parameters () (mush-
 room_rl.policy.torch_policy.TorchPolicy
 method), 133
parameters_size (mush-
 room_rl.distributions.distribution.Distribution
 attribute), 74
parameters_size (mush-
 room_rl.distributions.gaussian.GaussianCholeskyDistribution
 attribute), 80
parameters_size (mush-
 room_rl.distributions.gaussian.GaussianDiagonalDistribution
 attribute), 78
parameters_size (mush-
 room_rl.distributions.gaussian.GaussianDistribution
 attribute), 76

ParametricPolicy (class in `mushroom_rl.policy.policy`), 111
`parse_dataset()` (in module `mushroom_rl.utils.dataset`), 144
`parse_grid()` (in module `mushroom_rl.environments.generators.grid_world`), 102
`parse_grid()` (in module `mushroom_rl.environments.generators.taxis`), 104
`PGPE` (class in `mushroom_rl.algorithms.policy_search.black_box_optimization`), 34
`Policy` (class in `mushroom_rl.policy.policy`), 110
`policy_iteration()` (in module `mushroom_rl.solvers.dynamic_programming`), 139
`polygon()` (`mushroom_rl.utils.viewer.Viewer` method), 168
`PolynomialBasis` (class in `mushroom_rl.features.basis.polynomial`), 108
`PPO` (class in `mushroom_rl.algorithms.actor_critic.deep_actor_critic`), 26
`predict()` (`mushroom_rl.approximators.parametric.linear.LinearApproximator` method), 69
`predict()` (`mushroom_rl.approximators.parametric.torch_Approximator` method), 71
`predict()` (`mushroom_rl.approximators.regressor.Regressor` method), 67
`predict()` (`mushroom_rl.approximators.parametric.linear.LinearApproximator` method), 86
`predict()` (`mushroom_rl.utils.eligibility_trace.AccumulatingTrace` method), 148
`predict()` (`mushroom_rl.utils.eligibility_traceReplacingTrace` method), 146
`predict()` (`mushroom_rl.utils.table.EnsembleTable` method), 160
`predict()` (`mushroom_rl.utils.table.Table` method), 159
`preprocess_frame()` (in module `mushroom_rl.utils.frames`), 150
`PrioritizedReplayMemory` (class in `mushroom_rl.utils.replay_memory`), 156
`PuddleWorld` (class in `mushroom_rl.environments.puddle_world`), 98

Q

`QLambda` (class in `mushroom_rl.algorithms.value.td`), 43
`QLearning` (class in `mushroom_rl.algorithms.value.td`), 42
`quat_to_euler()` (in module `mushroom_rl.utils.angles`), 142

R

`Regressor` (class in `mushroom_rl.approximators.regressor`), 66
`REINFORCE` (class in `mushroom_rl.algorithms.policy_search.policy_gradient`), 27
`render()` (`mushroom_rl.environments.atari.MaxAndSkip` method), 82
`ReplacingTrace` (class in `mushroom_rl.utils.eligibility_trace`), 145
`ReplayMemory` (class in `mushroom_rl.utils.replay_memory`), 154
`REINFORCE` (class in `mushroom_rl.algorithms.policy_search.black_box_optimization`), 36
`reset()` (`mushroom_rl.approximators.regressor.Regressor` method), 67
`reset()` (`mushroom_rl.core.core.Core` method), 9
`reset()` (`mushroom_rl.environments.atari.Atari` method), 83
`reset()` (`mushroom_rl.environments.atari.MaxAndSkip` method), 82
`reset()` (`mushroom_rl.environments.car_on_hill.CarOnHill` method), 84
`reset()` (`mushroom_rl.environments.cart_pole.CartPole` method), 85
`reset()` (`mushroom_rl.environments.dmc_control_env.DMControl` method), 85
`reset()` (`mushroom_rl.environments.environment.Environment` method), 8
`reset()` (`mushroom_rl.environments.finite_mdp.FiniteMDP` method), 86
`reset()` (`mushroom_rl.environments.grid_world.AbstractGridWorld` method), 87
`reset()` (`mushroom_rl.environments.grid_world.GridWorld` method), 88
`reset()` (`mushroom_rl.environments.grid_world.GridWorldVanHasselt` method), 89
`reset()` (`mushroom_rl.environments.gym_env.Gym` method), 90
`reset()` (`mushroom_rl.environments.inverted_pendulum.InvertedPendulum` method), 91
`reset()` (`mushroom_rl.environments.lqr.LQR` method), 94
`reset()` (`mushroom_rl.environments.mujoco.MuJoCo` method), 96
`reset()` (`mushroom_rl.environments.puddle_world.PuddleWorld` method), 99
`reset()` (`mushroom_rl.environments.segway.Segway` method), 100
`reset()` (`mushroom_rl.environments.ship_steering.ShipSteering` method), 101
`reset()` (`mushroom_rl.policy.deterministic_policy.DeterministicPolicy` method), 114
`reset()` (`mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy` method), 116

```

reset() (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy(mushroom_rl.distributions.gaussian.GaussianDistribution
    method), 120
        GaussianPolicy(mushroom_rl.distributions.gaussian.GaussianDistribution
            method), 75
reset() (mushroom_rl.policy.gaussian_policy.GaussianPolicy(mushroom_rl.algorithms.value.td), 37
    method), 118
        TD(mushroom_rl.algorithms.value.td), 37
        SARSALambda(mushroom_rl.algorithms.value.td), 39
        SARSALambdaContinuous(mushroom_rl.algorithms.value.td), 39
reset() (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy(mushroom_rl.algorithms.value.td), 39
    method), 124
        StateLogStdGaussianPolicy(mushroom_rl.algorithms.value.td), 39
reset() (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy(mushroom_rl.algorithms.value.td), 52
    method), 122
        save() (mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPD
            method), 122
reset() (mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPD
    method), 125
        OrnsteinUhlenbeckPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPD
            method), 125
reset() (mushroom_rl.policy.policy.ParametricPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
    method), 112
        ParametricPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
            method), 112
reset() (mushroom_rl.policy.policy.Policy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
    method), 110
        Policy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
            method), 110
reset() (mushroom_rl.policy.td_policy.BoltzmannPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
    method), 130
        BoltzmannPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
            method), 130
reset() (mushroom_rl.policy.td_policy.EpsGreedyPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
    method), 128
        EpsGreedyPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
            method), 128
reset() (mushroom_rl.policy.td_policy.MellowmaxPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
    method), 131
        MellowmaxPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
            method), 131
reset() (mushroom_rl.policy.td_policy.TDPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
    method), 127
        TDPolicy(mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stochastic
            method), 127
reset() (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy(mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C
    method), 138
        BoltzmannTorchPolicy(mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C
            method), 138
reset() (mushroom_rl.policy.torch_policy.GaussianTorchPolicy(mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG
    method), 136
        GaussianTorchPolicy(mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG
            method), 136
reset() (mushroom_rl.policy.torch_policy.TorchPolicy(mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC
    method), 133
        TorchPolicy(mushroom_rl.algorithms.actor_critic.deep_actor_critic.DeepAC
            method), 133
reset() (mushroom_rl.utils.eligibility_trace.AccumulatingTrace(mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPO
    method), 24
        AccumulatingTrace(mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPO
            method), 24
reset() (mushroom_rl.utils.eligibility_trace.ReplacingTrace(mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC
    method), 22
        ReplacingTrace(mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC
            method), 22
reset() (mushroom_rl.utils.replay_memory.ReplayMemory(mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC
    method), 147
        ReplayMemory(mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAC
            method), 147
reset() (mushroom_rl.utils.table.EnsembleTable(mushroom_rl.algorithms.policy_search.black_box_optimization.TD3
    method), 145
        EnsembleTable(mushroom_rl.algorithms.policy_search.black_box_optimization.TD3
            method), 145
reset() (mushroom_rl.utils.table.Table(mushroom_rl.algorithms.policy_search.black_box_optimization.TRPO
    method), 154
        Table(mushroom_rl.algorithms.policy_search.black_box_optimization.TRPO
            method), 154
reset() (mushroom_rl.utils.table.Table(mushroom_rl.algorithms.policy_search.black_box_optimization.eNAC
    method), 161
        Table(mushroom_rl.algorithms.policy_search.black_box_optimization.eNAC
            method), 161
RLearning(mushroom_rl.algorithms.value.td), 47
        RLearning(mushroom_rl.algorithms.value.td), 47
RQLearning(mushroom_rl.algorithms.value.td), 50
        RQLearning(mushroom_rl.algorithms.value.td), 50
RWR(mushroom_rl.algorithms.policy_search.black_box_optimization.eNAC), 33
        RWR(mushroom_rl.algorithms.policy_search.black_box_optimization.eNAC), 33
S
SAC(mushroom_rl.algorithms.actor_critic.deep_actor_critic), 22
        SAC(mushroom_rl.algorithms.actor_critic.deep_actor_critic), 22
sample() (mushroom_rl.distributions.distribution.Distribution(mushroom_rl.algorithms.value.batch_td.DoubleFQI
    method), 73
        Distribution(mushroom_rl.algorithms.value.batch_td.DoubleFQI
            method), 73
sample() (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution(mushroom_rl.algorithms.value.batch_td.LSPI
    method), 79
        GaussianCholeskyDistribution(mushroom_rl.algorithms.value.batch_td.LSPI
            method), 79
sample() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution(mushroom_rl.algorithms.value.dqn.AveragedDQN
    method), 77
        GaussianDiagonalDistribution(mushroom_rl.algorithms.value.dqn.AveragedDQN
            method), 77
        save() (mushroom_rl.algorithms.value.dqn.CategoricalDQN
            method), 64
        save() (mushroom_rl.algorithms.value.dqn.DoubleDQN
            method), 66
        save() (mushroom_rl.algorithms.value.dqn.DoubleDQN
            method), 62
        save() (mushroom_rl.algorithms.value.dqn.DQN
            method), 58
        save() (mushroom_rl.algorithms.value.dqn.DQN
            method), 56
        save() (mushroom_rl.algorithms.value.dqn.LSPI
            method), 59
        save() (mushroom_rl.algorithms.value.dqn.AveragedDQN
            method), 64
        save() (mushroom_rl.algorithms.value.dqn.CategoricalDQN
            method), 64
        save() (mushroom_rl.algorithms.value.dqn.DoubleDQN
            method), 66
        save() (mushroom_rl.algorithms.value.dqn.DoubleDQN
            method), 62
        save() (mushroom_rl.algorithms.value.dqn.DQN
            method), 58

```

```

        method), 61
    save () (mushroom_rl.algorithms.value.td.DoubleQLearning.save () (mushroom_rl.algorithms.value.td.DoubleQLearning
        method), 46
    save () (mushroom_rl.algorithms.value.td.ExpectedSARSA.save () (mushroom_rl.algorithms.value.td.ExpectedSARSA
        method), 41
    save () (mushroom_rl.algorithms.value.td.QLambda.save () (mushroom_rl.algorithms.value.td.QLambda
        method), 44
    save () (mushroom_rl.algorithms.value.td.QLearning.save () (mushroom_rl.algorithms.value.td.QLearning
        method), 43
    save () (mushroom_rl.algorithms.value.td.RLearning.save () (mushroom_rl.algorithms.value.td.RLearning
        method), 49
    save () (mushroom_rl.algorithms.value.td.RQLearning.save () (mushroom_rl.algorithms.value.td.RQLearning
        method), 52
    save () (mushroom_rl.algorithms.value.td.SARSA.save () (mushroom_rl.algorithms.value.td.SARSA
        method), 38
    save () (mushroom_rl.algorithms.value.td.SARSALambda.save () (mushroom_rl.algorithms.value.td.SARSALambda
        method), 40
    save () (mushroom_rl.algorithms.value.td.SARSALambdaContinuum.save () (mushroom_rl.algorithms.value.td.SARSALambdaContinuum
        method), 53
    save () (mushroom_rl.algorithms.value.td.SpeedyQLearning.save () (mushroom_rl.algorithms.value.td.SpeedyQLearning
        method), 47
    save () (mushroom_rl.algorithms.value.td.TrueOnlineSARSALambda.save () (mushroom_rl.algorithms.value.td.TrueOnlineSARSALambda
        method), 55
    save () (mushroom_rl.algorithms.value.td.WeightedQLearning.save () (mushroom_rl.algorithms.value.td.WeightedQLearning
        method), 50
    save () (mushroom_rl.approximators.parametric.linear.LinearApproximator.save () (mushroom_rl.approximators.parametric.linear.LinearApproximator
        method), 70
    save () (mushroom_rl.approximators.parametric.torch_Approximator.save () (mushroom_rl.approximators.parametric.torch_Approximator
        method), 72
    save () (mushroom_rl.approximators.regressor.Regressor.save () (mushroom_rl.approximators.regressor.Regressor
        method), 68
    save () (mushroom_rl.core.serialization.Serializable.save () (mushroom_rl.core.serialization.Serializable
        method), 10
    save () (mushroom_rl.distributions.distribution.Distribution.save () (mushroom_rl.distributions.distribution.Distribution
        method), 74
    save () (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution.save () (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution
        method), 81
    save () (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution.save () (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution
        method), 79
    save () (mushroom_rl.distributions.gaussian.GaussianDistribution.save () (mushroom_rl.distributions.gaussian.GaussianDistribution
        method), 76
    save () (mushroom_rl.policy.deterministic_policy.DeterministicPolicy.save () (mushroom_rl.policy.deterministic_policy.DeterministicPolicy
        method), 114
    save () (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy.save () (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy
        method), 116
    save () (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy.save () (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy
        method), 120
    save () (mushroom_rl.policy.gaussian_policy.GaussianPolicy.save () (mushroom_rl.policy.gaussian_policy.GaussianPolicy
        method), 118
    save () (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy.save () (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy
        method), 124
    save () (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy.save () (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy
        method), 122
    save () (mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy.save () (mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy
        method), 61
    save () (mushroom_rl.policy.policy.ParametricPolicy.save () (mushroom_rl.policy.policy.ParametricPolicy
        method), 112
    save () (mushroom_rl.policy.policy.Policy.save () (mushroom_rl.policy.policy.Policy
        method), 111
    save () (mushroom_rl.policy.td_policy.BoltzmannPolicy.save () (mushroom_rl.policy.td_policy.BoltzmannPolicy
        method), 130
    save () (mushroom_rl.policy.td_policy.EpsGreedyPolicy.save () (mushroom_rl.policy.td_policy.EpsGreedyPolicy
        method), 128
    save () (mushroom_rl.policy.td_policy.MellowmaxPolicy.save () (mushroom_rl.policy.td_policy.MellowmaxPolicy
        method), 132
    save () (mushroom_rl.policy.td_policy.TDPolicy.save () (mushroom_rl.policy.td_policy.TDPolicy
        method), 127
    save () (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy.save () (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy
        method), 138
    save () (mushroom_rl.policy.torch_policy.GaussianTorchPolicy.save () (mushroom_rl.policy.torch_policy.GaussianTorchPolicy
        method), 136
    save () (mushroom_rl.policy.torch_policy.TorchPolicy.save () (mushroom_rl.policy.torch_policy.TorchPolicy
        method), 134
    save () (mushroom_rl.utils.eligibility_trace.AccumulatingTrace.save () (mushroom_rl.utils.eligibility_trace.AccumulatingTrace
        method), 148
    save () (mushroom_rl.utils.eligibility_trace.ReplacingTrace.save () (mushroom_rl.utils.eligibility_trace.ReplacingTrace
        method), 149
    save () (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory.save () (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory
        method), 155
    save () (mushroom_rl.utils.table.EnsembleTable.save () (mushroom_rl.utils.table.EnsembleTable
        method), 157
    save () (mushroom_rl.utils.table.Table.save () (mushroom_rl.utils.table.Table
        method), 159
    save () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.ClassicActorCritic.save () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.ClassicActorCritic
        method), 12
    save () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.ClassicActorCritic.save () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.ClassicActorCritic
        method), 13
    save () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.ClassicActorCritic.save () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.ClassicActorCritic
        method), 15
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2CActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2CActorCritic
        method), 18
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2CActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2CActorCritic
        method), 20
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPGActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPGActorCritic
        method), 20
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPGActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPGActorCritic
        method), 26
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPGActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPGActorCritic
        method), 27
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SACActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SACActorCritic
        method), 24
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SACActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SACActorCritic
        method), 22
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3ActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3ActorCritic
        method), 22
    save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3ActorCritic.save () (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3ActorCritic
        method), 25
    save () (mushroom_rl.algorithms.agent.Agent.save () (mushroom_rl.algorithms.agent.Agent
        method), 7
    save () (mushroom_rl.algorithms.policy_search.black_box_optimizer.BlackBoxOptimizer.save () (mushroom_rl.algorithms.policy_search.black_box_optimizer.BlackBoxOptimizer
        method), 35
    save () (mushroom_rl.algorithms.policy_search.black_box_optimizer.BlackBoxOptimizer.save () (mushroom_rl.algorithms.policy_search.black_box_optimizer.BlackBoxOptimizer
        method), 35

```

method), 37
save_zip () (mushroom_rl.algorithms.policy_search.black_box_optimization.RWRL.distributions.distribution.Distribution method), 74
save_zip () (mushroom_rl.algorithms.policy_search.policy_gradient.GRADPOMDP.distributions.gaussian.GaussianCholeskyDistribution method), 81
save_zip () (mushroom_rl.algorithms.policy_search.policy_gradient.GRADPOMDP.distributions.gaussian.GaussianDiagonalDistribution method), 79
save_zip () (mushroom_rl.algorithms.policy_search.policy_gradient.REINFORCE.distributions.gaussian.GaussianDistribution method), 77
save_zip () (mushroom_rl.algorithms.value.batch_td.DoubleQTip () (mushroom_rl.policy.deterministic_policy.DeterministicPolicy method), 114
save_zip () (mushroom_rl.algorithms.value.batch_td.FQSave_zip () (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy method), 116
save_zip () (mushroom_rl.algorithms.value.batch_td.LSPLSave_zip () (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy method), 120
save_zip () (mushroom_rl.algorithms.value.dqn.AveragedDQN_save_zip () (mushroom_rl.policy.gaussian_policy.GaussianPolicy method), 118
save_zip () (mushroom_rl.algorithms.value.dqn.CategoricalDQNip () (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy method), 124
save_zip () (mushroom_rl.algorithms.value.dqn.DoubleDQN_ezip () (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy method), 122
save_zip () (mushroom_rl.algorithms.value.dqn.DQN save_zip () (mushroom_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy method), 126
save_zip () (mushroom_rl.algorithms.value.td.DoubleQLearning_ip () (mushroom_rl.policy.policy.ParametricPolicy method), 112
save_zip () (mushroom_rl.algorithms.value.td.ExpectedSARSA_save_zip () (mushroom_rl.policy.policy.Policy method), 111
save_zip () (mushroom_rl.algorithms.value.td.QLambdaSave_zip () (mushroom_rl.policy.td_policy.Boltzmann method), 130
save_zip () (mushroom_rl.algorithms.value.td.QLearningSave_zip () (mushroom_rl.policy.td_policy.EpsGreedy method), 129
save_zip () (mushroom_rl.algorithms.value.td.RLearningSave_zip () (mushroom_rl.policy.td_policy.Mellowmax method), 132
save_zip () (mushroom_rl.algorithms.value.td.RQLearningSave_zip () (mushroom_rl.policy.td_policy.TDPolicy method), 127
save_zip () (mushroom_rl.algorithms.value.td.SARSA_save_zip () (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy method), 138
save_zip () (mushroom_rl.algorithms.value.td.SARSALambdaSave_zip () (mushroom_rl.policy.torch_policy.GaussianTorchPolicy method), 136
save_zip () (mushroom_rl.algorithms.value.td.SARSALambdaCartPoleSave_zip () (mushroom_rl.policy.torch_policy.TorchPolicy method), 134
save_zip () (mushroom_rl.algorithms.value.td.SpeedyQLearning_ip () (mushroom_rl.utils.eligibility_trace.AccumulatingTrace method), 149
save_zip () (mushroom_rl.algorithms.value.td.TrueOnlineSARSAAlgorithmSave_zip () (mushroom_rl.utils.eligibility_trace.ReplacingTrace method), 147
save_zip () (mushroom_rl.algorithms.value.td.WeightedQLearninip () (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory method), 157
save_zip () (mushroom_rl.approximators.parametric.linear.LinearApproximator(mushroom_rl.utils.replay_memory.ReplayMemory method), 155
save_zip () (mushroom_rl.approximators.parametric.torch.Approximator(mushroom_rl.utils.table.EnsembleTable method), 161
save_zip () (mushroom_rl.approximators.regressor.Regressor_save_zip () (mushroom_rl.utils.table.Table method), 159
save_zip () (mushroom_rl.core.serialization.SerializableScreen (mushroom_rl.utils.viewer.Viewer attribute),

168
 seed() (mushroom_rl.environments.atari.Atari
 method), 84
 seed() (mushroom_rl.environments.atari.MaxAndSkip
 method), 82
 seed() (mushroom_rl.environments.car_on_hill.CarOnHill
 method), 84
 seed() (mushroom_rl.environments.cart_pole.CartPole
 method), 93
 seed() (mushroom_rl.environments.dm_control_env.DMControl
 method), 86
 seed() (mushroom_rl.environments.environment.Environment
 method), 8
 seed() (mushroom_rl.environments.finite_mdp.FiniteMDP
 method), 87
 seed() (mushroom_rl.environments.grid_world.AbstractGridWorld
 method), 88
 seed() (mushroom_rl.environments.grid_world.GridWorld
 method), 89
 seed() (mushroom_rl.environments.grid_world.GridWorld
 method), 89
 seed() (mushroom_rl.environments.gym_env.Gym
 method), 91
 seed() (mushroom_rl.environments.inverted_pendulum.InvertedPendulum
 method), 92
 seed() (mushroom_rl.environments.lqr.LQR
 method), 95
 seed() (mushroom_rl.environments.mujoco.MuJoCo
 method), 96
 seed() (mushroom_rl.environments.puddle_world.PuddleWorld
 method), 99
 seed() (mushroom_rl.environments.segway.Segway
 method), 100
 seed() (mushroom_rl.environments.ship_steering.ShipSteering
 method), 101
 Segway (class in mushroom_rl.environments.segway),
 100
 select_first_episodes() (in module
 mushroom_rl.utils.dataset), 144
 select_random_samples() (in module
 mushroom_rl.utils.dataset), 144
 Serializable (class in
 mushroom_rl.core.serialization), 10
 set_beta() (mushroom_rl.policy.td_policy.Boltzmann
 method), 129
 set_beta() (mushroom_rl.policy.td_policy.Mellowmax
 method), 131
 set_episode_end() (mushroom_rl.environments.atari.Atari
 method), 84
 set_epsilon() (mushroom_rl.policy.td_policy.EpsGreedy
 method), 128
 set_parameters() (mushroom_rl.environments.distribution.Distribution
 method), 74
 set_parameters() (mushroom_rl.distributions.gaussian.GaussianCholeskyDistribution
 method), 80
 set_parameters() (mushroom_rl.distributions.gaussian.GaussianDiagonalDistribution
 method), 78
 set_parameters() (mushroom_rl.distributions.gaussian.GaussianDistribution
 method), 76
 set_q() (mushroom_rl.policy.td_policy.Boltzmann
 method), 130
 set_q() (mushroom_rl.policy.td_policy.EpsGreedy
 method), 129
 set_q() (mushroom_rl.policy.td_policy.Mellowmax
 method), 132
 set_q() (mushroom_rl.policy.td_policy.TDPolicy
 method), 126
 set_weights() (mushroom_rl.policy.gaussian_policy.GaussianPolicy
 method), 117
 set_std() (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy
 method), 117
 set_weights() (in module
 mushroom_rl.utils.torch), 161
 set_weights() (mushroom_rl.approximators.parametric.linear.LinearApproximator
 method), 69
 set_weights() (mushroom_rl.approximators.parametric.torch_approximator.TorchApp
 method), 72
 set_weights() (mushroom_rl.policy.deterministic_policy.DeterministicPolicy
 method), 113
 set_weights() (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy
 method), 116
 set_weights() (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy
 method), 119
 set_weights() (mushroom_rl.policy.gaussian_policy.GaussianPolicy
 method), 117
 set_weights() (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy
 method), 123
 set_weights() (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy
 method), 121
 set_weights() (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy
 method), 121

```

room_rl.policy.noise_policy.OrnsteinUhlenbeckPolicy (class in mushroom-
method), 125
set_weights () (mush- square () (mushroom_rl.utils.viewer.Viewer method),
room_rl.policy.policy.ParametricPolicy (mushroom_rl.algorithms.value.td), 46
method), 111
set_weights () (mush- StateLogStdGaussianPolicy (class in mush-
room_rl.policy.torch_policy.BoltzmannTorchPolicy (mushroom_rl.algorithms.value.td), 46
method), 137 room_rl.policy.gaussian_policy), 122
set_weights () (mush- StateStdGaussianPolicy (class in mush-
room_rl.policy.torch_policy.GaussianTorchPolicy (mushroom_rl.algorithms.value.td), 46
method), 135 room_rl.policy.gaussian_policy), 120
set_weights () (mush- step () (in module mushroom_rl.solvers.car_on_hill),
room_rl.policy.torch_policy.TorchPolicy (mushroom_rl.environments.atari.Atari
method), 133 method), 83
shape (mushroom_rl.environments.environment.MDPInfo step () (mushroom_rl.environments.car_on_hill.CarOnHill
attribute), 7 method), 84
shape (mushroom_rl.utils.eligibility_trace.AccumulatingTrace step () (mushroom_rl.environments.cart_pole.CartPole
attribute), 149 method), 93
shape (mushroom_rl.utils.eligibility_traceReplacingTrace step () (mushroom_rl.environments.dmc_control_env.DMCControl
attribute), 147 method), 85
shape (mushroom_rl.utils.parameters.ExponentialParameter step () (mushroom_rl.environments.environment.Environment
attribute), 153 method), 8
shape (mushroom_rl.utils.parameters.LinearParameter step () (mushroom_rl.environments.finite_mdp.FiniteMDP
attribute), 152 method), 86
shape (mushroom_rl.utils.parameters.Parameter step () (mushroom_rl.environments.grid_world.AbstractGridWorld
attribute), 152 method), 87
shape (mushroom_rl.utils.spaces.Box attribute), 158 step () (mushroom_rl.environments.grid_world.GridWorld
shape (mushroom_rl.utils.spaces.Discrete attribute), 158 step () (mushroom_rl.environments.grid_world.GridWorldVanHasselt
method), 89
shape (mushroom_rl.utils.table.Table attribute), 159 step () (mushroom_rl.environments.grid_world.GridWorldVanHasselt
shape (mushroom_rl.utils.variance_parameters.VarianceD step () (mushroom_rl.environments.gym_env.Gym
attribute), 165 method), 90
shape (mushroom_rl.utils.variance_parameters.VarianceIn step () (mushroom_rl.environments.inverted_pendulum.InvertedPendulum
attribute), 164 method), 91
shape (mushroom_rl.utils.variance_parameters.VariancePar step () (mushroom_rl.environments.lqr.LQR method),
attribute), 164 94
shape (mushroom_rl.utils.variance_parameters.WindowedV step () (mushroom_rl.environments.mujoco.MuJoCo
attribute), 167 method), 96
shape (mushroom_rl.utils.variance_parameters.WindowedV step () (mushroom_rl.environments.puddle_world.PuddleWorld
attribute), 166 method), 99
ShipSteering (class in mushroom-
room_rl.environments.ship_steering), 100 step () (mushroom_rl.environments.segway.Segway
shortest_angular_distance () (in module mushroom_rl.utils.angles), 142 step () (mushroom_rl.environments.ship_steering.ShipSteering
method), 101
size (mushroom_rl.environments.environment.MDPInfo StochasticAC (class in mushroom-
attribute), 7 room_rl.algorithms.actor_critic.classic_actor_critic),
size (mushroom_rl.utils.replay_memory.ReplayMemory StochasticAC_AVG (class in mushroom-
attribute), 154 room_rl.algorithms.actor_critic.classic_actor_critic),
size (mushroom_rl.utils.replay_memory.SumTree attribute), 155 stop () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.COPD,
size (mushroom_rl.utils.spaces.Discrete attribute), 158 method), 12
size (mushroom_rl.utils.viewer.Viewer attribute), 168 stop () (mushroom_rl.algorithms.actor_critic.classic_actor_critic.Stocha-
solve_car_on_hill () (in module mushroom-
room_rl.solvers.car_on_hill), 140 method), 14

```

```

stop() (mushroom_rl.algorithms.actor_critic.classic_actor_critic) Stochastic Actor-Critic Algorithms 50
method), 15
stop() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.A2C) (mushroom_rl.algorithms.value.td.RQLearning 52
method), 18
stop() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG) (mushroom_rl.algorithms.value.td.SARSA 53
method), 20
stop() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.DDPG) (mushroom_rl.algorithms.value.td.SARSA 54
LambdaContinuous
method), 16
stop() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.PPO) (mushroom_rl.algorithms.value.td.SpeedyQLearning 55
method), 27
stop() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.SAG) (mushroom_rl.algorithms.value.td.TrueOnlineSARSA 56
Lambda
method), 24
stop() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TD3) (mushroom_rl.algorithms.value.td.WeightedQLearning 57
method), 22
stop() (mushroom_rl.algorithms.actor_critic.deep_actor_critic.TRPO) (mushroom_rl.environments.atari.Atari 58
method), 26
stop() (mushroom_rl.algorithms.agent.Agent method), stop() (mushroom_rl.environments.car_on_hill.CarOnHill
method), 85
6
stop() (mushroom_rl.algorithms.policy_search.black_box_optimizations.BGPE) (mushroom_rl.environments.cart_pole.CartPole 59
method), 35
stop() (mushroom_rl.algorithms.policy_search.black_box_optimizations.REPS) (mushroom_rl.environments.dmc_control_env.DMControl 60
method), 37
stop() (mushroom_rl.algorithms.policy_search.black_box_optimizations.RWAE) (mushroom_rl.environments.environment.Environment 61
method), 34
stop() (mushroom_rl.algorithms.policy_search.policy_gradient.eNAC) (mushroom_rl.environments.finite_mdp.FiniteMDP 62
method), 33
stop() (mushroom_rl.algorithms.policy_search.policy_gradient.GROMD) (mushroom_rl.environments.grid_world.AbstractGridWorld 63
method), 31
stop() (mushroom_rl.algorithms.policy_search.policy_gradient.REINFORCE) (mushroom_rl.environments.grid_world.GridWorld 64
method), 29
stop() (mushroom_rl.algorithms.value.batch_td.DoubleFQ) stop() (mushroom_rl.environments.grid_world.GridWorldVanHasselt
method), 58
method), 90
stop() (mushroom_rl.algorithms.value.batch_td.FQI) stop() (mushroom_rl.environments.gym_env.Gym
method), 57
method), 91
stop() (mushroom_rl.algorithms.value.batch_td.LSPI) stop() (mushroom_rl.environments.inverted_pendulum.InvertedPendulum
method), 59
method), 92
stop() (mushroom_rl.algorithms.value.dqn.AveragedDQN) stop() (mushroom_rl.environments.lqr.LQR method), 65
method), 64
stop() (mushroom_rl.algorithms.value.dqn.CategoricalDQN) stop() (mushroom_rl.environments.mujoco.MuJoCo
method), 66
method), 96
stop() (mushroom_rl.algorithms.value.dqn.DoubleDQN) stop() (mushroom_rl.environments.puddle_world.PuddleWorld
method), 63
method), 99
stop() (mushroom_rl.algorithms.value.dqn.DQN) stop() (mushroom_rl.environments.segway.Segway
method), 61
method), 100
stop() (mushroom_rl.algorithms.value.td.DoubleQLearning) stop() (mushroom_rl.environments.ship_steering.ShipSteering
method), 46
method), 101
stop() (mushroom_rl.algorithms.value.td.ExpectedSARSA) SumTree (class in mushroom_rl.utils.replay_memory), 155
method), 41
stop() (mushroom_rl.algorithms.value.td.QLambda
method), 44
stop() (mushroom_rl.algorithms.value.td.QLearning
method), 43
stop() (mushroom_rl.algorithms.value.td.RLearning
method), 49

```

T

Table (class in mushroom_rl.utils.table), 158

TD3 (class in mushroom_rl.algorithms.actor_critic.deep_actor_critic), 20

```

TDPolicy (class in mushroom_rl.policy.td_policy), 126
Tiles (class in mushroom_rl.features.tiles.tiles), 109
to_float_tensor() (in module mushroom_rl.utils.torch), 161
to_int_tensor() (in module mushroom_rl.utils.torch), 162
TorchApproximator (class in mushroom_rl.approximators.parametric.torch_approximator), 70
TorchPolicy (class in mushroom_rl.policy.torch_policy), 132
torque_arrow() (mushroom_rl.utils.viewer.Viewer method), 169
total_p (mushroom_rl.utils.replay_memory.SumTree attribute), 156
TRPO (class in mushroom_rl.algorithms.actor_critic.deep_actor_critic), 24
TrueOnlineSARSALambda (class in mushroom_rl.algorithms.value.td), 54

U
uniform_grid() (in module mushroom_rl.utils.features), 149
unwrapped(mushroom_rl.environments.atari.MaxAndSkip attribute), 82
update() (mushroom_rl.policy.td_policy.Boltzmann method), 129
update() (mushroom_rl.policy.td_policy.EpsGreedy method), 128
update() (mushroom_rl.policy.td_policy.Mellowmax method), 131
update() (mushroom_rl.utils.eligibility_trace.AccumulatingTrace method), 147
update() (mushroom_rl.utils.eligibility_traceReplacingTrace method), 145
update() (mushroom_rl.utils.parameters.ExponentialParameter method), 153
update() (mushroom_rl.utils.parameters.LinearParameter method), 152
update() (mushroom_rl.utils.parameters.Parameter method), 152
update() (mushroom_rl.utils.replay_memory.PrioritizedReplayMemory method), 156
update() (mushroom_rl.utils.replay_memory.SumTree method), 155
update() (mushroom_rl.utils.variance_parameters.VarianceDecreasingParameter method), 165
update() (mushroom_rl.utils.variance_parameters.VarianceIncreasingParameter method), 164
update() (mushroom_rl.utils.variance_parameters.VarianceParameter method), 163
update() (mushroom_rl.utils.variance_parameters.WindowedVarianceIncreasingParameter method), 167

V
update() (mushroom_rl.utils.variance_parameters.WindowedVarianceParameter method), 166
use_cuda (mushroom_rl.policy.torch_policy.BoltzmannTorchPolicy attribute), 139
use_cuda (mushroom_rl.policy.torch_policy.GaussianTorchPolicy attribute), 136
use_cuda (mushroom_rl.policy.torch_policy.TorchPolicy attribute), 133

VarianceDecreasingParameter (class in mushroom_rl.utils.variance_parameters), 164
VarianceIncreasingParameter (class in mushroom_rl.utils.variance_parameters), 164
VarianceParameter (class in mushroom_rl.utils.variance_parameters), 163
Viewer (class in mushroom_rl.utils.viewer), 167

W
WeightedQLearning (class in mushroom_rl.algorithms.value.td), 49
weights_size (mushroom_rl.approximators.parametric.linear.LinearApproximator attribute), 69
weights_size (mushroom_rl.approximators.parametric.torch_approximator.TorchApp attribute), 72
weights_size (mushroom_rl.approximators.regressor.Regressor attribute), 67
weights_size (mushroom_rl.policy.deterministic_policy.DeterministicPolicy attribute), 113
weights_size (mushroom_rl.policy.gaussian_policy.AbstractGaussianPolicy attribute), 116
weights_size (mushroom_rl.policy.gaussian_policy.DiagonalGaussianPolicy attribute), 119
weights_size (mushroom_rl.policy.gaussian_policy.GaussianPolicy attribute), 117
weights_size (mushroom_rl.policy.gaussian_policy.StateLogStdGaussianPolicy attribute), 123
weights_size (mushroom_rl.policy.gaussian_policy.StateStdGaussianPolicy attribute), 121
weights_size (mushroom_rl.policy.gaussian_policy.OrnsteinUhlenbeckPolicy attribute), 125

```

weights_size (mush-
room_rl.policy.policy.ParametricPolicy at-
tribute), 112

WindowedVarianceIncreasingParameter
(class in mushroom_rl.utils.variance_parameters), 166

WindowedVarianceParameter (class in mushroom_rl.utils.variance_parameters), 165

Z

zero_grad() (in module mushroom_rl.utils.torch),
161